

T Mobile

ZONING JURISDICTION:
CITY OF MUKILTEO

SITE ID:
SE01458B

SITE NAME:
WEST BAKERVIEW - SCHLOSSER - SNOPUD

PROJECT TYPE:
REPLACEMENT


SITE LOCATION:
4822 103RD PL SW
MUKILTEO, WA 98275

FSA:
TAEC

LEGAL DESCRIPTION:

KAMIAK NO. 1 BLK 000 D-00 LOT 55 SUBJ TO ESE PUD 1 & GEN TEL

VICINITY MAP



DRIVING DIRECTIONS:

FROM LOCAL T-MOBILE OFFICE (19807 NORTH CREEK PKWY N, BOTHELL, WA 98011)
 1. HEAD SOUTHEAST TOWARD N CREEK PKWY
 2. TURN LEFT TOWARD N CREEK PKWY
 3. TURN LEFT TOWARD N CREEK PKWY
 4. TURN RIGHT ONTO N CREEK PKWY
 5. USE THE RIGHT LANE TO TURN RIGHT ONTO NE 195TH ST
 6. TURN RIGHT TO MERGE ONTO I-405 N TOWARD EVERETT
 7. CONTINUE ONTO WA-525 N
 8. TURN LEFT ONTO HARBOUR POINTE BLVD
 9. TURN RIGHT ONTO 48TH AVE W
 10. TURN LEFT ONTO 103RD PL SW
 11. KEEP LEFT TO STAY ON 103RD PL SW
 12. DESTINATION WILL BE ON THE LEFT

REVIEWERS SHALL CLEARLY PLACE INITIALS ADJACENT TO EACH REDLINE NOTE AS DRAWINGS ARE BEING REVIEWED

APPROVED BY:	DATE:	SIGNATURE:	APPROVED BY:	DATE:	SIGNATURE:
PROJECT MANAGER:			RF ENGINEER:		
SITE ACQUISITION:			OPERATIONS MANAGER:		
ZONING:			DEVELOPMENT MANAGER:		
CONSTRUCTION MANAGER:			REGULATORY:		
CONSTRUCTION MANAGER:					



Know what's
BELOW.
Call before you dig.
www.call811.com

PROJECT LEASE AREA:

120 SF

PARCEL NUMBER:

00650500005500

NEW IMPERVIOUS AREA:

EXISTING: ± 3374 SF
NEW: ± 136 SF

AREA OF PARCEL:

0.26 ACRES

GENERAL INFORMATION:

PARKING REQUIREMENTS ARE UNCHANGED TRAFFIC IS UNAFFECTED
SIGNAGE IS PROPOSED

DRAWING INDEX:

SH #	SHEET DESCRIPTION
T-1	TITLE SHEET
T-2	NOTES & LEGEND
SV1	EXISTING SITE SURVEY
SV1	EXISTING SITE SURVEY
A-1	EXISTING SITE PLAN
A-1.1	FINAL SITE PLAN
A-2	EQUIPMENT PLAN
A-2.1	EQUIPMENT SHELTER ELEVATIONS
A-3	ELEVATIONS
A-4	ELEVATIONS
A-5	DETAILS
A-6	DETAILS
A-7	DETAILS
A-8	HYBRID TRUNK SPECIFICATIONS
M-1	MECHANICAL PLAN & NOTES
M-2	MECHANICAL SPECIFICATIONS
E-1	ELECTRICAL NOTES
E-2	ELECTRICAL SITE PLAN
E-3	PANEL SCHEDULE & ONE-LINE DIAGRAM
E-4	POWER, LIGHTING, & SIGNAL PLAN
G-1	GROUNDING PLANS
G-2	GROUNDING DETAILS
S0.0	GENERAL STRUCTURAL NOTES
S0.1	GENERAL STRUCTURAL NOTES
S1.0	TYPICAL DETAILS
S1.1	TYPICAL DETAILS
S2.0	FOUNDATION AND ROOF FRAMING PLAN
S3.0	FOUNDATION AND ROOF FRAMING DETAILS
L1.0	LANDSCAPE PLAN
L2.0	TREE RETENTION SITE PLAN
L2.1	TREE RETENTION PLAN

PROJECT DESCRIPTION:

T-MOBILE PROPOSES (PER RFDS V1, 03/06/2025) TO MODIFY AN EXISTING UNMANNED TELECOMMUNICATIONS FACILITY WITH:

THE REMOVAL OF:
• PORTION OF EXISTING WOOD FENCE

THE ADDITION OF:
• (1) 10'x12' EQUIPMENT SHELTER
• (2) INDOOR RACKS (1-23", 1-19")
• (2) ASIM IN 19" RACK
• (3) ABIP IN 19" RACK
• (1) AMID IN 19" RACK
• (1) ROUTER IN 19" RACK
• (1) VOLTAGE BOOSTER W/ 2 MODULES AND EXTERNAL AMPLIFIER
• (16) BATTERIES IN 23" RACK
• (2) HYBRID 6x24 AT 50m
• (1) AIR HANDLER
• (1) OUTDOOR CONDENSER
• (1) WOOD ACCESS GATE


PLANS PREPARED BY: _____

Technology Associates

SEATTLE MARKET OFFICE
1455 NW LEARY WAY, STE. 400
SEATTLE, WA 98107

JURISDICTION APPROVAL SEAL: _____

ENGINEERING SEAL: _____



DRAWING NOTICE:
THESE DOCUMENTS ARE CONFIDENTIAL AND ARE THE SOLE PROPERTY OF T-MOBILE AND MAY NOT BE REPRODUCED, DISSEMINATED OR REDISTRIBUTED WITHOUT THE EXPRESS WRITTEN CONSENT OF T-MOBILE.

REVISIONS:	DESCRIPTION	DATE	BY	REV
ISSUED FOR 90% CD		07/30/2025	MGM	A
ISSUED FOR 100%CD		08/13/2025	MGM	0

SITE NAME:
WEST BAKERVIEW - SCHLOSSER - SNOPUD

SITE NUMBER:
SE01458B

SITE ADDRESS:
4822 103RD PL SW
MUKILTEO, WA 98275


SHEET DESCRIPTION:
TITLE SHEET

SHEET NUMBER:
T-1

T Mobile

19807 NORTH CREEK PKWY N
BOTHELL, WA 98011

Technology Associates

SEATTLE MARKET OFFICE
1455 NW LEARY WAY, STE. 400
SEATTLE, WA 98107

THESE DOCUMENTS ARE CONFIDENTIAL
AND ARE THE SOLE PROPERTY OF
T-MOBILE AND MAY NOT BE REPRODUCED,
DISSEMINATED OR REDISTRIBUTED
WITHOUT THE EXPRESS WRITTEN
CONSENT OF T-MOBILE.

REVISIONS:	DESCRIPTION	DATE	BY	REV
ISSUED FOR 90% CD		07/30/2025	MGM	A
ISSUED FOR 100% CD		08/13/2025	MGM	0

WEST BAKERVIEW -
SCHLOSSER - SNOPUD

SE01458B

4822 103RD PL SW
MUKILTEO, WA 98275

NOTES & LEGEND

T-2

GENERAL NOTES

- THIS FACILITY IS EXEMPT FROM HANDICAP REQUIREMENTS PER 2021 INTERNATIONAL BUILDING CODE SECTION 1103.2.9. THIS FACILITY IS NON-OCCUPYABLE SPACE AND ENTERED ONLY BY SERVICE PERSONNEL. THIS SPACE IS NOT FOR HUMAN OCCUPANCY.
- THE CONTRACTOR SHALL VERIFY ALL EXISTING CONDITIONS AND DIMENSIONS PRIOR TO SUBMITTING HIS BID. ANY DISCREPANCIES, CONFLICTS OR OMISSIONS SHALL BE REPORTED TO THE ENGINEER PRIOR TO SUBMITTING BIDS, AND PROCEEDING WITH ANY WORK.
- THE CONTRACTOR SHALL NOTIFY ENGINEER OF ANY ERRORS, OMISSIONS, OR DISCREPANCIES AS THEY MAY BE DISCOVERED IN THE PLANS, SPECIFICATIONS, & NOTES PRIOR TO STARTING CONSTRUCTION, INCLUDING BUT NOT LIMITED BY DEMOLITION. THE CONTRACTOR SHALL BE RESPONSIBLE FOR CORRECTING ANY ERRORS, OMISSION, OR INCONSISTENCY AFTER THE START OF CONSTRUCTION WHICH HAS NOT BEEN BROUGHT TO THE ATTENTION OF THE ARCHITECT/ENGINEER AND SHALL INCUR ANY EXPENSES TO RECTIFY THE SITUATION. THE METHOD OF CORRECTION SHALL BE APPROVED BY THE ARCHITECT OR THE ENGINEER RESPONSIBLE FOR THE PROJECT.
- PRIOR TO STARTING CONSTRUCTION, THE CONTRACTOR HAS THE RESPONSIBILITY TO LOCATE ALL EXISTING UTILITIES, WHETHER OR NOT SHOWN ON THE PLANS, AND TO PROTECT THEM FROM DAMAGE. THE CONTRACTOR OR SUBCONTRACTOR SHALL BEAR THE EXPENSE OF REPAIRING OR REPLACING ANY DAMAGE TO THE UTILITIES CAUSED DURING THE EXECUTION OF THE WORK. CONTACT USA DIG ALERT @ 800-227-2600
- PRIOR TO STARTING CONSTRUCTION, THE CONTRACTOR SHALL PROTECT ALL AREAS FROM DAMAGE WHICH MAY OCCUR DURING CONSTRUCTION. ANY DAMAGE TO PROPOSED OR EXISTING SURFACES, STRUCTURES OR EQUIPMENT SHALL BE IMMEDIATELY REPAIRED OR REPLACED TO THE SATISFACTION OF THE PROPERTY OWNER. THE CONTRACTOR SHALL BEAR THE EXPENSE OF REPAIRING OR REPLACING ANY DAMAGED AREAS.
- A COPY OF THE APPROVED PLANS SHALL BE KEPT IN A PLACE SPECIFIED BY THE GOVERNING AGENCY, AND BY LAW SHALL BE AVAILABLE FOR INSPECTION AT ALL TIMES. IT IS THE CONTRACTOR'S RESPONSIBILITY TO ENSURE ALL CONSTRUCTION SETS REFLECT THE SAME INFORMATION AS THE APPROVED PLANS. THE CONTRACTOR SHALL ALSO MAINTAIN ONE SET OF PLANS AT THE SITE FOR THE PURPOSE OF DOCUMENTING ALL AS-BUILT CHANGES, REVISIONS, ADDENDA, OR CHANGE ORDERS. THE CONTRACTOR SHALL FORWARD THE AS-BUILT/HIRED DRAWINGS TO THE ARCHITECT OR THE ENGINEER RESPONSIBLE OF THE PROJECT AT THE CONCLUSION OF THE PROJECT.
- THE CONTRACTOR SHALL BE RESPONSIBLE FOR THE COMPLETE SECURITY OF THE SITE WHILE THE WORK IS IN PROGRESS UNTIL THE JOB IS COMPLETE.
- THE CONTRACTOR IS RESPONSIBLE TO PROVIDE TEMPORARY POWER, WATER, AND TOILET FACILITIES AS REQUIRED BY THE PROPERTY OWNER OR GOVERNING AGENCY.
- ALL CONSTRUCTION THROUGH THE PROJECT SHALL CONFORM TO THE LATEST I.B.C. AND ALL OTHER GOVERNING CODES, INCLUDING THE MOST RESTRICTIVE CODE SHALL GOVERN.
- THE CONTRACTOR AND SUBCONTRACTOR SHALL COMPLY WITH ALL LOCAL AND STATE REGULATIONS INCLUDING ALL OSHA REQUIREMENTS.
- WHEN REQUIRED STORAGE OF MATERIALS OCCURS, THEY SHALL BE EVENLY DISTRIBUTED OVER THE FLOOR OR ROOF SO AS NOT TO EXCEED THE DESIGNED LIVE LOADS FOR THE STRUCTURE. TEMPORARY SHORING OR BRACING SHALL BE PROVIDED WHERE THE STRUCTURE OR SOIL HAS NOT ATTAINED THE DESIGN STRENGTH FOR THE CONDITIONS PRESENT.
- THE CONTRACTOR SHALL SUPERVISE AND COORDINATE ALL WORK, USING HIS PROFESSIONAL KNOWLEDGE AND SKILLS. HE IS SOLELY RESPONSIBLE FOR ALL CONSTRUCTION MEANS, METHODS, TECHNIQUES, PROCEDURES AND SEQUENCING AND COORDINATING ALL PORTIONS OF THE WORK UNDER THE PROJECT.
- THE CONTRACTOR SHALL BE RESPONSIBLE TO OBTAIN AND PAY FOR ALL PERMITS, LICENSES AND INSPECTIONS WITH RESPECT TO THE WORK TO COMPLETE THE PROJECT. BUILDING PERMIT APPLICATIONS SHALL BE FILED BY THE OWNER OR AUTHORIZED AGENT. CONTRACTOR SHALL OBTAIN THE PERMIT AND MAKE FINAL PAYMENT OF SAID DOCUMENT.
- ALL DIMENSIONS TAKE PRECEDENCE OVER SCALE. DRAWINGS ARE NOT TO BE SCALED UNDER ANY CIRCUMSTANCES.
- THE CONTRACTOR SHALL PROVIDE ALL NECESSARY BLOCKING, BACKING, FRAMING, HANGERS OR SUPPORTS FOR INSTALLATION OF ITEMS INDICATED ON THE DRAWINGS.
- THE CONTRACTOR SHALL PROVIDE THE FIRE MARSHALL OR UL APPROVED MATERIALS TO FILL/SEAL PENETRATIONS THROUGH FIRE RATED ASSEMBLIES.
- PROPOSED CONSTRUCTION ADDED TO EXISTING CONSTRUCTION SHALL BE MATCHED IN FORM, TEXTURE, MATERIAL AND PAINT COLOR EXCEPT AS NOTED IN THE PLANS.
- THE CONTRACTOR IS TO PROVIDE PORTABLE FIRE EXTINGUISHERS HAVING A MINIMUM 2A-10-B:C RATING WITHIN 75FT. OF TRAVEL TO ALL PORTIONS OF THE CONSTRUCTION AREA. (2021 INTERNATIONAL BUILDING CODE 906.1.1 AND SECTION 906.3.1)
- MATERIALS TESTING SHALL BE TO THE LATEST STANDARDS AVAILABLE AS REQUIRED BY THE LOCAL GOVERNING AGENCY RESPONSIBLE FOR APPROVING THE RESULTS.
- ALL GENERAL NOTES AND STANDARD DETAILS ARE THE MINIMUM REQUIREMENTS TO BE USED IN CONDITIONS WHICH ARE NOT SPECIFICALLY SHOWN OTHERWISE.
- ALL DEBRIS AND REFUSE IS TO BE REMOVED FROM THE PROJECT. PREMISES SHALL BE LEFT IN A CLEAN BROOM FINISHED CONDITION AT ALL TIMES.
- BUILDING INSPECTORS AND/OR OTHER BUILDING OFFICIALS ARE TO BE NOTIFIED PRIOR TO ANY GRADING AND CONSTRUCTION EFFORT AS MANDATED BY THE GOVERNING AGENCY.
- ALL SYMBOLS AND ABBREVIATIONS ARE CONSIDERED CONSTRUCTION INDUSTRY STANDARDS. IF A CONTRACTOR HAS A QUESTION REGARDING THEIR EXACT MEANING THE ARCHITECT OR THE ENGINEER RESPONSIBLE OF THE PROJECT SHALL BE NOTIFIED FOR CLARIFICATIONS.
- SITE CONTRACTOR TO CALL DIG ALERT (1-800-227-2600) TO LOCATE ANY AND ALL UNDERGROUND UTILITIES PRIOR TO ANY EXCAVATION.
- ALL FACILITIES TO BE INSTALLED ARE UNMANNED. NO (E) PARKING SPACES WILL BE USED OR REMOVED BY THIS PROJECT.
- PRIOR TO THE ISSUANCE OF ANY CONSTRUCTION PERMITS, THE APPLICANT SHALL INCORPORATE ANY CONSTRUCTION BEST MANAGEMENT PRACTICES NECESSARY TO COMPLY WITH THE CITY'S MUNICIPAL CODES INTO THE CONSTRUCTION PLANS OR SPECIFICATIONS.
- PRIOR TO THE ISSUANCE OF ANY CONSTRUCTION PERMITS, THE APPLICANT SHALL SUBMIT A WATER POLLUTION CONTROL PLAN (WPCC). THE WPCC SHALL BE PREPARED IN ACCORDANCE WITH THE GUIDELINES IN APPENDIX E OF THE CITY'S STORM WATER STANDARDS.
- THIS PROJECT PROPOSES NO DEVELOPMENT IMPROVEMENTS OUTSIDE THE EXISTING BUILDING FOOTPRINT FOR THIS DISCRETIONARY REVIEW AND THEREFORE DOES NOT REQUIRE ANY PERMANENT STORM WATER BEST MANAGEMENT PRACTICES.
- THIS IS ROOFTOP INSTALLATION ON AN EXISTING FACILITY AND NO GROUND DISTURBANCE OR TRENCHING IS PROPOSED BY THIS PROJECT.
- THIS PROJECT PROPOSES NO WORK WITHIN THE PUBLIC RIGHT-OF-WAY.

STORM WATER QUALITY NOTES CONSTRUCTION BMPs:

THIS PROJECT SHALL COMPLY WITH ALL REQUIREMENTS OF THE STATE PERMIT.

NOTES 1-6 BELOW REPRESENT KEY MINIMUM REQUIREMENTS FOR CONSTRUCTION BMPs.

- SUFFICIENT BMPs MUST BE INSTALLED TO PREVENT SILT, MUD OR OTHER CONSTRUCTION DEBRIS FROM BEING TRACKED INTO THE ADJACENT STREET(S) OR STORM WATER CONVEYANCE SYSTEMS DUE TO CONSTRUCTION VEHICLES OR ANY OTHER CONSTRUCTION ACTIVITY. THE CONTRACTOR SHALL BE RESPONSIBLE FOR CLEANING ANY SUCH DEBRIS THAT MAY BE IN THE STREET AT THE END OF EACH WORK DAY OR AFTER A STORM EVENT THAT CAUSES A BREECH IN THE INSTALLED CONSTRUCTION BMPs.
- ALL STOCK PILES OF UN-COMPACTED SOIL AND/OR BUILDING MATERIALS THAT ARE INTENDED TO BE LEFT UNPROTECTED FOR A PERIOD GREATER THAN SEVEN CALENDAR DAYS ARE TO BE PROVIDED WITH EROSION AND SEDIMENT CONTROLS, SUCH SOIL MUST BE PROTECTED EACH DAY WHEN THE PROBABILITY OF RAIN IS 40% OR GREATER.
- A CONCRETE WASHOUT SHALL BE PROVIDED ON ALL PROJECTS WHICH PROPOSE THE CONSTRUCTION OF ANY CONCRETE IMPROVEMENTS THAT ARE TO BE POURED IN PLACE ON THE SITE.
- ALL EROSION/SEDIMENT CONTROL DEVICES SHALL BE MAINTAINED IN WORKING ORDER AT ALL TIMES.
- ALL SLOPES THAT ARE CREATED OR DISTURBED BY CONSTRUCTION ACTIVITY MUST BE PROTECTED AGAINST EROSION AND SEDIMENT TRANSPORT AT ALL TIMES.
- THE STORAGE OF ALL CONSTRUCTION MATERIALS AND EQUIPMENT MUST BE PROTECTED AGAINST ANY POTENTIAL RELEASE OF POLLUTANTS INTO THE ENVIRONMENT.


GENERAL FIRE NOTES:

- BUILDINGS UNDERGOING CONSTRUCTION, ALTERATION, OR DEMOLITION SHALL BE IN ACCORDANCE WITH 2021 INTERNATIONAL BUILDING CODE AND ALL GOVERNING CODES.
- ADDRESS SHALL BE PROVIDED FOR ALL PROPOSED AND EXISTING BUILDINGS IN A POSITION AS TO BE PLAINLY VISIBLE AND LEGIBLE FROM THE STREET OR ROAD FRONTING THE PROPERTY. (2021 INTERNATIONAL BUILDING CODE 501.2)
- DECORATIVE MATERIALS SHALL BE MAINTAINED IN A FLAME-RETARDANT CONDITION. (2021 INTERNATIONAL BUILDING CODE 806.1)
- PORTABLE FIRE EXTINGUISHERS: AT LEAST ONE FIRE EXTINGUISHER WITH A MINIMUM RATING OF 2-A-10-B:C SHALL BE PROVIDED WITHIN 75 FEET MAXIMUM TRAVEL DISTANCE FOR EACH 6,000 SQUARE FEET OR PORTION THEREOF ON EACH FLOOR. (2021 INTERNATIONAL BUILDING CODE 906.1.1 AND SECTION 906.3.1)

LANDLORD SIGNATURE

ABBREVIATION	DEFINITION	ABBREVIATION	DEFINITION	ABBREVIATION	DEFINITION
AB	ANCHOR BOLT	EXP	EXPANSION	P/C	PRECAST CONCRETE
ABV	ABOVE	EXT (E)	EXISTING	PCS	PERSONAL COMMUNICATION SERVICES
ACCA	ANTENNA CABLE COVER ASSEMBLY	EXT	EXTERIOR	PLY	PLYWOOD
ADD'L	ADDITIONAL	FAB	FABRICATION(OR)	PPC	POWER PROTECTION CABINET
AFF	ABOVE FINISHED FLOOR	FF	FINISH FLOOR	PRC	PRIMARY RADIO CABINET
AFG	ALUMINUM	FG	FINISH GRADE	PSF	POUNDS PER SQUARE FOOT
ALU	ALUMINUM	FIN	FINISH(ED)	PSI	POUNDS PER SQUARE INCH
ALT	ALTERNATE	FLR	FLOOR	PT	PRESSURE TREATED
ANT	ANTENNA	FDN	FOUNDATION	PWR	POWER (CABINET)
APPRX	APPROXIMATE(LY)	FOM	FACE OF CONCRETE	QTY	QUANTITY
ARCH	ARCHITECT(URAL)	FOS	FACE OF MASONRY	RAD (R)	RADIUS
AWG	AMERICAN WIRE GAUGE	FOW	FACE OF WALL	REF	REFERENCE
BLDG	BUILDING	FS	FINISH SURFACE	REINF	REINFORCEMENT(ING)
BLK	BLOCK	FT (')	FOOT (FEET)	REQ'D	REQUIRED
BLKG	BLOCKING	FTG	FOOTING	RGS	RIGID GALVANIZED STEEL
BM	BEAM	G	GROWTH (CABINET)	RRU	RADIO REMOTE UNIT
BN	BOUNDARY NAILING	GA	GAUGE	SCH	SCHEDULE
BTCW	BARE TINNED COPPER WIRE	GI	GALVANIZE(D)	SHT	SHEET
BOF	BOTTOM OF FOOTING	GFI	GROUND FAULT CIRCUIT INTERRUPTER	SIM	SIMILAR
B/U	BACK-UP CABINET	GLB (GLU-LAM)	GLULAM (LAMINATED BEAM)	SPEC	SPECIFICATION(S)
CAB	CABINET	GPS	GLOBAL POSITIONING SYSTEM	SO	SOLID
CANT	CANTILEVERED	GRND	GROUND	SS	STAINLESS STEEL
CP	CAST IN PLACE	HDR	HEADER	STD	STANDARD
CLG	CEILING	HGR	HANGER	STRUC	STRUCTURAL
CLR	CLEAR	HT	HEIGHT	TEMP	TEMPORARY
COL	COLUMN	ICGB	ISOLATED COPPER GROUND BUS	THK	THICKNESS
CONC	CONCRETE	IN (")	INCH(E)	TMA	TOWER MOUNTED AMPLIFIER
CONN	CONNECTION(OR)	INT	INTERIOR	TN	TOE NAIL
CONST	CONSTRUCTION	LB (#)	POUND(S)	TOA	TOP OF ANTENNA
CONT	CONTINUOUS	LB	LAG BOLTS	TOC	TOP OF CURB
d	PENNY (NAILS)	LF	LINEAR FEET (FOOT)	TOF	TOP OF FOUNDATION
DBL	DOUBLE	L	LONG(TUDINAL)	TOP	TOP OF PLATE (PARAPET)
DEPT	DEPARTMENT	MAS	MASONRY	TOS	TOP OF STEEL
DF	DOUGLAS FIR	MAX	MAXIMUM	TOW	TOP OF WALL
DIA	DIAMETER	MB	MACHINE BOLT	TYP	TYPICAL
DIAG	DIAGONAL	MECH	MECHANICAL	UG	UNDER GROUND
DIM	DIMENSION	MFR	MANUFACTURER	UL	UNDERWRITERS LABORATORY
DWG	DRAWING(S)	MIN	MINIMUM	UNO	UNLESS NOTED OTHERWISE
DWL	DOWEL(S)	MISC	MISCELLANEOUS	VIF	VERIFY IN FIELD
EA	EACH	MTL	METAL	W	WIDE (WIDTH)
EL	ELEVATION	(N)	NEW	W/	WITH
ELEC	ELECTRICAL	NTS	NUMBER	WD	WOOD
ELEV	ELEVATOR	NOT TO SCALE	NOT TO SCALE	WP	WEATHERPROOF
EMT	ELECTRICAL METALLIC TUBING	OC	ON CENTER	WT	WEIGHT
EN	EDGE NAIL	OPNG	OPENING	¶	CENTERLINE PLATE
ENG	ENGINEER				
EQ	EQUAL				

ABBREVIATIONS



1

LEGEND

—	SUBJECT BOUNDARY LINE
— — —	RIGHT-OF-WAY CENTERLINE
— — —	RIGHT-OF-WAY LINE
— — —	ADJACENT BOUNDARY LINE
— — —	SECTIONAL BREAKDOWN LINE
— — —	EASEMENT LINE
— DP	OVERHEAD POWER LINE
— UP	BURIED POWER LINE
— UT	BURIED TELEPHONE LINE
— DITCH	DITCH LINE/FLOW LINE
— — —	ROCK RETAINING WALL
— — —	VEGETATION LINE
— — —	WOOD FENCE
♂	UTILITY POLE
—	GUY ANCHOR
COM	COMM. VAULT
□	TEL. PEDESTAL
234.21	SPOT ELEVATION


CAUTION!

UNDERGROUND UTILITIES
EXIST IN THE AREA AND
UTILITY INFORMATION SHOWN
MAY BE INCOMPLETE. STATE
LAW REQUIRES THAT
CONTRACTOR CONTACT THE
ONE-CALL UTILITY LOCATE
SERVICE AT LEAST 48 HOURS
BEFORE STARTING ANY
CONSTRUCTION.



Know what's below.
Call before you dig.

GRAPHIC SCALE



NOTE:
1. ALL ELEVATIONS SHOWN ARE ABOVE MEAN SEA LEVEL
(AMSL) AND ARE REFERENCED TO THE NAVD88 DATUM.
2. ALL TOWER, TREE AND APPURTENANCE HEIGHTS ARE
ABOVE GROUND LEVEL (AGL) AND ARE ACCURATE TO
± 0.5 FEET OR ± 1% OF TOTAL HEIGHT, WHICHEVER IS
GREATER.

TREE LEGEND

DECIDUOUS TREE	JMP=JAPANESE MAPLE
	DS=DECIDUOUS
AL12	TRUNK DIAMETER (IN)
TYPE	
EVERGREEN TREE	CE=CEDAR
	DF=DOUGLAS FIR
DF18	ST=STUMP
195.2	HEIGHT AGL IF MEASURED

NOTE:
TREE DRIP LINES ARE NOT TO SCALE. TREE SYMBOLS
REFERENCE TRUNK LOCATION ONLY. TRUNK DIAMETERS
WERE APPROXIMATED AT 3.5' TO 4' ABOVE GROUND LEVEL.
TREES SHOWN ARE FOR REFERENCE ONLY AND OTHER
TREES AND VEGETATION MAY EXIST.


LATITUDE/LONGITUDE POSITION

COORDINATE DATA AT CENTER OF EXISTING UTILITY POLE:
NAD 83/91


LAT - 47°54'16.20" N
LONG - 122°17'58.69" W

NAVD 88
ELEV= 483.2 FEET

LAT - 47.904500° N
LONG - 122.299636° W




BENCHMARK IS BASED ON
WSRN PUGET SOUND
REFERENCE NETWORK.
ELEVATION DERIVED USING
GPS. ACCURACY MEETS OR
EXCEEDS 1A STANDARDS AS
DEFINED ON THE FAA ASAC
INFORMATION SHEET 91:003



T-Mobile®

Technology Associates



DUNCANSON
Company, Inc.
145 SW 155th Street, Suite 102
Seattle, Washington 98166
Phone 206.244.4141
Fax 206.244.4555


SITE
SE01458B
WEST BAKERVIEW
SNOPUD
4822 103RD PL SW
MUKILTEO, WA 98275
SNOHOMISH COUNTY

THIS DRAWING WAS CREATED FOR THE
EXCLUSIVE USE OF THE CLIENT NAMED HEREON,
AND IS NOT TO BE USED IN WHOLE OR IN PART
WITHOUT WRITTEN AUTHORIZATION FROM
SAID CLIENT.
© 2024 DUNCANSON COMPANY, INC.

FIELD CREW: CR
FIELD BOOK: 642/26
DRAWN BY: DAS
JOB #: 01808.1940
DATE: 10/16/2024

REVISIONS

DATE	DESCRIPTION	BY
-	-	-
-	-	-
-	-	-
-	-	-



SHEET TITLE
EXISTING SITE SURVEY
SEC 21, TWP 28 N, RNG 4 E, WM

SHEET NUMBER
SV2

T Mobile

19807 NORTH CREEK PKWY N
BOTHELL, WA 98011


PLANS PREPARED BY: ■

Technology Associates

SEATTLE MARKET OFFICE
1455 NW LEARY WAY, STE. 400
SEATTLE, WA 98107

JURISDICTION APPROVAL S

ENGINEERING SEAL:



DRAWING NOTICE: 
THESE DOCUMENTS ARE CONFIDENTIAL
AND ARE THE SOLE PROPERTY OF
T-MOBILE AND MAY NOT BE REPRODUCED,
DISSEMINATED OR REDISTRIBUTED
WITHOUT THE EXPRESS WRITTEN
CONSENT OF **T-MOBILE**.

SITE NAME: WEST BAKERVIEW -

— 10 —

SITE ADDRESS:

SHEET DESCRIPTION: _____

SHEET NUMBER: ■

A-


103RD PL SW

LANDLORD SIGNATURE

NOTE: THE ORIGINAL SIZE OF THIS PLAN IS 24" X 36". SCALE RATIO IS NOT VALID FOR REDUCED OR ENLARGED SHEET SIZES

EXISTING SITE PLAN

HARBOUR POINTE BLVD. C



A scale bar and registration marks for a 10' x 10' grid. The scale bar is marked at 10', 0', 5', and 10'. The registration marks consist of a 2x4 grid of black and white squares. To the right of the scale bar is a table with the following data:

SCALE: 1" = 10'-0" (24x36)
(OR) 1/2" = 10'-0" (11x17)

A large number '1' is positioned at the far right end of the scale bar.

1

T Mobile

19807 NORTH CREEK PKWY N
BOTHELL, WA 98011

Technology Associates

SEATTLE MARKET OFFICE
1455 NW LEARY WAY, STE. 400
SEATTLE, WA 98107

DRAWING NOTICE:
THESE DOCUMENTS ARE CONFIDENTIAL
AND ARE THE SOLE PROPERTY OF
T-MOBILE AND MAY NOT BE REPRODUCED,
DISSEMINATED OR REDISTRIBUTED
WITHOUT THE EXPRESS WRITTEN
CONSENT OF T-MOBILE.

REVISIONS:	DESCRIPTION	DATE	BY	REV
ISSUED FOR 90% CD		07/30/2025	MGM	A
ISSUED FOR 100% CD		08/13/2025	MGM	0

SITE NAME:
WEST BAKERVIEW -
SCHLOSSER - SNOPUD


SITE NUMBER:
SE01458B

SITE ADDRESS:
4822 103RD PL SW
MUKILTEO, WA 98275

SHEET DESCRIPTION:
FINAL SITE PLAN

SHEET NUMBER:

A-1.1



T Mobile

19807 NORTH CREEK PKWY N
BOTHELL, WA 98011

LANDLORD SIGNATURE


GROUND: FINAL EQUIPMENT INVENTORY

SCOPE OF WORK	QUANTITY	TECHNOLOGY	MANUFACTURER	EQUIPMENT MODEL	DIMENSIONS (LxWxD)	WEIGHT (LBS)	CABINET TYPE (LOCATION OF EQUIPMENT)	CABINET QUANTITY
ADD NEW	(1)	CAMLOCK	PANTROL	PANLOC LITE	10.5" x 9.0" x 9.25"	-	ON WALL	-
ADD NEW	(1)	PPC/DISCONNECT	RAYCAP	RTMAC-2465-P-240-MTS	39"X22.855"X12.593"	80	ON WALL	-
ADD NEW	(1)	ROUTER	NOKIA	CSR IXR-e V2	1.75" x 17.25" x 10.0"	8.5	19" RACK	1
ADD NEW	(1)	RACK	DELTA	TITAN RACK 19"	21.88"x84"x23"	147	ON SLAB	-
ADD NEW	(1)	RACK	DELTA	ESAA600AHCU03	24.7"x84"x22.6"	250	ON SLAB	-
ADD NEW	(16)	BATTERIES	POWERSAFE	SBS 190F	22.1" x 4.9" x 12.4"	132.3	23" RACK	1
ADD NEW	(2)	BASEBAND	NOKIA	ASIM	1.89" x 8.62" x 14.84"	6.39	19" RACK	1
ADD NEW	(3)	BASEBAND	NOKIA	ABIP	0.98" x 8.62" x 14.33"	4.41	19" RACK	1
ADD NEW	(1)	BASEBAND	NOKIA	AMID	5.08" x 17.60" x 15.75"	11.68	19" RACK	1
ADD NEW	(1)	VOLTAGE BOOSTER	RAYCAP	POWERPLUS 103-1-1U	17.6" x 13.5" x 1.7"	2.1	19" RACK	1

BATTERY NOTES:

MAXIMUM OF (4) STRINGS OF (4) (16 BATTERIES TOTAL) OF VALVE REGULATED LEAD ACID BATTERIES (VRLA) MODEL POWERSAFE SBS 190F WITH IMMOBILIZED ELECTROLYTE TECHNOLOGY. TOTAL CAPACITY 36.48 KWH. COMPLIANCE WITH 2021 INTERNATIONAL FIRE CODE SECTION 1207.1.1 ENERGY STORAGE THRESHOLD QUANTITIES IS NOT REQUIRED.


NOTE:
1. NEW GABLE ROOF T-MOBILE EQUIPMENT SHELTER TO MATCH BUILDING IN FRONT AND SIMILAR ROOFING. SEE EQUIPMENT SHELTER ELEVATIONS FOR MORE INFORMATION.



PLANS PREPARED BY:
Technology Associates

SEATTLE MARKET OFFICE
1455 NW LEARY WAY, STE. 400
SEATTLE, WA 98107

JURISDICTION APPROVAL SEAL:



DRAWING NOTICE:
THESE DOCUMENTS ARE CONFIDENTIAL AND ARE THE SOLE PROPERTY OF T-MOBILE AND MAY NOT BE REPRODUCED, DISSEMINATED OR REDISTRIBUTED WITHOUT THE EXPRESS WRITTEN CONSENT OF T-MOBILE.

REVISIONS:	DESCRIPTION	DATE	BY	REV
ISSUED FOR 90% CD		07/30/2025	MGM	A
ISSUED FOR 100%CD		08/13/2025	MGM	0

SITE NAME:
WEST BAKERVIEW - SCHLOSSER - SNOPUD

SITE NUMBER:
SE01458B

SITE ADDRESS:
4822 103RD PL SW
MUKILTEO, WA 98275


SHEET DESCRIPTION:
EQUIPMENT PLAN

SHEET NUMBER:
A-2

T Mobile

19807 NORTH CREEK PKWY N
BOTHELL, WA 98011

LANDLORD SIGNATURE



SHELTER SOUTH ELEVATION

3


SCALE
N.T.S.

SHELTER EAST ELEVATION

1

0 6" 1' 2' SCALE: 1/2" = 1'-0" (24x36)
(OR) 1/4" = 1'-0" (11x17)

NOTE: 1. NEW GABLE ROOF T-MOBILE EQUIPMENT SHELTER TO MATCH BUILDING IN FRONT AND SIMILAR ROOFING.



SHELTER NORTH ELEVATION

4


SCALE
N.T.S.

SHELTER WEST ELEVATION

2

0 6" 1' 2' SCALE: 1/2" = 1'-0" (24x36)
(OR) 1/4" = 1'-0" (11x17)

NOTE: 1. NEW GABLE ROOF T-MOBILE EQUIPMENT SHELTER TO MATCH BUILDING IN FRONT AND SIMILAR ROOFING.



SHEET NUMBER:

A-2.1


PLANS PREPARED BY:

Technology Associates

SEATTLE MARKET OFFICE
1455 NW LEARY WAY, STE. 400
SEATTLE, WA 98107

JURISDICTION APPROVAL SEAL:

ENGINEERING SEAL:



DRAWING NOTICE:

THESE DOCUMENTS ARE CONFIDENTIAL AND ARE THE SOLE PROPERTY OF T-MOBILE AND MAY NOT BE REPRODUCED, DISSEMINATED OR REDISTRIBUTED WITHOUT THE EXPRESS WRITTEN CONSENT OF T-MOBILE.

REVISIONS:

DESCRIPTION DATE BY REV

ISSUED FOR 90% CD 07/30/2025 MGM A

ISSUED FOR 100% CD 08/13/2025 MGM 0

SITE NAME:
WEST BAKERVIEW - SCHLOSSER - SNOPUD

SITE NUMBER:

SE01458B

SITE ADDRESS:


4822 103RD PL SW
MUKILTEO, WA 98275SHEET DESCRIPTION:
EQUIPMENT SHELTER ELEVATIONS

SHEET NUMBER:

T Mobile

19807 NORTH CREEK PKWY N
BOTHELL, WA 98011

Technology Associates

SEATTLE MARKET OFFICE
1455 NW LEARY WAY, STE. 400
SEATTLE, WA 98107

DRAWING NOTICE:
THESE DOCUMENTS ARE CONFIDENTIAL
AND ARE THE SOLE PROPERTY OF
T-MOBILE AND MAY NOT BE REPRODUCED,
DISSEMINATED OR REDISTRIBUTED
WITHOUT THE EXPRESS WRITTEN
CONSENT OF T-MOBILE.

DESCRIPTION	DATE	BY	REV
ISSUED FOR 90% CD	07/30/2025	MGM	A
ISSUED FOR 100%CD	08/13/2025	MGM	0

SITE NAME: WEST BAKERVIEW - SCHLOSSER - SNOPUD

SITE NUMBER: SE01458B


SITE ADDRESS: 4822 103RD PL SW
MUKILTEO, WA 98275

SHEET DESCRIPTION: ELEVATIONS

SHEET NUMBER: A-3

LANDLORD SIGNATURE

DISCLAIMER:
1. NO CHANGES PROPOSED AT
EXISTING POLE OTHER THAN
CONNECTING NEW CABLING FROM
POLE TO NEW GROUND
EQUIPMENT LOCATION. ANTENNAS,
RADIOS, AND ANCILLARY
EQUIPMENT TO REMAIN
UNCHANGED.



SOUTH ELEVATION (EXISTING)


0 2' 4' 8' SCALE: 1/8" = 1'-0" (24x36)
(OR) 1/16" = 1'-0" (11x17)

1

SOUTH ELEVATION (FINAL)

0 2' 4' 8' SCALE: 1/8" = 1'-0" (24x36)
(OR) 1/16" = 1'-0" (11x17)

2



SHEET NUMBER: A-3


T Mobile

19807 NORTH CREEK PKWY N
BOTHELL, WA 98011

LANDLORD SIGNATURE

DISCLAIMER:

1. NO CHANGES PROPOSED AT EXISTING POLE OTHER THAN CONNECTING NEW CABLING FROM POLE TO NEW GROUND EQUIPMENT LOCATION. ANTENNAS, RADIOS, AND ANCILLARY EQUIPMENT TO REMAIN UNCHANGED.



NOTE: THE ORIGINAL SIZE OF THIS PLAN IS 24" X 36". SCALE RATIO IS NOT VALID FOR REDUCED OR ENLARGED SHEET SIZES

EAST ELEVATION (EXISTING)


0' 2' 4' 8' SCALE: 1/8" = 1'-0" (24x36)
(OR) 1/16" = 1'-0" (11x17)

1

EAST ELEVATION (FINAL)

0' 2' 4' 8' SCALE: 1/8" = 1'-0" (24x36)
(OR) 1/16" = 1'-0" (11x17)

2



PLANS PREPARED BY:

Technology Associates

SEATTLE MARKET OFFICE
1455 NW LEARY WAY, STE. 400
SEATTLE, WA 98107

JURISDICTION APPROVAL SEAL:



DRAWING NOTICE:

THESE DOCUMENTS ARE CONFIDENTIAL AND ARE THE SOLE PROPERTY OF T-MOBILE AND MAY NOT BE REPRODUCED, DISSEMINATED OR REDISTRIBUTED WITHOUT THE EXPRESS WRITTEN CONSENT OF T-MOBILE.

REVISIONS:

DESCRIPTION	DATE	BY	REV
ISSUED FOR 90% CD	07/30/2025	MGM	A
ISSUED FOR 100% CD	08/13/2025	MGM	0

SITE NAME:

WEST BAKERVIEW - SCHLOSSER - SNOPUD

SITE NUMBER:

SE01458B

SITE ADDRESS:

4822 103RD PL SW
MUKILTEO, WA 98275

SHEET DESCRIPTION:

ELEVATIONS


SHEET NUMBER:

A-4

T Mobile

19807 NORTH CREEK PKWY N
BOTHELL, WA 98011

LANDLORD SIGNATURE




NOTES:

1. PLACE SIGN ON LOCATION BY COMPLIANCE SPECIFICATIONS (PROVIDED BY T-MOBILE).
2. CONTRACTOR TO PROCURE FCC NO. FROM COMPLIANCE COORDINATOR.
3. TEXT FOR SIGNAGE SHALL INDICATE CORRECT SITE NAME AND NUMBER.
4. SIGNS DISPLAYED ON SHEET SHALL BE PLACED ON T-MOBILE COMPOUND ONLY.
5. FOR ADDITIONAL INFORMATION AND PLACEMENT, SEE NOTES UNDER SIGN.

NOTES:

1. CONTRACTOR SHALL FIELD VERIFY ALL CABLE LADDER LENGTHS, PRIOR TO INSTALLATION.
2. ALL CUT ENDS OF CABLE LADDER TO BE FILED SMOOTH AND PAINTED WITH MATCHING COLOR.
3. BOTTOM OF CABLE LADDER TO BE 7'-6" ABOVE FINISH FLOOR, UNLESS NOTED OTHERWISE.
4. CORNER BRACKETS TO BE ON THE INSIDE, UNLESS LADDER RUNGS INTERFERE, THEN CORNER BRACKETS MAY BE ON THE OUTSIDE.
5. CABLE LADDER RUNGS TO BE ON TOP OF HORIZONTAL LADDER AND AWAY FROM WALL ON VERTICAL LADDERS.
6. NUTS TO BE ON BOTTOM OF ASSEMBLY, OR TOWARDS WALL.
7. 5/8" THREADED RODS, SUPPORTING CABLE LADDER, SPACED 6'-0" APART.
8. AFTER FINAL LEVELING OF CABLE LADDER CUT ROD SO THAT 1/2" OF THE THREADS ARE EXPOSED BELOW THE NUT, CAP EACH OCCURRENCE WITH PROPERLY SIZED VINYL VOLT CAPS.
9. ANCHOR ALL ENDS OF CABLE LADDER TO WALL.
10. INSTALL UNISTRUT AS REQUIRED, OTHERWISE ATTACHED DIRECTLY TO CEILING.
11. ENSURE NEW BLOCKING IS INSTALLED IN WALL AND CEILING TO ACCEPT LAG SCREWS AND OTHER EMBEDMENT REQUIREMENTS.



NOT USED

SCALE
N.T.S.

10

SIGNAGE

SCALE
N.T.S.

7

CABLE LADDER


SCALE
N.T.S.

1


RAB | OUTDOOR SERVICE LIGHT: X34-35L/120

DIMENSIONS:
DRIVER INFO:
TYPE:
120V:
INPUT WATTS:
LED INFO:
WATTS:
COLOR TEMP:
COLOR ACCURACY:
L70 LIFESPAN:
LUMENS:
EFFICACY:

6-1/8" x 5-3/4" x 1-5/8" (FLOODLIGHT)
CONSTANT CURRENT
0.3A
34.10W
35.00W
5000K (COOL)
85 CRI
50,000
3,501
102.7 LPW





ELEVATIONS




NOTES:

1. PLACE SIGN ON LOCATION BY COMPLIANCE SPECIFICATIONS (PROVIDED BY T-MOBILE).
2. CONTRACTOR TO PROCURE FCC NO. FROM COMPLIANCE COORDINATOR.
3. TEXT FOR SIGNAGE SHALL INDICATE CORRECT SITE NAME AND NUMBER.
4. SIGNS DISPLAYED ON SHEET SHALL BE PLACED ON T-MOBILE COMPOUND ONLY.
5. FOR ADDITIONAL INFORMATION AND PLACEMENT, SEE NOTES UNDER SIGN.



NOTES:

1. LEAN CONCRETE RED-COLORED TOP, MAY BE USED IN PLACE OF COMPACTED SAND.
2. BURY CONDUITS 36" MINIMUM BELOW FINISHED GRADE.
3. ALL PVC SWEEPS TO BE A MINIMUM 36" SWEEPS.



SERVICE LIGHT

SCALE
N.T.S.

11

INSTRUCTIONAL & NOTICE SIGN

SCALE
N.T.S.

8

CONDUIT TRENCH

SCALE
N.T.S.

5


CONDUIT STUB-UP

SCALE
N.T.S.

2


MSFDS - MSF-LLCM-E16S

MANUFACTURE: MSFDS
MODEL: MSF-LLCM-E16S
MATERIAL: ALUMINUM
ENCLOSURE DIMENSIONS, HxWxD: 12" x 8" x 6" (304.8 x 203.2 x 152.4 mm)
METER DIMENSIONS: 6 15/16" DIA. - 5" HEIGHT
GENERATOR INTERFACE: CAM LOCK/APPLETON
MOUNTING OPTIONS: WALL, POLE, OR CABINET MOUNT




NOTES:

1. PLACE SIGN ON LOCATION BY COMPLIANCE SPECIFICATIONS (PROVIDED BY T-MOBILE).
2. CONTRACTOR TO PROCURE FCC NO. FROM COMPLIANCE COORDINATOR.
3. TEXT FOR SIGNAGE SHALL INDICATE CORRECT SITE NAME AND NUMBER.
4. SIGNS DISPLAYED ON SHEET SHALL BE PLACED ON T-MOBILE COMPOUND ONLY.
5. FOR ADDITIONAL INFORMATION AND PLACEMENT, SEE NOTES UNDER SIGN.



ANCHORAGE USE:
@ WOOD: 1/2"Ø LAG SCREWS WITH 2" MIN. EMBED.
@ CONCRETE: 1/2"Ø HILTI KB-TZ WITH 2" EMBED. (ICC-ESR#1917)
@ CMU: 1/2"Ø HILTI KB3 WITH 2-1/4" MIN. EMBED. (ICC-ESR#1385)
@ METAL: #10 SIMPSON SELF-DRILLING TAPPING SCREW (ICC-ESR#3006)
IF THRU-BOLTED: 1/2"Ø A307 THRU-BOLTS AND NUTS.



NOTE: ANCHORAGE OCCURS AT EACH CORNER OF THE RACK

METER SPECIFICATIONS

SCALE
N.T.S.

12

CAUTION SIGN

SCALE
N.T.S.

9

UNISTRUT MOUNTING

SCALE
N.T.S.

6


RACK ANCHOR DETAIL

SCALE
N.T.S.

3

A-5

Technology Associates

SEATTLE MARKET OFFICE
1455 NW LEARY WAY, STE. 400
SEATTLE, WA 98107

THESE DOCUMENTS ARE CONFIDENTIAL AND ARE THE SOLE PROPERTY OF T-MOBILE AND MAY NOT BE REPRODUCED, DISSEMINATED OR REDISTIBUTED WITHOUT THE EXPRESS WRITTEN CONSENT OF T-MOBILE.

DESCRIPTION	DATE	BY	REV
ISSUED FOR 90% CD	07/30/2025	MGM	A
ISSUED FOR 100%CD	08/13/2025	MGM	0

WEST BAKERVIEW - SCHLOSSER - SNOPUD

SE01458B

4822 103RD PL SW
MUKILTEO, WA 98275


DETAILS

A-5

T Mobile

19807 NORTH CREEK PKWY N
BOTHELL, WA 98011

Technology Associates

SEATTLE MARKET OFFICE
1455 NW LEARY WAY, STE. 400
SEATTLE, WA 98107

DRAWING NOTICE:
THESE DOCUMENTS ARE CONFIDENTIAL
AND ARE THE SOLE PROPERTY OF
T-MOBILE AND MAY NOT BE REPRODUCED,
DISSEMINATED OR REDISTRIBUTED
WITHOUT THE EXPRESS WRITTEN
CONSENT OF T-MOBILE.

REVISIONS:	DESCRIPTION	DATE	BY	REV
ISSUED FOR 90% CD		07/30/2025	MGM	A
ISSUED FOR 100% CD		08/13/2025	MGM	0


SITE NAME:	WEST BAKERVIEW - SCHLOSSER - SNOPUD
SITE NUMBER:	SE01458B

SITE ADDRESS:	4822 103RD PL SW MUKILTEO, WA 98275
---------------	--

SHEET DESCRIPTION:	DETAILS
--------------------	---------

SHEET NUMBER:	A-6
---------------	-----

LANDLORD SIGNATURE



NOT USED

SCALE
N.T.S.

10 FPKA BRACKET DETAIL

7

SCALE
N.T.S.


DELTA 23" 700A POWER RACK

1

SCALE
N.T.S.

DELTA: ELITE POWER -48V 700A

INDOOR RACK MOUNTED POWER SYSTEM
48V/600A RACK (23") MOUNTED POWER SYSTEM
SLIMLINE HIGH POWER / EFFICIENCY DPR2900 RECTIFIERS
7" HIGH 2 POST RELAY RACK W/ 4 BATTERY TRAYS



Model	Elite Power Rack 48V 700A
1. Input	Single phase, 240+PE (L1, L2/N, FG) 110 - 240VAC
AC Voltage	Single phase, 50VDC (def)
AC Current	Single phase, 32A each (6) / 190A total (max)
AC Frequency	50 - 60Hz
2. Output	
Output Voltage	42 - 56VDC, 54VDC (def)
Output Current	600A @ 54V
Power Limitation	32.4kW @ 54V
Voltage Regulation	±1% over line, load, and temperature
Current Sharing	±5% of the full capacity of the rectifier
3. General	
Rectifier	DPR 2900C-48, up to 96.3% efficiency, 12k
Controller	Orion Touch
Battery	4 Trays, 190AH
Dimensions (W x H x D)	24.7" x 94" x 22.6"
Weight	250 Lbs
4. Standards	
Safety	IEC / EN 60950, UL1801, UL1900
EMC	NEBS (GR-108G)
Operating Temperature	-40°C to +75°C (-40°F to +167°F)
Humidity (relative)	95%, non-condensing (Max.)
Environment	NEBS Level 3 (earthquake zone 4)
5. Equipment	
Load Cable Entry	Front access
Circuit Breakers and	26x -48V, 100A max. per position, 1/4"-20, 5/8" center to center
Landings	
Fuse Module (optional)	10 position GMT 15A max/position 110A max. total
Battery Landings	(6) 1/2" holes - 5/8" center to center, (4) 1/2" holes - 1" center to center
Low Voltage Disconnect	Battery LVD included
6. Ordering Information	
System	E8AA600AHCU03 Elite Power Rack, 7", -48V 600A, (4) Battery Trays including (10) Rectifiers
Rectifier	E8R-48/6C F-A 48V / 56A 2900W, 96.4%, CAN communication
GMT Module (optional)	379290000-S 10 pos. plug-in module takes 2 positions
Load Breaker	0830xxxxxx Breaker, Bullet, Mid-Trip, 5A - 250A
Load Breaker Adapter	379235700-S 2 Pole Lug Adapter Kit (125A-200A)
	379236400-S 3 Pole Lug Adapter Kit (250A)

NOT USED

SCALE
N.T.S.

11 VOLTAGE BOOSTER

8

SCALE
N.T.S.

AMID

5

SCALE
N.T.S.

DELTA 19" RACK

2

NOT USED

SCALE
N.T.S.

POWERSAFE: SBS 190F

8

SCALE
N.T.S.

NOKIA: AIRSCALE CAPACITY UNIT (ABIP)

8

5

2

NOT USED

SCALE
N.T.S.

NOKIA: AIRSCALE CONTROL UNIT (ASIM)

8

SCALE
N.T.S.

NOKIA: AIRSCALE CONTROL UNIT (ASIM)

8

5

NOT USED

SCALE
N.T.S.

ABIP

9

SCALE
N.T.S.

ASIM

6

SCALE
N.T.S.

ASIM

3

NOT USED

SCALE
N.T.S.

BATTERY SPECIFICATIONS

12

SCALE
N.T.S.

ASIM

9

SCALE
N.T.S.

ASIM

3

NOT USED

SCALE
N.T.S.

DELTA: ELITE POWER -48V 700A

10

SCALE
N.T.S.

ASIM

10

SCALE
N.T.S.

ASIM

10

NOT USED

SCALE
N.T.S.

TITAN RACK 19"

11

SCALE
N.T.S.

TITAN RACK 19"

11

NOT USED

SCALE
N.T.S.

TITAN RACK 19"

11

SCALE
N.T.S.

TITAN RACK 19"

11

NOT USED

SCALE
N.T.S.

TITAN RACK 19"

11

SCALE
N.T.S.

TITAN RACK 19"

11

NOT USED

SCALE
N.T.S.

TITAN RACK 19"

11

SCALE
N.T.S.

TITAN RACK 19"

11

NOT USED

SCALE
N.T.S.

TITAN RACK 19"

11

SCALE
N.T.S.

TITAN RACK 19"

11

NOT USED

SCALE
N.T.S.

TITAN RACK 19"

11

SCALE
N.T.S.

TITAN RACK 19"

11

NOT USED

SCALE
N.T.S.

TITAN RACK 19"

11

SCALE
N.T.S.

TITAN RACK 19"

11

NOT USED

SCALE
N.T.S.

TITAN RACK 19"

11

SCALE
N.T.S.

TITAN RACK 19"

11

NOT USED

SCALE
N.T.S.

TITAN RACK 19"

11

SCALE
N.T.S.

TITAN RACK 19"

11

NOT USED

SCALE
N.T.S.


T Mobile

19807 NORTH CREEK PKWY N
BOTHELL, WA 98011

LANDLORD SIGNATURE

CHARLES UNIVERSAL BROADBAND ENCLOSURES (CUBE) RL1000 SERIES BACKHAUL CABINETS

MANUFACTURER: CHARLES
MODEL: CUBE RL1003
DIMENSIONS: 22'H x 22'W x 20'D
WEIGHT: 90 LBS (EMPTY)
RU: 14
MOUNTING RAILS: 19" FIXED RAIL
LOAD CENTER: NONE




PLANS PREPARED BY:

Technology Associates

SEATTLE MARKET OFFICE
1455 NW LEARY WAY, STE. 400
SEATTLE, WA 98107

JURISDICTION APPROVAL SEAL:



DRAWING NOTICE:
THESE DOCUMENTS ARE CONFIDENTIAL
AND ARE THE SOLE PROPERTY OF
T-MOBILE AND MAY NOT BE REPRODUCED,
DISSEMINATED OR REDISTRIBUTED
WITHOUT THE EXPRESS WRITTEN
CONSENT OF T-MOBILE.

REVISIONS:	DESCRIPTION	DATE	BY	REV
ISSUED FOR 90% CD		07/30/2025	MGM	A
ISSUED FOR 100% CD		08/13/2025	MGM	0

SITE NAME:
WEST BAKERVIEW -
SCHLOSSER - SNOPUD

SITE NUMBER:
SE01458B

SITE ADDRESS:
4822 103RD PL SW
MUKILTEO, WA 98275

SHEET DESCRIPTION:
DETAILS



SHEET NUMBER:
A-7

NOTE: THE ORIGINAL SIZE OF THIS PLAN IS 24" X 36". SCALE RATIO IS NOT VALID FOR REDUCED OR ENLARGED SHEET SIZES


NOT USED

SCALE
N.T.S.**10**

NOT USED

SCALE
N.T.S.**7****BACKHAUL CABINET**SCALE
N.T.S.**1****RAYCAP: RTMAC-2465-P-240-MTS**



MANUFACTURER: RAYCAP
PART NUMBER: RTMAC-2465-P-240
UTILITY BREAKER: 200A, 65KAIC
GENERATOR BREAKER: 200A, 10KAIC
GENERATOR INTERFACE: CAMLOCK
OPERATING AC VOLTAGE: 240/120, 1 PHASE 3W+G
TRANSFER SWITCH: MANUAL
GFIC: INCLUDED
LOAD CENTER: 24 POSITION




NOT USED

SCALE
N.T.S.**11**

DOOR JAMB

SCALE
N.T.S.**8****WOODEN GATE**SCALE
N.T.S.**5****ELECTRICAL PANEL**SCALE
N.T.S.**2****PANTROL: PANLOC LITE**

DIMENSIONS:
FEATURES:
10.5'H X 9'W X 9.25'D
ELIMINATES MULTIPLE GENERATOR PLUGS AND ADAPTERS
INDUSTRY STANDARD, COLOR CODED SINGLE POLE CONNECTORS
TOUCH SAFE DESIGN INDUSTRY STANDARD MOUNTING DECREASED
DOWN TIME 200A, 3-PHASE CAPABILITIES KAIC RATING: UP TO 10,000
AMPS ALUMINUM CONSTRUCTION REMOVABLE ACCESS COVER EASE
OF USE UL LISTED




ONE HOUR EXTERIOR WALL PROTECTION AND EAVE PROTECTION

SCALE
N.T.S.**9****COMPOUND: SITE FINISHING**SCALE
N.T.S.**6****CAM LOCK**SCALE
N.T.S.**3**

T Mobile

19807 NORTH CREEK PKWY N
BOTHELL, WA 98011

Technology Associates

SEATTLE MARKET OFFICE
1455 NW LEARY WAY, STE. 400
SEATTLE, WA 98107

DRAWING NOTICE:
THESE DOCUMENTS ARE CONFIDENTIAL
AND ARE THE SOLE PROPERTY OF
T-MOBILE AND MAY NOT BE REPRODUCED,
DISSEMINATED OR REDISTIBUTED
WITHOUT THE EXPRESS WRITTEN
CONSENT OF T-MOBILE.

REVISIONS:	DESCRIPTION	DATE	BY	REV
ISSUED FOR 90% CD		07/30/2025	MGM	A
ISSUED FOR 100%CD		08/13/2025	MGM	0

SITE NAME:
WEST BAKERVIEW -
SCHLOSSER - SNOPUD

SITE NUMBER:
SE01458B

SITE ADDRESS:
4822 103RD PL SW
MUKILTEO, WA 98275

SHEET DESCRIPTION:
**HYBRID TRUNK
SPECIFICATIONS**

SHEET NUMBER:

A-8

LANDLORD SIGNATURE

PRODUCT DATASHEET
HB158-21U6S24-XXM SERIESHYBRIFLEX® Hybrid Feeder Cabling Solution 6x24, 4AWG, 1-5/8",
Single-Mode Fiber, DLC to ODC, with 6AWG DC breakout top

Technical Features		
STRUCTURE		
Cable Type	HYBRIFLEX®	
Size	1-5/8"	
MECHANICAL SPECIFICATIONS		
Outer Diameter Nominal	mm (in)	50.7 (1.99)
kg/m (lb/ft)	3.65 (0.25)	
Minimum Bending Radius, Single Bend	mm (in)	25.4 (1.0)
Minimum Bending Radius, Multi Bends	mm (in)	50.8 (2.0)
Recommended / Maximum Clamp Spacing	mm (in)	11.12 (3.25 / 4)
DC POWER CABLE SPECIFICATIONS		
Number of DC Pairs	6	
Maximum DC-Resistance Power Cable	Ω/km (Ω/ft)	0.83 (0.25)
Cross Section of Power Cable	mm ² (AWG)	23.1 (4)
DC Wire Jacket Material	PVC/Nylon	
DC Cable Diameter	mm (in)	7.8 (0.308)
DC Standards (Meets or Exceeds)	For use in UL 1069 PVC Nylon, RoHS/REACH Compliant	
Break-out length (Top)	mm (in)	5000 (197)
Break-out length (Bottom)	mm (in)	1000 (39)
DC Cable sealing method	Semi-rigid flame-retarded polyolefin, with hot melt adhesive	
CABLE JACKET		
UV-Protection Individual and External Jacket	Yes	
ARMOR SPECIFICATIONS		
Armor Type	Corrugated Aluminum	
Maximum DC-Resistance of Armor	Ω/km (Ω/ft)	0.58 (0.178)
Diameter Corrugated Armor	mm (in)	46.4 (1.83)
F/OD CABLE SPECIFICATIONS		
F/OD Cable Type	G657-A1 Single Mode, Bond Termination	
Number of F/OD Pairs	24	
Core/Clad	μm	9/125
Secondary Protection Nominal	μm (in)	900 (0.035)
Single Bending Radius	mm (in)	157 (6.2)
ODC Standards (Meets or Exceeds)	UL Listed Type OFNR (UL1665), RoHS/REACH Compliant	
Optical Loss	dB/km	0.4 @ 1310 nm 0.5 @ 1550 nm
Fiber Termination End 1	ODC plug	
Fiber Termination End 2	ODC Connector	
FO Break-out length (Top)	mm (in)	700 (27.5)
FO Break-out length (Bottom)	mm (in)	1610 (63.4)
Fiber sealing method	Semi-rigid flame-retarded polyolefin, with hot melt adhesive	
TESTING AND ENVIRONMENTAL		
Storage Temperature	°C (°F)	-40 to 70 (-40 to 158)
Operation Temperature	°C (°F)	-40 to 05 (-40 to 149)
Installation Temperature	°C (°F)	20 to 05 (-4 to 149)
ASSEMBLY LOSS		
Optical Insertion Loss, Assembly or Jumper	Assembly or Jumper	0.4 dB (typ) 0.9dB (max) @1310/1550
SYSTEM LOSS		
Optical Insertion Loss	Total Path	0.6dB (typ) 1.9dB (max) @1310/1550

HB158-21U6S24-XXM SERIES REV: B

REV DATE: 30Oct20

www.rfsworld.com

All information contained in the present datasheet is subject to confirmation at time of ordering.

Page 1 of 3

PRODUCT DATASHEET
HB158-21U6S24-XXM SERIESHYBRIFLEX® Hybrid Feeder Cabling Solution 6x24, 4AWG, 1-5/8",
Single-Mode Fiber, DLC to ODC, with 6AWG DC breakout top

External Document Links			Notes	
Installation Guidelines			Nominal length equals length of trunk not including top and bottom breakouts; breakout lengths add additionally to the total assembly length up to top.	
Top Breakout - DC Power Cable Specifications:			No of DC pairs: 6. Specifications per 1 pair: Maximum DC-Resistance Power Cable Q/km (Ω/km) t.4 (0.42), Cross Section of Power Cable mm ² (AWG) 13.3 (6). Overall Cable Diameter mm (in) 17.8 (0.70). DC Cable Jacket Material PVC, EMI Shield Thread Copper Braid	
External Link Reference			View Factory Test Results On-line	
http://myrfs.rfsworld.com/hybriflex/Default.aspx				


HB158-21U6S24-XXM SERIES REV: B

REV DATE: 30Oct20

www.rfsworld.com

All information contained in the present datasheet is subject to confirmation at time of ordering.

Page 2 of 3

PRODUCT DATASHEET
HB158-21U6S24-XXM SERIESHYBRIFLEX® Hybrid Feeder Cabling Solution 6x24, 4AWG, 1-5/8",
Single-Mode Fiber, DLC to ODC, with 6AWG DC breakout top

HB158-21U6S24-XXM SERIES REV: B

REV DATE: 30Oct20

www.rfsworld.com

All information contained in the present datasheet is subject to confirmation at time of ordering.

Page 3 of 3

T Mobile

19807 NORTH CREEK PKWY N
BOTHELL, WA 98011

LANDLORD SIGNATURE

KEYED NOTES:

- 1 NOT USED
- 2 INSTALL AIR HANDLING UNITS ON WALL PER MANUFACTURER'S INSTRUCTIONS AND PER DETAILS INDICATED ON DRAWINGS
- 3 INSTALL OUTDOOR CONDENSING UNIT PER MANUFACTURER'S INSTRUCTIONS AND PER DETAILS INDICATED ON DRAWINGS
- 4 NOT USED
- 5 NOT USED
- 6 NOT USED
- 7 DIRECTION OF AIR FLOW
- 8 NOT USED
- 9 NOT USED
- 10 NOT USED

HVAC EQUIPMENT SCHEDULE:

CU 1	INDOOR AIR HANDLER MITSUBISHI PKA-A36KA7 36,000 BTU/HR TOTAL COOLING CAPACITY WEIGHT: 46 LBS UNIT DIMENSION: 14 3/8" H x 46 1/16" W x 11 5/8" D	EER = 10.8 SEER = 18.8
CU 2	OUTDOOR CONDENSING UNIT MITSUBISHI PUY-A36NKA7 36,000 BTU/HR TOTAL COOLING CAPACITY WEIGHT: 211.0 LBS UNIT DIMENSION: 52 11/16" H x 41 5/16" W x 13 + 1 3/16" D	

ENERGY CONSERVATION NOTE:

1. INSULATION MATERIALS SHALL MEET THE 2021 WASHINGTON STATE ENERGY CODES QUALITY STANDARDS PER SECTION C402 BUILDING ENVELOPE REQUIREMENTS (C402.2).
2. DOORS AND WINDOWS SHALL MEET THE MINIMUM INFILTRATION REQUIREMENTS PER SECTION (C403.4, C402.4.4, C402.1.4).
3. ALL PIPING AND DUCTWORK SHALL BE INSULATED CONSISTENT WITH REQUIREMENTS OF SECTION (C403.2, C403.2.9).

ENVIRONMENTAL CONTROL GENERAL NOTES:

SPACE-ENVIRONMENTAL CONTROL SEQUENCE

SITE TEMPERATURE CONTROL IS TO BE PROVIDED BY AIR CONDITIONING UNIT(S) EQUIPPED WITH 1 OR 2-STAGE. COOL/WARM WALL THERMOSTAT PROVIDED BY CONTRACTOR. SYSTEM IS TO OPERATE 24 HOURS A DAY, 7 DAYS A WEEK, 365 DAYS A YEAR AND SHALL MAINTAIN SPACE @ 78°F(±2°).

HVAC GENERAL NOTES:

DESIGN CRITERIA:

SUMMER AUG 3 PM:	OUTSIDE TEMPERATURE: 91 FDB 50 % RH
WINTER JAN 12 AM:	OUTSIDE TEMPERATURE: 34 FDB INSIDE TEMPERATURE: 78 FDB

THE SUBCONTRACTOR SHALL PERFORM THE WORK IN ACCORDANCE WITH THE BEST ASHRAE AND INDUSTRIAL STANDARDS.

ALL HVAC WORK SHALL COMPLY WITH ALL APPLICABLE STATE AND LOCAL BUILDING CODES AND FEDERAL HAVING JURISDICTION OVER THE CONSTRUCTION.

SUBCONTRACTOR SHALL EXAMINE THE PROJECT SITE AND DISCUSS GENERAL REQUIREMENTS OF THE BUILDING AND WORK PERFORMANCE WITH THE PROJECT MANAGER. SUBCONTRACTOR SHALL COORDINATE HIS WORK WITH THE WORK OF OTHERS ON THE PROJECT. SUBCONTRACTOR SHALL CONFIRM EXISTING CONDITIONS AND PROVIDE ALL LABOR AND MATERIALS TO MAKE A WORKABLE AND USABLE SYSTEM.

SUBCONTRACTOR IS TO REPORT TO CONSTRUCTION ENGINEER ANY OBSERVATIONS OR CONDITIONS WHICH ARE DISCOVERED IN THE BUILDING WHICH WOULD PREVENT THE FULLEST USE OF THE HVAC SYSTEM.

SUBCONTRACTOR SHALL ARRANGE AND PAY FOR ALL FEES, PERMITS, AND INSPECTIONS CONCERNING THE WORK.

A MAINTENANCE LABEL MUST BE AFFIXED TO MECHANICAL EQUIPMENT. TWO COPIES OF A MAINTENANCE MANUAL FOR THE EQUIPMENT ITEMS SHALL BE PROVIDED TO THE OWNER BY THE SUBCONTRACTOR.

CONDENSATE DRAINS TO BE COPPER TUBING. DRAINS SHALL BE INDIRECT. DRAINS SHALL BE SUPPLIED AND INSTALLED BY THE SUBCONTRACTOR. DRAINS SHALL NOT BE RUN ABOVE ELECTRICAL OR ELECTRONIC EQUIPMENT.

THE SUCTION LINES, AND LIQUID LINES SHALL BE TYPE L HARD DRAWN COPPER TUBING. INSULATED WITH MINIMUM OF 1/2" ARMALFLEX OR EQUAL. SOFT COPPER TUBING MAY BE USED IF NECESSARY TO INSTALL LINES AROUND OBSTRUCTIONS. AVOID SHARP BENDS AS TUBING MAY PINCH CAUSING A RESTRICTION. USE LONG RADIUS ELBOWS WHENEVER POSSIBLE. SHORT RADIUS ELLS FOR THE TRAPS AT THE BOTTOM OF ALL SECTION RISERS. BRAZE ALL CU TO CU JOINTS WITH SILFOS-5 OR EQUIVALENT BRAZING MATERIAL. DO NOT USE SOFT SOLDER. SUCTION LINES TO BE SUPPORTED A MINIMUM OF EVERY 8'-0" LIQUID LINES TO BE SUPPORTED A MINIMUM OF EVERY 6'-0"

RIGID SPIRAL LOCK-SEAM DUCTS AND FITTINGS MAY BE INTERCHANGED WITH SQUARE OR RECTANGULAR SHEET METAL DUCTWORK AT SUBCONTRACTOR'S OPTION.

ALL LOW VOLTAGE (24V) ALARM WIRING BY SUBCONTRACTOR. ALL CONDUIT BY SUBCONTRACTOR. #22 STRANDED COPPER.

THE SUBCONTRACTOR SHALL BE RESPONSIBLE FOR THE ACQUISITION AND PAYMENT OF ALL PERMITS AND INSPECTORS REQUIRED AND RELATED FEES FOR THIS INSTALLATION. ALL WORK SHALL COMPLY WITH APPLICABLE STATE AND LOCAL CODES.

ALL CONNECTIONS BETWEEN A/C UNITS/FANS AND DUCTWORK SHALL HAVE FIREPROOF, HEAVY DUTY FLEX-CONNECTIONS (LOCAL JURISDICTION APPROVED) WITH 3" MIN CLEARANCE. ISOLATE ALL HVAC UNITS/FANS AND EQUIPMENT FROM STRUCTURE WITH APPROVED ISOLATION MOUNTS.

ALL WEATHER EXPOSED EQUIPMENT, DUCTS, ETC., SHALL BE COMPLETELY WEATHERPROOFED.

ALL SUPPLY AND RETURN DUCTS WHERE EXPOSED TO WEATHER AND ELSEWHERE AS INDICATED ON DRAWINGS, SHALL BE LINED WITH 1-1/2", 1-1/2# DENSITY FIBERGLASS INSULATION AND SECURED WITH GALVANIZED WIRES. PROVIDE VAPOR BARRIER ON SUPPLY DUCTS. USE 1-1/2" THICK INSULATION ON SUPPLY, 1-1/2" THICK ON RETURN. LINED DUCTS AND PLENUMS IN CEILING SPACES MAY BE LINED WITH 1" THICK INSULATION.

EER RATING AND HEATING COMBUSTION EFFICIENCY RATING OF EACH HVAC UNIT SHALL COMPLY WITH STATE REQUIREMENTS.


INSULATION SUCTION LINES W/ 1-1/2" THICK MANVILLE "MICROLOK" FIBERGLASS INSULATION W/ VAPOR BARRIER JACKET (ARMAFLEX TYPE EXPANDED URETHANE NOT ACCEPTABLE).

INSTALL CONDENSATE DRAIN LINES AWAY FROM ALL ELECTRICAL, RADIO, AND TELEPHONE EQUIPMENT.

ALL HVAC EQUIPMENT SHALL BE SEISMICALLY BRACED PER LOCAL REQUIREMENTS.

SUBCONTRACTOR MUST PROVIDE TRANSITION FITTINGS FOR ROOF PENETRATIONS FROM ROUND TO SQUARE OR WHATEVER NECESSARY FOR EXHAUST, SUPPLY AND RETURN DUCT APPLICATIONS.

THE SUPPLY AND RETURN DUCTS ARE SHOWN INSIDE LINED OR WHERE LINING IS NOT INDICATED, INSULATE ALL DUCTS PER GENERAL NOTES AND MANUFACTURER'S PRINTED INSTRUCTIONS, INCLUDING ALL DUCT DROPS TO CEILING OUTLETS.



T-MOBILE EQUIPMENT SHELTER MECHANICAL PLAN

SCALE
N.T.S. 2

THE SUBCONTRACTOR TO FURNISH AND INSTALL LINE VOLTAGE CONDUIT AND WIRING AND LOW VOLTAGE CONDUIT.

THERMOSTAT SHALL BE LOCATED FIVE FEET (5'-0") ABOVE THE FINISH FLOOR OR AT THE SAME HEIGHT OF ANY ADJACENT ELECTRICAL SWITCHES.

REFER TO MANUFACTURER'S MANUAL FOR RECOMMENDED FUSE AND WIRE SIZES.

ALL SWITCHES, MAGNETIC STARTERS AND CONTACTORS, NOT AN INTEGRAL PART OF THE AIR CONDITIONING EQUIPMENT ARE TO BE FURNISHED AND INSTALLED BY THE SUBCONTRACTOR.

THE SUBCONTRACTOR IS TO MAKE CORRECTIONS TO DEVICES FOR THE AUTOMATIC CONTROL OF THE HVAC INCLUDING AUTOMATIC VALVES AND COMPONENTS WHICH ARE A PART OF THE A/C PIPING SYSTEMS.

ALL FINAL CONNECTIONS TO THE EQUIPMENT ARE TO BE OF FLEXIBLE WEATHERPROOF CONDUIT TO MEET INTERNATIONAL BUILDING CODES. SUBCONTRACTOR TO FURNISH AND INSTALL ALL NECESSARY LOW VOLTAGE WIRING.

GENERAL NOTE (TYPICAL FOR ALL SYSTEMS)

CONTROL DIAGRAMS ARE SCHEMATIC AND ACTUAL WIRING OF ALL EQUIPMENT SHALL BE PERFORMED BASED ON EITHER MANUFACTURER'S RECOMMENDED CONTROL DIAGRAMS OR SUBCONTRACTOR'S APPROVED SHOP DRAWINGS. WRITTEN APPROVALS ON ALL EQUIPMENT AND CONTROL WIRING DIAGRAMS ARE REQUIRED.

PLANS PREPARED BY:

Technology Associates

SEATTLE MARKET OFFICE
1455 NW LEARY WAY, STE. 400
SEATTLE, WA 98107

JURISDICTION APPROVAL SEAL:

ENGINEERING SEAL:



DRAWING NOTICE:

THESE DOCUMENTS ARE CONFIDENTIAL AND ARE THE SOLE PROPERTY OF T-MOBILE AND MAY NOT BE REPRODUCED, DISSEMINATED OR REDISTRIBUTED WITHOUT THE EXPRESS WRITTEN CONSENT OF T-MOBILE.

REVISIONS:

DESCRIPTION DATE BY REV

ISSUED FOR 90% CD 07/30/2025 MGM A

ISSUED FOR 100%CD 08/13/2025 MGM 0

SITE NAME: WEST BAKERVIEW - SCHLOSSER - SNOPUD


SITE NUMBER: SE01458B

SITE ADDRESS: 4822 103RD PL SW
MUKILTEO, WA 98275

SHEET DESCRIPTION: MECHANICAL PLANS & NOTES

SHEET NUMBER:

M-1



DESCRIPTION	DATE	BY	REV
ISSUED FOR 90% CD	07/30/2025	MGM	A
ISSUED FOR 100%CD	08/13/2025	MGM	0



Changes for the Better

P-SERIES

SUBMITTAL DATA: PKA-A36KA7 & PUY-A36NKA7

36,000 BTU/H WALL-MOUNTED AIR-CONDITIONING SYSTEM

Job Name:	Engineer:
Purchaser:	Application: <input type="checkbox"/> Std. Cooling <input type="checkbox"/> Ultra Low Ambient Cooling
Submitted To:	For: <input type="checkbox"/> Reference <input type="checkbox"/> Approval <input type="checkbox"/> Construction
Submitted By:	Location:
System Designation:	Schedule No.:



Electrical Power Requirements	208 / 230V, 1-Phase, 60 Hz
Minimum Circuit Amperage (MCA) *	Breaker Size MOCP (Outdoor)
Indoor 1 AMP	Outdoor 25 AMP 30 AMP 31 AMP
*All electrical work shall comply with National (CEC) and local codes and regulations.	
Indoor Unit	
Fan Motor (ECM)	F.L.A. 0.57
Fan Motor Output	W 56
SHF / Moisture Removal	0.70 / 9.7 pt/h
Field Drainpipe Size O.D.	In.(mm) 5/8 (16)
Outdoor Unit	
Compressor	DC INVERTER-driven Twin Rotary
Fan Motor (ECM)	F.L.A. 0.5 + 0.5
Fan Motor Power	W 74
Airflow Rate (Low-Mid-Hi)	
Indoor (DRY)	705-810-920
(Cooling) WET	CFM 635-730-830
Outdoor (DRY)	3,880
Sound Pressure Level	
Indoor (Low-Mid-Hi)	dB(A) 43-46-49
Outdoor (Cooling)	52
External Dimensions	
Indoor (H x W x D)	14 3/8 x 46 1/16 x 11 5/8 (365 x 1170 x 295)
In.(mm)	
Outdoor (H x W x D)	52-11/16 x 41-5/16 x 13 + 1-3/16 (1,338 x 1050 x 330 + 30)
Net Weight	
Indoor	Lbs.(kg) 46 (21)
Outdoor	211 (96)
External Finish	
Indoor	White Munsell No. 1.0Y 9.2/0.2
Outdoor	Ivory Munsell No. 3Y 7.8 / 1.1
Refrigerant	R410A; 10lbs., 6oz. (4.7kg)
AHRI Efficiency Rating	
EER	10.8
SEER	18.8

Note: Mitsubishi Electric (MESCA) supports the use of only MESCA supplied and approved Snow Guards / Wind Deflectors / Windscreens and accessories for proper functioning of the units. Use of non-MESCA supported Snow Guard / Wind Deflectors / Windscreens and accessories will effect warranty coverage.

SPECIFICATIONS:

Rated Conditions (Capacity / Input)*	
Cooling	Btuh / W 36,000 / 3,330

* Rating Conditions per AHRI Standard:
Cooling (Indoor: 80°F (27°C) DB / 67°F (19°C) WB
Outdoor: 95°F (35°C) DB / 75°F (24°C) WB)

Capacity Range	
Cooling	Btuh 16,000 - 36,000

Operating Range	
Cooling	-40F** (-40.0°C) to 115°F (46°C) DB

** Windscreens required for cooling operation below 23°F (-5°C)

Specifications are subject to change without notice.

© 2016 Mitsubishi Electric Sales Canada Inc.

Page 1 of 3

Form # SB_PKA-A36KA7_PUY-A36NKA7_201908

NOTE: THE ORIGINAL SIZE OF THIS PLAN IS 24" X 36". SCALE RATIO IS NOT VALID FOR REDUCED OR ENLARGED SHEET SIZES

Should the document be altered or changed without MESCA's permission, it becomes null and void. MESCA assumes no responsibility for any consequences in such cases.

Should this document be altered or changed without MESCA's permission, it becomes null and void. MESCA assumes no responsibility for any consequences in such cases.

Should this document be altered or changed without MESCA's permission, it becomes null and void. MESCA assumes no responsibility for any consequences in such cases.

Should this document be altered or changed without MESCA's permission, it becomes null and void. MESCA assumes no responsibility for any consequences in such cases.

Should this document be altered or changed without MESCA's permission, it becomes null and void. MESCA assumes no responsibility for any consequences in such cases.

Should this document be altered or changed without MESCA's permission, it becomes null and void. MESCA assumes no responsibility for any consequences in such cases.

Should this document be altered or changed without MESCA's permission, it becomes null and void. MESCA assumes no responsibility for any consequences in such cases.

Should this document be altered or changed without MESCA's permission, it becomes null and void. MESCA assumes no responsibility for any consequences in such cases.

Should this document be altered or changed without MESCA's permission, it becomes null and void. MESCA assumes no responsibility for any consequences in such cases.

Should this document be altered or changed without MESCA's permission, it becomes null and void. MESCA assumes no responsibility for any consequences in such cases.

Should this document be altered or changed without MESCA's permission, it becomes null and void. MESCA assumes no responsibility for any consequences in such cases.

Should this document be altered or changed without MESCA's permission, it becomes null and void. MESCA assumes no responsibility for any consequences in such cases.

Should this document be altered or changed without MESCA's permission, it becomes null and void. MESCA assumes no responsibility for any consequences in such cases.

Should this document be altered or changed without MESCA's permission, it becomes null and void. MESCA assumes no responsibility for any consequences in such cases.

Should this document be altered or changed without MESCA's permission, it becomes null and void. MESCA assumes no responsibility for any consequences in such cases.

Should this document be altered or changed without MESCA's permission, it becomes null and void. MESCA assumes no responsibility for any consequences in such cases.

Should this document be altered or changed without MESCA's permission, it becomes null and void. MESCA assumes no responsibility for any consequences in such cases.

Should this document be altered or changed without MESCA's permission, it becomes null and void. MESCA assumes no responsibility for any consequences in such cases.

Should this document be altered or changed without MESCA's permission, it becomes null and void. MESCA assumes no responsibility for any consequences in such cases.

Should this document be altered or changed without MESCA's permission, it becomes null and void. MESCA assumes no responsibility for any consequences in such cases.

Should this document be altered or changed without MESCA's permission, it becomes null and void. MESCA assumes no responsibility for any consequences in such cases.

Should this document be altered or changed without MESCA's permission, it becomes null and void. MESCA assumes no responsibility for any consequences in such cases.

Should this document be altered or changed without MESCA's permission, it becomes null and void. MESCA assumes no responsibility for any consequences in such cases.

Should this document be altered or changed without MESCA's permission, it becomes null and void. MESCA assumes no responsibility for any consequences in such cases.

Should this document be altered or changed without MESCA's permission, it becomes null and void. MESCA assumes no responsibility for any consequences in such cases.

Should this document be altered or changed without MESCA's permission, it becomes null and void. MESCA assumes no responsibility for any consequences in such cases.

Should this document be altered or changed without MESCA's permission, it becomes null and void. MESCA assumes no responsibility for any consequences in such cases.

Should this document be altered or changed without MESCA's permission, it becomes null and void. MESCA assumes no responsibility for any consequences in such cases.

Should this document be altered or changed without MESCA's permission, it becomes null and void. MESCA assumes no responsibility for any consequences in such cases.

Should this document be altered or changed without MESCA's permission, it becomes null and void. MESCA assumes no responsibility for any consequences in such cases.

Should this document be altered or changed without MESCA's permission, it becomes null and void. MESCA assumes no responsibility for any consequences in such cases.

Should this document be altered or changed without MESCA's permission, it becomes null and void. MESCA assumes no responsibility for any consequences in such cases.

Should this document be altered or changed without MESCA's permission, it becomes null and void. MESCA assumes no responsibility for any consequences in such cases.

Should this document be altered or changed without MESCA's permission, it becomes null and void. MESCA assumes no responsibility for any consequences in such cases.

Should this document be altered or changed without MESCA's permission, it becomes null and void. MESCA assumes no responsibility for any consequences in such cases.

Should this document be altered or changed without MESCA's permission, it becomes null and void. MESCA assumes no responsibility for any consequences in such cases.

Should this document be altered or changed without MESCA's permission, it becomes null and void. MESCA assumes no responsibility for any consequences in such cases.

Should this document be altered or changed without MESCA's permission, it becomes null and void. MESCA assumes no responsibility for any consequences in such cases.

Should this document be altered or changed without MESCA's permission, it becomes null and void. MESCA assumes no responsibility for any consequences in such cases.

Should this document be altered or changed without MESCA's permission, it becomes null and void. MESCA assumes no responsibility for any consequences in such cases.

Should this document be altered or changed without MESCA's permission, it becomes null and void. MESCA assumes no responsibility for any consequences in such cases.

Should this document be altered or changed without MESCA's permission, it becomes null and void. MESCA assumes no responsibility for any consequences in such cases.

Should this document be altered or changed without MESCA's permission, it becomes null and void. MESCA assumes no responsibility for any consequences in such cases.

Should this document be altered or changed without MESCA's permission, it becomes null and void. MESCA assumes no responsibility for any consequences in such cases.

Should this document be altered or changed without MESCA's permission, it becomes null and void. MESCA assumes no responsibility for any consequences in such cases.

Should this document be altered or changed without MESCA's permission, it becomes null and void. MESCA assumes no responsibility for any consequences in such cases.

Should this document be altered or changed without MESCA's permission, it becomes null and void. MESCA assumes no responsibility for any consequences in such cases.

Should this document be altered or changed without MESCA's permission, it becomes null and void. MESCA assumes no responsibility for any consequences in such cases.

Should this document be altered or changed without MESCA's permission, it becomes null and void. MESCA assumes no responsibility for any consequences in such cases.

Should this document be altered or changed without MESCA's permission, it becomes null and void. MESCA assumes no responsibility for any consequences in such cases.

Should this document be altered or changed without MESCA's permission, it becomes null and void. MESCA assumes no responsibility for any consequences in such cases.

Should this document be altered or changed without MESCA's permission, it becomes null and void. MESCA assumes no responsibility for any consequences in such cases.

Should this document be altered or changed without MESCA's permission, it becomes null and void. MESCA assumes no responsibility for any consequences in such cases.

Should this document be altered or changed without MESCA's permission, it becomes null and void. MESCA assumes no responsibility for any consequences in such cases.

Should this document be altered or changed without MESCA's permission, it becomes null and void. MESCA assumes no responsibility for any consequences in such cases.

Should this document be altered or changed without MESCA's permission, it becomes null and void. MESCA assumes no responsibility for any consequences in such cases.

Should this document be altered or changed without MESCA's permission, it becomes null and void. MESCA assumes no responsibility for any consequences in such cases.

Should this document be altered or changed without MESCA's permission, it becomes null and void. MESCA assumes no responsibility for any consequences in such cases.

Should this document be altered or changed without MESCA's permission, it becomes null and void. MESCA assumes no responsibility for any consequences in such cases.


Should this document be altered or changed without MESCA's permission, it becomes null and void. MESCA assumes no responsibility for any consequences in such cases.

Should this document be altered or changed without MESCA's permission, it becomes null and void. MESCA assumes no responsibility for any consequences in such cases.

T Mobile

19807 NORTH CREEK PKWY N
BOTHELL, WA 98011

Technology Associates

SEATTLE MARKET OFFICE
1455 NW LEARY WAY, STE. 400
SEATTLE, WA 98107

DRAWING NOTICE:
THESE DOCUMENTS ARE CONFIDENTIAL
AND ARE THE SOLE PROPERTY OF
T-MOBILE AND MAY NOT BE REPRODUCED,
DISSEMINATED OR REDISTRIBUTED
WITHOUT THE EXPRESS WRITTEN
CONSENT OF T-MOBILE.

REVISIONS:	DESCRIPTION	DATE	BY	REV
ISSUED FOR 90% CD		07/30/2025	MGM	A
ISSUED FOR 100% CD		08/13/2025	MGM	0


SITE NAME:
WEST BAKERVIEW -
SCHLOSSER - SNOPUD

SITE NUMBER:
SE01458B

SITE ADDRESS:
4822 103RD PL SW
MUKILTEO, WA 98275

SHEET DESCRIPTION:
**PANEL SCHEDULE &
ONE-LINE DIAGRAM**

SHEET NUMBER:
E-3



NOTES:


- ALL EQUIPMENT (FUSES, CIRCUIT BREAKERS, BUSSING, ETC.) SHALL HAVE A SHORT CIRCUIT RATING EQUAL TO, OR GREATER THAN, THE AVAILABLE SHORT CIRCUIT CURRENT AT THE LOCATION.
- ALL ELECTRICAL EQUIPMENT SHALL BE U.L. LISTED.
- ALL ELECTRICAL EQUIPMENT EXPOSED TO THE WEATHER SHALL BE LISTED FOR EXTERIOR USE.
- SQUARE "Ø" NOOD PANELBOARD
- CU-2 SHALL OPERATE ONLY IF CU-1 IS DISCONNECTED FROM POWER BY AUTOMATIC CONTROLS.
- MULTIPLE CIRCUITS NEED COMMON "OFF" HANDLE CUPS.

PANEL SCHEDULE


SCALE
N.T.S. 1

KEY NOTES:

① NEW 5/8"Ø x 10'-0" COPPER CLAD STEEL GROUND ROD AND #2 CU GROUND. BOND TO ISOLATED GROUND ROD.

EXISTING TRANSFORMER
(POWER P.O.C.)

LANDLORD SIGNATURE



UTILITY POINTS OF SERVICE AND WORK / MATERIALS SHOWN ARE BASED UPON PRELIMINARY INFORMATION PROVIDED BY THE SITE WALK. PRIOR TO START OF CONSTRUCTION CONTRACTOR TO OBTAIN CURRENT UTILITY PLAN.

CONTRACTOR SHALL COORDINATE WITH UTILITY COMPANY FOR FINAL AND EXACT WORK / MATERIALS REQUIREMENTS AND CONSTRUCT TO UTILITY COMPANY ENGINEERING PLANS AND SPECIFICATIONS ONLY. CONTRACTOR SHALL FURNISH AND INSTALL ALL CONDUIT, PULL ROPES, CABLES, PULL BOXES, CONCRETE ENCASEMENT OF CONDUIT (IF REQUIRED), TRANSFORMER PAD, BARRIERS, POLE RISERS, TRENCHING, BACKFILL, PAY ALL UTILITY COMPANY FEES AND INCLUDE ALL REQUIREMENTS IN SCOPE OF WORK.

SCALE
N.T.S. 2


ONE LINE DIAGRAM

SCALE
N.T.S. 3

T Mobile

19807 NORTH CREEK PKWY N
BOTHELL, WA 98011

Technology Associates

SEATTLE MARKET OFFICE
1455 NW LEARY WAY, STE. 400
SEATTLE, WA 98107

THESE DOCUMENTS ARE CONFIDENTIAL
AND ARE THE SOLE PROPERTY OF
T-MOBILE AND MAY NOT BE REPRODUCED,
DISSEMINATED OR REDISTRIBUITED
WITHOUT THE EXPRESS WRITTEN
CONSENT OF T-MOBILE.

REVISIONS:	DESCRIPTION	DATE	BY	REV
ISSUED FOR 90% CD		07/30/2025	MGM	A
ISSUED FOR 100% CD		08/13/2025	MGM	0

WEST BAKERVIEW -
SCHLOSSER - SNOPUD

SE01458B

4822 103RD PL SW
MUKILTEO, WA 98275POWER, LIGHTING &
SIGNAL PLAN

E-4

LEGEND:

- CONDUIT TURNED UP
- II 3/4" CONDUIT WITH 2#12 CONDUCTORS
PLUS 1#12 EQUIPMENT GROUNDING CONDUCTOR
- III 3/4" CONDUIT WITH 2#8 CONDUCTORS
PLUS 1#12 EQUIPMENT GROUNDING CONDUCTOR
- A-17 → HOMERUN TO INDICATED PANELBOARD "A".
NUMBERS (1,3) INDICATE BRANCH CIRCUIT NUMBERS.
- J JUNCTION BOX, SIZED PER N.E.C., U.N.O.
- ∅ DUPLEX RECEPTACLE, GFI PROTECTION, MOUNTED
AT +15" AFF U.N.O.
- R ∅ RECEPTACLE, WITH GFI PROTECTION, LOCATED ON ROOF
- Sa SINGLE POLE, SINGLE THROW TOGGLE SWITCH, MOUNTED AT
+48" U.N.O. SUBSCRIPT INDICATES CONTROLLING SWITCH LEG.
SPEC. GRADE WITH STAINLESS STEEL PLATE.
- F DISCONNECT SWITCH, HEAVY DUTY TYPE
- COMBINATION SWITCH, HEAVY DUTY TYPE WITH STARTER
- Sm HORSEPOWER RATED MANUAL SWITCH

FIXTURE NOTES:

1. FIXTURE CONNECTIONS SHALL BE AS INDICATED ON THE PLANS AND SHALL COMPLY WITH THE APPLICABLE REQUIREMENTS OF 2015 IEC/C/WASHINGTON STATE ENERGY CODE.
2. CATALOG NUMBERS ARE BASED ON VENDOR INFORMATION, SALES LITERATURE AND PHOTOMETRIC DATA ON HAND AT THE TIME OF PROJECT DESIGN BY TURPIN & RATTAN AND ARE INTENDED TO CONVEY THE FEATURES/PERFORMANCE REQUIRED. EACH FIXTURE MUST BE PROVIDED COMPLETE WITH ALL FITTINGS AS APPROPRIATE FOR PROPER MOUNTING AT THE LOCATIONS INDICATED.
3. MOUNTING SHALL INCLUDE CONCEALED SOLID BLOCKING FOR FIXTURES MOUNTED IN/WALLS AND CEILINGS EXCEPT AT SUSPENDED CEILINGS WHERE SEISMIC ANCHORING AND/OR RESTRAINT SHALL BE PROVIDED.
4. WHERE RECESSED FIXTURES ARE INSTALLED IN FIRE RATED CEILINGS, THE CONTRACTOR SHALL PROVIDE A FIRE RATED ENCLOSURE AROUND EACH FIXTURE.
5. EMERGENCY LIGHT FIXTURE TO BE WIRED TO UNSWITCHED LEG OR CIRCUIT #17.
6. ALL ELECTRICAL OUTLETS NOT SHOWN SHALL BE DISCONNECTED & REMOVED FROM SOURCE.
7. (DESIGNERS EDGE L1707 SV WEATHER TIGHT INDUSTRIAL LIGHT OR EQUIVALENT) OUTDOOR LIGHT

EMERGENCY FIXTURE CONNECTIONS

ALL LIGHT FIXTURES WITH INTEGRAL BATTERY PACKS REQUIRE PERMANENT UNSWITCHED POWER TO ENSURE THE BATTERY IS NEVER ALLOWED TO DRAIN TO ZERO.



DO NOT CONNECT THESE FIXTURES TO TEMPORARY BUILDING CONSTRUCTION POWER.

CONNECT ONLY TO PERMANENT BUILDING POWER WHEN AVAILABLE, AND ACCORDING TO THE RESPECTIVE MANUFACTURERS RECOMMENDATIONS.

LIGHTING FIXTURE SCHEDULE

FIXTURE TYPE	MANUFACTURER AND CATALOG NUMBER	LAMPS		Fixture		BALLAST TYPE	BALLAST TYPE	DESCRIPTION
		QTY.	TYPE	WATTS	COLOR TEMP.			
Ⓐ	LITHONIA LB-232-GB10	2	T-8	32	3500° K	120	62	ELECTRONIC SURFACE CEILING 10" WIDE, 4'-0" LONG FLUORESCENT WITH ACRYLIC WRAP-AROUND LENS
Ⓑ	SURE LITES CC-2/6/8-120/277	1	INCAND. PAR 36	3.6	2700° K	120	<5	- SURFACE WALL WHITE EMERGENCY LIGHTING FIXTURE WITH INTEGRAL CHARGER, ADJUSTABLE HEADS AND EXTERNAL TEST BUTTON.

LANDLORD SIGNATURE



NOTES:

- ① CONDUIT ROUTED @ CEILING PENETRATING TO BUILDING WALL TO TELEPHONE SERVICE @ GROUND LEVEL. FOR CONTINUATION SEE SHEET E2. PROVIDE RADIUS SWEEPS DOWN THROUGH NIU CABINET
- ② 120VAC IONIZATION SMOKE DETECTORS SHALL BE PYROTRONICS #449CSRT, WITH AUXILIARY CONTACT(S) CLOSED IN NORMAL MODE. CONNECT CONTACTS IN SERIES AND PROVIDE 1/2"-2#16 BACK TO TELEPHONE BACKBOARD.
- ③ DOOR ALARM SWITCH SHALL BE 'ADEMCO' MAGNETIC TYPE WITH NORMALLY CLOSED CONTACT. MOUNT AT TOP OF DOOR JAMB ON LATCH SIDE. INSTALL ON 3" ALUMINUM STAND-OFF BRACKET. PROVIDE 1/2"-2#16 BACK TO TELEPHONE BACKBOARD.
- ④ TECH ON SITE KEY SWITCH AS MANUFACTURED BY 'C & K' COMPONENTS #Y201122C203N-Q. PROVIDE 1/2"-2#16 BLACK.
- ⑤ COMMERCIAL POWER FAILURE ALARM FROM CUTLER-HAMMER CABINET.
- ⑥ HIGH-TEMPERATURE ALARM DEVICE, DAYTON #E206. PROVIDE 1/2"-2#16
- ⑦ LOW-TEMPERATURE ALARM DEVICE, DAYTON #E206. PROVIDE 1/2"-2#16
- ⑧ ATTIC VENTILATION FAN


LEGEND:

- II CONDUIT TURNED UP
- CONDUIT INSTALLED EXPOSED
- - - CONDUIT CONCEALED UNDERFLOOR SLAB OR UNDERGROUND
- ∅ SMOKE DETECTOR - IONIZATION TYPE
- H HIGH TEMPERATURE THERMOSTAT
- L LOW TEMPERATURE THERMOSTAT
- A DOOR ALARM SWITCH, AS NOTED. (VERIFY EXACT LOCATION)
- HOMERUN TO INDICATED PANELBOARD "A".
NUMBERS (1,3) INDICATE BRANCH CIRCUIT NUMBERS.
- Sk KEY SWITCH AT +48" U.N.O. (VERIFY EXACT LOCATION)

T Mobile

19807 NORTH CREEK PKWY N
BOTHELL, WA 98011

Technology Associates

SEATTLE MARKET OFFICE
1455 NW LEARY WAY, STE. 400
SEATTLE, WA 98107

DRAWING NOTICE:
THESE DOCUMENTS ARE CONFIDENTIAL
AND ARE THE SOLE PROPERTY OF
T-MOBILE AND MAY NOT BE REPRODUCED,
DISSEMINATED OR REDISTRIBUTED
WITHOUT THE EXPRESS WRITTEN
CONSENT OF T-MOBILE.

REVISIONS:		DESCRIPTION	DATE	BY	REV
ISSUED FOR 90% CD			07/30/2025	MGM	A
ISSUED FOR 100% CD			08/13/2025	MGM	0

SITE NAME:
WEST BAKERVIEW -
SCHLOSSER - SNOPUD

SITE NUMBER:
SE01458B

SITE ADDRESS:
4822 103RD PL SW
MUKILTEO, WA 98275

SHEET DESCRIPTION:
GROUNDING PLANS

SHEET NUMBER:
G-1

LANDLORD SIGNATURE


ELECTRICAL GROUNDING SPECIFICATIONS

- GROUNDING SHALL COMPLY WITH ARTICLE 250 OF THE NATIONAL ELECTRICAL CODE CURRENTLY IN EFFECT FOR THE AUTHORITY HAVING JURISDICTION.
- ALL GROUNDING DEVICES SHALL BE U.L. LISTED FOR THEIR INTENDED USE.
- GROUND WIRES SHALL BE TINNED #2 AWG BARE SOLID COPPER UNLESS OTHERWISE NOTED.
- CONNECTIONS OF ALL GROUND WIRES TO THE GROUND RING SHALL BE EXOTHERMIC (CAD-WELDED), UNLESS OTHERWISE NOTED, AND SHALL BE INSTALLED IN ACCORDANCE WITH MANUFACTURER'S RECOMMENDATIONS AND T-MOBILE WIRELESS BROADBAND STANDARDS.
- GROUNDING CONDUCTORS SHALL BE ROUTED ALONG THE SHORTEST AND STRAIGHTEST PATH POSSIBLE. WHEN REQUIRED, GROUND LEADS SHALL BE BENT TO A MINIMUM OF 8" RADIUS.
- WHERE GROUND WIRES ARE ROUTED FROM ANY CONNECTION ABOVE GRADE TO THE GROUND RING, INSTALL WIRE IN 3/4" HEAVY WALL LIQUID TIGHT FLEXIBLE CONDUIT FROM CONNECTION POINT TO 5" BELOW GRADE AND SEAL THE TOP WITH SILICONE SEALANT.
- ALL GROUND BARS SHALL BE TINNED, 1/4" COPPER, SECTOR BARS 2", COLLECTOR AND MGB BARS 4" OF SUFFICIENT LENGTH TO ACCOMMODATE ALL REQUIRED CONNECTIONS WITHOUT DOUBLING LUGS, AND EACH INSTALLED WITH ISOLATORS. WHEN CONNECTING GROUND BARS (WITHIN 10 FEET OF GRADE) DIRECTLY TO THE GROUND RING, 2 EA. #2 SOLID DOWNLEADS SHALL BE CAD-WELDED TO THE GROUND BAR, 1 AT EACH OPPOSITE BOTTOM CORNER, AND EACH SHALL RUN IN 3/4" HEAVY WALL LIQUID TIGHT FLEXIBLE CONDUIT FROM GROUND BAR DOWN TO THE GROUND RING. WHEN CONNECTING SECTOR GROUND BARS, DAISY-CHAIN THE GROUND BARS AND RUN 1 EA. #2 AWG STRANDED COPPER WIRE WITH THHN INSULATION FROM THE MIDDLE GROUND BAR TO THE GROUND RING AND CAD-WELD TO THE RING.
- WHEN ATTACHING STRANDED GROUND LEADS TO THE GROUND BARS, 2 HOLE COMPRESSION LUGS SHALL BE USED, PROTECT WITH WEATHERPROOF HEAT SHRINK, AND WITH A THIN COAT OF "KOPR SHIELD" OR EQUIVALENT PROPERLY APPLIED AND ATTACHED ONLY WITH STAINLESS STEEL HARDWARE.
- WHEN GROUNDING EQUIPMENT ENCLOSURES, PANELS, FRAMES, AND OTHER METAL APPARATUS, A #6 AWG STRANDED COPPER WIRE WITH THHN INSULATION SHALL BE ATTACHED UTILIZING A 2 HOLE COMPRESSION TYPE LUG, PROTECTED WITH WEATHERPROOF HEAT A CLEAN AND CORROSION FREE METALLIC SURFACE UTILIZING STAINLESS STEEL SELF-TAPPING SCREWS AS NOTED IN NOTE 10 BELOW.
- PREPARE ALL BONDING SURFACES FOR GROUND CONNECTIONS BY REMOVING ANY AND ALL PAINT AND CORROSION TO SHINY METAL. FOLLOWING CAD-WELDED CONNECTIONS TO NON-COPPER SURFACES, APPLY ONE COAT OF ANY ANTI-OXIDIZING PAINT, "COLD GALV" OR EQUIVALENT.
- GROUND RODS SHALL BE COPPER-CLAD STEEL 5/8" x 10', SPACED NO LESS THAN 10' ON CENTER.
- ALL GROUND SYSTEM CONDUCTORS AND CONDUITS SHALL BE SECURED UTILIZING ONLY NONMETALLIC, NON-CONDUCTIVE, UV RATED CLAMPS, BRACKET, AND OR SUPPORTS.
- WHEN REQUIRED, THE CONTRACTOR SHALL ENGAGE THE SERVICES OF AN INDEPENDENT TESTING FIRM TO VERIFY, UTILIZING A MEGGER TEST, THAT THE RESISTANCE TO EARTH OF THE NEW GROUND SYSTEM IS EQUAL TO OR LESS THAN 5 (OHMS), A COPY OF THE COMPLETE TESTING REPORT SHALL BE PROVIDED TO THE T-MOBILE REPRESENTATIVE.
- ALL MATERIALS AND HARDWARE SHALL BE INSTALLED IN A WORKMAN-LIKE MANNER IN ACCORDANCE WITH MANUFACTURER'S RECOMMENDATIONS, AND DEFINED IN NFPA-70 AND APPROVED BY A.H.J.

LEGEND	
■	EXOTHERMIC CONNECTION
●	MECHANICAL CONNECTION
■■■	EQUIPMENT GROUND BAR
■■■	ANTENNA GROUND BAR (AS REQUIRED)
■■■	#2 AWG GROUND LEAD (AS REQUIRED)

NOTE:


- CONTRACTOR TO REPLACE ALL MISSING GROUND BARS AND GROUNDING CONNECTIONS AS REQUIRED.



T Mobile

19807 NORTH CREEK PKWY N
BOTHELL, WA 98011

Technology Associates

SEATTLE MARKET OFFICE
1455 NW LEARY WAY, STE. 400
SEATTLE, WA 98107

DRAWING NOTICE:
THESE DOCUMENTS ARE CONFIDENTIAL
AND ARE THE SOLE PROPERTY OF
T-MOBILE AND MAY NOT BE REPRODUCED,
DISSEMINATED OR REDISTRIBUTED
WITHOUT THE EXPRESS WRITTEN
CONSENT OF T-MOBILE.

REVISIONS:	DESCRIPTION	DATE	BY	REV
ISSUED FOR 90% CD		07/30/2025	MGM	A
ISSUED FOR 100% CD		08/13/2025	MGM	0



SITE NAME:
WEST BAKERVIEW -
SCHLOSSER - SNOPUD

SITE NUMBER:
SE01458B

SITE ADDRESS:
4822 103RD PL SW
MUKILTEO, WA 98275

SHEET DESCRIPTION:
GROUNDING DETAILS

SHEET NUMBER:
G-2



CABLE GROUND KIT TO ANTENNA CABLE CONNECTION

NOTES:

1. DO NOT INSTALL CABLE GROUND KIT AT A BEND AND ALWAYS DIRECT GROUND WIRE DOWN TO GROUND BAR.
2. GROUNDING KIT SHALL BE WITH TWO-HOLE LUG.
3. WEATHERPROOFING SHALL INCORPORATE PPC WEATHERPROOFING TAPE KIT, COLD SHRINK SHALL NOT BE USED.


EXOTHERMIC WELDING

SCALE
N.T.S.

10

CABLE GROUNDING

NEW #6 AWG STRANDED Cu WIRE TO NEW EQUIPMENT
NEW GROUND EQUIPMENT GROUNDING KITS:
#6 AWG STRANDED CU WIRE WITH GREEN, 600V, THWN INSULATION OR BLACK



NOTES:

1. PROVIDE NO-OX GREASE AT CONTACT SURFACE BETWEEN LUG AND GROUND BAR.
2. CONTRACTOR WILL VERIFY BUSS BAR GROUNDING TO THE TOWER OR RING.
3. GROUND BARS AT BOTTOM OF TOWERS OR MONOPLES SHALL USE EXOTHERMIC CONNECTION.

WIRE SIZE	BURNDY LUG	BOLT SIZE
#6 AWG GREEN INSULATED	YA6C-2TC38	3/8" - 16 NC S 2 BOLT
#2 AWG SOLID TINNED	YA3C-2TC38	3/8" - 16 NC S 2 BOLT
#2 AWG STRANDED	YA2C-2TC38	3/8" - 16 NC S 2 BOLT
#2/0 AWG STRANDED	YA26-2TC38	3/8" - 16 NC S 2 BOLT
#4/0 AWG STRANDED	YA28-2N	1/2" - 16 NC S 2 BOLT

NOTES:

1. ALL HARDWARE BOLTS, NUTS, LOCK WASHERS SHALL BE STAINLESS STEEL. ALL HARDWARE ARE TO BE AS FOLLOWS: BOLT, FLAT WASHER, GROUND BAR, GROUND LUG, FLAT WASHER, LOCK WASHER AND NUT.
2. COPPER SHIELD, ANTI-OX, CR NO-OX OR EQUIVALENT SHALL BE PLACE WHERE ALL DISSIMILAR METALS CONNECT.
3. ALL LUGS ARE TO BE INSTALLED PER MANUFACTURER'S SPECIFICATIONS.
4. ALL LUGS MUST HAVE INSPECTION WINDOWS.

12" TO 24"
ANTENNA CABLE
WEATHERPROOFING
KIT (SEE NOTE 3)
#6 AWG STRANDED Cu WIRE WITH
GREEN, 600V, THWN INSULATION OR
BLACK (GROUNDED TO GROUND BAR)

CABLE GROUND KIT TO ANTENNA CABLE CONNECTION

NOTES:

1. DO NOT INSTALL CABLE GROUND KIT AT A BEND AND ALWAYS DIRECT GROUND WIRE DOWN TO GROUND BAR.
2. GROUNDING KIT SHALL BE WITH TWO-HOLE LUG.
3. WEATHERPROOFING SHALL INCORPORATE PPC WEATHERPROOFING TAPE KIT, COLD SHRINK SHALL NOT BE USED.

MAIN GROUND BAR



SCALE
N.T.S.

8

MECHANICAL LUG CONNECTION


SCALE
N.T.S.

2



NOTES:

1. HALO GROUND SHALL BE #2 AWG STRANDED GREEN COPPER WIRE.
2. VERTICAL DROPS SHALL BE #2 AWG STRANDED GREEN COPPER WIRE.
3. ALL BENDS SHALL MAINTAIN A MINIMUM 6" BEND RADIUS.
4. APPLY ANTI-OXIDATION COMPOUND TO ALL CONNECTIONS.
5. ALL GROUNDING WIRES FOR HVAC GRILLS, BOXES, DOORS, CABLE TRAYS, ETC., SHALL BE #6 AWG GREEN STRANDED COPPER WIRE AND A 2-HOLE LUG.
6. BARE COPPER CONDUCTORS SHALL NOT BE IN CONTACT WITH ANY DISSIMILAR MATERIAL. PLACE ON STANDOFFS IF NECESSARY TO ALLOW FOR PROPER INSTALLATION.
7. ALL GROUNDING CONDUCTORS SHALL BE KEPT AS SHORT AS POSSIBLE. THE SHORTEST PRACTICAL ROUTE SHALL BE CHOSEN WITH THE LEAST AMOUNT OF BENDS AND SPLICES. USE THIS RULE AT ALL TIMES, EVEN IF ELEVATION PLAN CONFLICTS. PLANS ARE SOMETIMES UNCLEAR DUE TO SCALE.
8. ALL CONNECTIONS TO GROUND BARS SHALL BE WITH A 2-HOLE LUG, UNO.
9. ALL SOLID WIRE SHALL USE A 2-HOLE LONG-BARREL LUG.
10. WHEN GROUNDING MORE THAN ONE PIECE OF EQUIPMENT, DO NOT USE THE EQUIPMENT AS A GROUNDING CONDUCTOR. DOUBLE STACKING OF LUGS IS NOT ALLOWED TO BE USED.
11. REMOVE ALL PAINT BENEATH THE SURFACE OF GROUND LUGS. INSTALL PANDUIT CLIP AN "Y" DROP AT CABLE TRAY TO AVOID CONTACT WITH CABLE TRAY.
12. ALL GROUND WIRES CONNECTING TO THE HALO SHALL CONNECT IN THE SHORTEST DIRECTION TO THE MAIN GROUND BAR.
13. INSTALL GROUND BAR UNDER INSTALLED COAX. ALL WIRING AT GROUND BAR IS TYPICAL FOR ALL LOCATIONS.



GROUND ROD

SCALE
N.T.S.

12

TEST WELL

SCALE
N.T.S.


9

HALO GROUNDING

SCALE
N.T.S.

3

<p>1. GENERAL NOTES</p> <p>1.1. PROJECT SCOPE: THESE STRUCTURAL DRAWINGS MAY ONLY BE USED TO CONSTRUCT THE PROJECT SHOWN HEREIN, LOCATED AT: 4822 103RD PL SW MUKILTEO, WA 98275</p> <p>1.2. BUILDING CODE: THIS DESIGN IS BASED ON THE INTERNATIONAL BUILDING CODE (IBC), 2021 EDITION. ALL WORK SHALL BE PERFORMED IN ACCORDANCE WITH THIS CODE AND CITY OF SEATTLE REQUIREMENTS.</p> <p>1.3. OCCUPANCY CATEGORY: THIS STRUCTURE IS CLASSIFIED AS A CATEGORY II STRUCTURE.</p> <p>1.4. DESIGN LOADS:</p> <table border="1"> <tr> <td colspan="4">DEAD LOADS (BASED ON SELF WEIGHT OF CONSTRUCTION MATERIALS)</td> </tr> <tr> <td>LOAD CLASSIFICATION</td> <td>AREA</td> <td>CONCENTRATED</td> <td>NOTES</td> </tr> <tr> <td>ROOF</td> <td>13 PSF</td> <td>---</td> <td>---</td> </tr> </table> <table border="1"> <tr> <td colspan="4">LIVE LOADS (BASED ON 2021 INTERNATIONAL BUILDING CODE)</td> </tr> <tr> <td>LOAD CLASSIFICATION</td> <td>AREA</td> <td>CONCENTRATED</td> <td></td> </tr> <tr> <td>ROOFS</td> <td>20 PSF</td> <td>---</td> <td></td> </tr> </table> <table border="1"> <tr> <td colspan="4">SNOW LOADS (BASED ON ASCE 7-16, CHAPTER 7)</td> </tr> <tr> <td>DESIGN VARIABLE</td> <td>VALUE</td> <td colspan="2">NOTES</td> </tr> <tr> <td>GROUND SNOW LOAD</td> <td>20 PSF</td> <td colspan="2">PER MAPS WITHIN THE 2021 IBC</td> </tr> <tr> <td>DESIGN SNOW LOAD</td> <td>20 PSF</td> <td colspan="2">PER MAPS WITHIN THE 2021 IBC</td> </tr> <tr> <td>EXPOSURE FACTOR</td> <td>1.00</td> <td colspan="2">PARTIALLY EXPOSED IN TERRAIN CATEGORY C</td> </tr> <tr> <td>TERMAL FACTOR</td> <td>1.00</td> <td colspan="2">ALL OTHER STRUCTURES</td> </tr> <tr> <td>IMPORTANCE FACTOR</td> <td>1.00</td> <td colspan="2">OCCUPANCY CATEGORY: II</td> </tr> </table> <table border="1"> <tr> <td colspan="4">WIND LOADS (BASED ON ASCE 7-16, CHAPTER 26, THROUGH 30)</td> </tr> <tr> <td>DESIGN VARIABLE</td> <td>VALUE</td> <td colspan="2">NOTES</td> </tr> <tr> <td>3-SECOND WIND SPEED</td> <td>110 MPH</td> <td colspan="2">PER MAPS WITHIN THE 2018 IBC</td> </tr> <tr> <td>EXPOSURE CLASSIFICATION</td> <td>C</td> <td colspan="2">OPEN TERRAIN WITH SCATTERED OBSTRUCTION</td> </tr> </table> <table border="1"> <tr> <td colspan="4">SEISMIC LOADS (BASED ON ASCE 7, CHAPTERS 11 THROUGH 23)</td> </tr> <tr> <td>DESIGN VARIABLE</td> <td>VALUE</td> <td colspan="2">NOTES</td> </tr> <tr> <td>S_s</td> <td>1.402</td> <td colspan="2">SPECTRAL RESPONSE ACCEL. PARAMETER AT SHORT PERIODS</td> </tr> <tr> <td>S₁</td> <td>0.501</td> <td colspan="2">SPECTRAL RESPONSE ACCEL. PARAMETER AT 1-SECOND PERIOD</td> </tr> <tr> <td>SOIL SITE CLASS</td> <td>D</td> <td colspan="2">PER GEOTECH OR ASCE 7 SECTION COEFFICIENT</td> </tr> <tr> <td>IMPORTANCE FACTOR</td> <td>1</td> <td colspan="2">OCCUPANCY CATEGORY: II</td> </tr> <tr> <td>F_a</td> <td>1.2</td> <td colspan="2">SHORT-PERIOD SITE COEFFICIENT</td> </tr> <tr> <td>F_v</td> <td>-</td> <td colspan="2">1-SECOND PERIOD SITE COEFFICIENT</td> </tr> <tr> <td>S_{ds}</td> <td>1.122</td> <td colspan="2">DESIGN SPECTRAL RESPONSE ACCEL. PARA AT 1-SECOND PERIOD</td> </tr> <tr> <td>S_{d1}</td> <td>N/A</td> <td colspan="2">DESIGN SPECTRAL RESPONSE ACCEL PARA AT 1-SECOND PERIOD</td> </tr> <tr> <td>SEISMIC DESIGN CATEGORY</td> <td>D</td> <td colspan="2">BASED ON 1-SEC AND SHORT PERIOD ACCELERATION PARAMETER</td> </tr> <tr> <td>R</td> <td>6.5</td> <td colspan="2">RESPONSE MODIFICATION COEFFICIENT</td> </tr> <tr> <td>LATERAL FORCE SYSTEM</td> <td colspan="3">LIGHT FRAME (WOOD) SHEATHING WOOD STRUCTURAL PANELS RATED FOR SHEAR RESISTANCE</td> </tr> </table> <p>1.5. GENERAL CONSTRUCTION REQUIREMENTS:</p> <p>1.5.1. CONSTRUCTION METHOD THE CONTRACT STRUCTURAL DRAWINGS & SPECIFICATIONS REPRESENT THE FINISHED STRUCTURE. THEY DO NOT INDICATE THE CONTRACTOR'S MEANS, METHODS, TECHNIQUES, PROCEDURES, SEQUENCES OF CONSTRUCTION OR JOB SITE SAFETY. THE ENGINEER OF RECORD IS NOT RESPONSIBLE FOR THE CONTRACTOR'S FAILURE TO FOLLOW PLANS, SPECIFICATIONS, AND/OR ENGINEERING RECOMMENDATIONS, NOR IS TECHNOLOGY ASSOCIATES RESPONSIBLE FOR ECONOMIC LOSS AND/OR DELAYS OF THE CONTRACTOR OR SUBCONTRACTORS.</p> <p>WHERE CONSTRUCTION MATERIALS ARE PLACED ON FRAMED FLOORS AND/OR ROOFS, THEY SHALL BE SPREAD OUT AND NOT CONCENTRATED IN ANY GIVEN AREA. THE LIVE LOADS SHOWN IN THE TABLE ABOVE SHALL NOT BE EXCEEDED UNDER ANY CIRCUMSTANCES. ALL CONSTRUCTION SHALL BE ADEQUATELY BRAZED TO PREVENT DISTORTION AND DAMAGE DUE TO CONSTRUCTION LOADS AND NATURAL FORCES.</p> <p>THE CONTRACTOR IS RESPONSIBLE FOR SAFETY PRECAUTIONS, PROCEDURES AND PROGRAMS FOR THIS PROJECT THAT SHALL COMPLY WITH THE REGULATIONS OF THE OCCUPATIONAL SAFETY AND HEALTH ADMINISTRATION (OSHA).</p> <p>1.5.2. TRADE COORDINATION THE STRUCTURAL DRAWINGS ARE TO BE USED IN CONJUNCTION WITH THE ARCHITECTURAL, ELECTRICAL, MECHANICAL, PLUMBING AND SITE DRAWINGS. CONFLICTS IN DIMENSION AND INTERFERENCE SHALL BE DIRECTED TO THE ARCHITECT PRIOR TO CONSTRUCTION.</p> <p>1.5.3. DISCREPANCIES IF CONFLICT ARISES FROM THE RECOMMENDATIONS OF THESE DRAWINGS AND THOSE CONTAINED IN THE SPECIFICATIONS, THE GREATER REQUIREMENTS SHALL GOVERN.</p> <p>1.5.4. OPENINGS LOCATE AND VERIFY ALL OPENINGS, SLEEVES, POCKETS, CONDUITS, AND INSERTS FOR ARCHITECTURAL, MECHANICAL, PLUMBING, WITH APPROPRIATE TRADES DRAWINGS AND SUBCONTRACTORS PRIOR TO CONSTRUCTION. THESE OPENINGS, SLEEVES, POCKETS, CONDUITS, AND INSERTS SHALL NOT BE PLACED IN BEAMS, JOISTS, COLUMNS, ETC. UNLESS SPECIFICALLY DETAILED ON THE STRUCTURAL DRAWINGS. TECHNOLOGY ASSOCIATES IS TO BE NOTIFIED WHEN OPENINGS, SLEEVES, POCKETS, ETC. ARE TO BE LOCATED IN STRUCTURAL MEMBERS AND ARE NOT SHOWN ON THE STRUCTURAL DRAWINGS.</p> <p>1.5.5. TYPICAL DETAILS TYPICAL DETAILS ARE NOT NECESSARILY CUT ON THE DRAWINGS, BUT SHALL APPLY UNLESS NOTED OTHERWISE.</p> <p>1.5.6. ENGINEERED DESIGNS BY OTHERS ANY ENGINEERED DESIGN PROVIDED BY OTHERS AND SUBMITTED FOR REVIEW SHALL BEAR THE SIGNATURE AND SEAL OF THE ENGINEER PERFORMING THE WORK. THE ENGINEER IS TO BE REGISTERED IN THE STATE OF WASHINGTON.</p> <p>1.5.7. REFERENCED MATERIAL STANDARDS WHERE REFERENCE IS MADE TO VARIOUS MATERIAL TEST STANDARDS, THE MOST CURRENT STANDARD AND ADDENDUM ARE TO BE INCORPORATED INTO THIS CONSTRUCTION, UNLESS NOTED OTHERWISE.</p> <p>1.5.8. DRAWING DIMENSIONS NO DIMENSION IS TO BE DETERMINED BY SCALING THE DRAWINGS OR DETAILS. IF A DIMENSION IS NOT INDICATED ON THE DRAWINGS AND IS NEEDED, CONTACT THE STRUCTURAL ENGINEER FOR CLARIFICATION. IF DISCREPANCIES ARE FOUND BETWEEN THE STRUCTURAL DRAWINGS AND THE ARCHITECTURAL DRAWINGS, CONTACT THE STRUCTURAL ENGINEER OR THE ARCHITECT FOR CLARIFICATION.</p> <p>1.5.9. PROPRIETARY PRODUCTS WHERE PROPRIETARY PRODUCTS FROM SPECIFIC MANUFACTURERS ARE LISTED IN THE STRUCTURAL DRAWINGS, THE CONTRACTOR MAY SUBSTITUTE OTHER PRODUCTS FROM OTHER MANUFACTURERS ONLY AFTER THE APPROVAL FROM TECHNOLOGY ASSOCIATES. THE CONTRACTOR IS TO PREPARE A SUBMITTAL THAT SPECIFICALLY STATES THE ORIGINALLY SPECIFIED PRODUCT, AND ITS ASSOCIATED PROPERTIES SHOWN IN THESE DRAWINGS, ALONG WITH THE REQUESTED REPLACEMENT PRODUCT, AND ITS ASSOCIATED PROPERTIES. THE PROPERTIES OF THE REPLACEMENT PRODUCT ARE TO MEET OR EXCEED THOSE LISTED FOR THE ORIGINAL PRODUCT. THE REPLACEMENT REQUEST IS TO BE SUBMITTED TO TECHNOLOGY ASSOCIATES A MINIMUM OF 2 WEEKS PRIOR TO THE START OF FABRICATION OR CONSTRUCTION. REPLACEMENT PRODUCT REQUESTS SUBMITTED AFTER THIS TIME WILL NOT BE CONSIDERED.</p> <p>1.5.10. OPTIONS & SUBSTITUTIONS WHERE OPTIONS ARE SHOWN ON THE DRAWINGS, OR WHERE THE CONTRACTOR SUBSTITUTES ONE PRODUCT FOR AN APPROVED ALTERNATE PRODUCT, THE CONTRACTOR SHALL BE RESPONSIBLE FOR ALL RESULTING CHANGES NECESSARY AND SHALL COORDINATE ALL DETAILS FOR THE OPTION OR SUBSTITUTION WITH OTHER TRADES.</p> <p>2. FOUNDATIONS & SLABS ON GRADE</p> <p>2.1. GEOTECHNICAL INVESTIGATION: TECHNOLOGY ASSOCIATES RECOMMENDS THAT THE PROJECT OWNER RETAIN THE DESIGN SERVICES OF A GEOTECHNICAL ENGINEER IN AN EFFORT TO BETTER UNDERSTAND THE SOIL PROPERTIES PRESENT AT THIS SITE. TECHNOLOGY ASSOCIATES WILL NOT BE RESPONSIBLE FOR ADVERSE EFFECTS THAT ARISE IN THE STRUCTURE THAT RESULT FROM UNKNOWN SOIL CONDITIONS.</p> <p>IN THE ABSENCE OF A GEOTECHNICAL REPORT, MINIMUM DESIGN VALUES AS SPECIFIED IN THE IBC HAVE BEEN USED IN THE DESIGN OF THE FOUNDATIONS.</p> <table border="1"> <tr> <td colspan="4">FOUNDATION DESIGN VALUES AND NOTES PER GEOTECHNICAL REPORT</td> </tr> <tr> <td>PARAMETER</td> <td>VALUE</td> <td colspan="2">VALUE</td> </tr> <tr> <td>ALLOWABLE BEARING PRESSURE</td> <td>1500 PSF</td> <td colspan="2">BEARING DEPTH OF 18"</td> </tr> </table> <p>2.2. SPREAD FOOTINGS: CONVENTIONAL SPREAD-TYPE FOOTINGS HAVE BEEN DESIGNED FOR THE VALUES SHOW IN THE CHART ABOVE AND SHALL BEAR ON COMPACTED NATIVE SITE SOILS. BOTTOM OF FOOTINGS SHALL BE 18" BELOW ADJACENT GRADE. ADJACENT GRADE IS DEFINED AS LOWEST ADJACENT GRADE WITHIN 5'-0" OF THE FOUNDATION FOR EXTERIOR FOOTINGS AND FINISHED FLOOR LEVEL FOR INTERIOR FOOTINGS.</p> <p>THE SUB GRADE BELOW THE FOOTINGS IS TO BE INSPECTED AND SIGNED OFF BY THE GEOTECHNICAL ENGINEER OF RECORD TO VERIFY THE REQUIREMENTS NOTED IN THE GEOTECHNICAL REPORT HAVE BEEN SATISFIED.</p> <p>2.3. SLABS ON GRADE: SLAB ON GRADE SHALL GENERALLY BE ISOLATED FROM ALL WALLS, COLUMNS, AND SERVICE PENETRATIONS USING A 1/2" JOINT PER THE ARCHITECTURAL DRAWINGS.</p> <p>ALL SLABS SHALL BE FINISHED IN ACCORDANCE WITH ACI STANDARD 302 "GUIDE OF CONCRETE FLOOR AND SLAB CONSTRUCTION" AND ACI STANDARD 360R "GUIDE TO DESIGN OF SLABS-ON-GROUND".</p> <p>SAW CUT CONCRETE (WITHIN 18 HOURS OF PLACING CONCRETE) SUCH THAT NO MORE THAN 150 SQUARE FEET OF SLAB ARE WITHIN A GRID. SAW CUT JOINTS SHOULD BE SPACED AT NO MORE THAN 15 FEET ON CENTER OR AS INDICATED ON THE DRAWINGS.</p> <p>A MINIMUM OF 4-INCH LAYER OF CLEAN, GRADED GRAVEL OR CRUSHED ROCK DEVOID OF FINES SHOULD BE PLACED BELOW THE SLAB, U.N.C.</p> <p>IN MOISTURE SENSITIVE AREAS, OR AREAS REQUIRED BY THE ARCHITECT, A MINIMUM 10 MIL VAPOR BARRIER LAPPED 6 INCHES AND TAPED PER MANUFACTURER. RECOMMENDATIONS SHALL BE PROVIDED, I.N.O. ANY DAMAGE TO THE VAPOR BARRIER SHALL BE REPAIRED PRIOR TO POURING SLAB IN ACCORDANCE WITH MANUFACTURER RECOMMENDATIONS.</p> <p>SLABS WITH VAPOR SENSITIVE COVERINGS SHALL BE PLACED DIRECTLY OVER VAPOR BARRIER, WHICH IS PLACED OVER A DRY AGGREGATE BASE COURSE. TO MINIMIZE SLAB CURL, CONTRACTOR SHALL PROVIDE A LOW SHRINKAGE CONCRETE MIX DESIGN.</p> <p>CONCRETE CLOSURE POURS AROUND COLUMNS SHALL NOT BE PLACED BEFORE THE FULL COLUMN DEAD LOAD IS IN PLACE.</p> <p>SLAB DOWELS SHALL BE PER PNA CONSTRUCTION TECHNOLOGIES, OR APPROVED EQUIVALENT. SLAB DOWELS, WHERE INDICATED ON THE PLANS SHALL BE PER PNA CONSTRUCTION TECHNOLOGIES (OR APPROVED EQUIVALENT). AT SAW CUT JOINTS, 2 3/8" TAPERED PLATE DOWELS ARE TO BE USED. AT FORMED CONSTRUCTION JOINTS, 1/4" THICK DIAMOND DOWELS ARE TO BE USED.</p> <p>3. CONCRETE</p> <p>3.1. GENERAL REQUIREMENTS ALL CONCRETE SHALL BE MIXED, TRANSPORTED AND PLACED IN ACCORDANCE WITH ACI STANDARD 301 "STANDARD SPECIFICATIONS FOR STRUCTURAL CONCRETE" AND ACI STANDARD 318 "BUILDING CODE REQUIREMENTS FOR STRUCTURAL CONCRETE". ALL CONCRETE SHALL BE CONSTRUCTED WITHIN THE TOLERANCES SPECIFIED IN ACI STANDARD 117 "SPECIFICATION FOR TOLERANCES FOR CONCRETE CONSTRUCTION AND MATERIALS".</p> <p>3.2. MIXING REQUIREMENTS</p> <table border="1"> <tr> <td colspan="6">CONCRETE MIX REQUIREMENTS</td> </tr> <tr> <td>INTENDED USE</td> <td>f_c</td> <td>SLUMP AT PLACEMENT</td> <td>MAX W/c RATIO</td> <td>MAX AGGREGATE</td> <td>AIR ENTRAINMENT</td> </tr> <tr> <td>SPREAD FOOTING & WALL FUNDINGS</td> <td>3000 PSI</td> <td>3" TO 5"</td> <td>---</td> <td>3/4"</td> <td>6 ± 1.5</td> </tr> <tr> <td>SLABS ON GRADE (INTERIOR)</td> <td>3000 PSI</td> <td>5" TO 7"</td> <td>---</td> <td>3/4"</td> <td>6 ± 1.5</td> </tr> <tr> <td>SLABS ON GRADE (EXTERIOR)</td> <td>3000 PSI</td> <td>5" TO 7"</td> <td>---</td> <td>3/4"</td> <td>6 ± 1.5</td> </tr> </table> <p>EVEN THOUGH A HIGHER CONCRETE COMPRESSIVE STRENGTH IS SHOWN FOR FOUNDATIONS, THEIR DESIGN HAS BEEN BASED ON A COMPRESSIVE STRENGTH OF 2500 PSI.</p> <p>NO WATER SHALL BE ADDED TO THE MIX ON SITE OR DURING TRANSPORT, UNLESS IT HAS SPECIFICALLY BEEN WITHHELD FROM THE MIX AT THE BATCH PLANT. IF WATER WAS WITHHELD, THE BATCH TICKET SHALL SPECIFICALLY INDICATE THE AMOUNT OF WATER THAT WAS WITHHELD AND THE AMOUNT OF WATER THAT IS ALLOWED TO BE ADDED BEFORE PLACEMENT. AFTER THE ADDITION OF ALL WATER, THE MAXIMUM WATER TO CEMENTITIOUS MATERIAL RATIO NOTED ABOVE IS NOT TO BE EXCEEDED.</p> <p>IF CONCRETE IS TO RECEIVE A SUPERPLASTICIZING ADMIXTURE, THE SLUMP OF THE CONCRETE SHALL NOT EXCEED 4" ± 1" BEFORE ADDITION OF THE ADMIXTURE. THE SLUMP OF THE CONCRETE AFTER THE ADDITION OF THE ADMIXTURE SHALL NOT EXCEED 8" ± 1" AFTER THE ADDITION OF THE ADMIXTURE.</p> <p>VARIOUS CEMENTITIOUS MATERIAL MAY BE USED IN THE CONCRETE MIXES NOTED ABOVE, BUT ARE LIMITED TO THE MAXIMUM PERCENTAGES OF TOTAL CEMENTITIOUS MATERIAL SHOWN IN THE TABLE BELOW. USE OF ALL CEMENTITIOUS MATERIALS NOTED BELOW SHALL BE VERIFIED BY THE CONTRACTOR WITH THE ARCHITECTURAL REQUIREMENTS FOR THE PROJECT.</p> <table border="1"> <tr> <td colspan="4">CEMENTITIOUS MATERIAL REQUIREMENTS</td> </tr> <tr> <td>CEMENTITIOUS MATERIAL</td> <td>REFERRED STANDARD</td> <td colspan="2">MAXIMUM AMOUNT</td> </tr> <tr> <td>FLY ASH OR OTHER POZZOLANS</td> <td>ASTM C618</td> <td colspan="2">25%</td> </tr> <tr> <td>SLAG</td> <td>ASTM C989</td> <td colspan="2">50%</td> </tr> <tr> <td>SILICA FUME</td> <td>ASTM C1240</td> <td colspan="2">10%</td> </tr> <tr> <td>TOTAL OF FLY ASH, OTHER POZZOLANS, SLAG, AND SILICA FUME</td> <td>---</td> <td colspan="2">50%</td> </tr> <tr> <td>TOTAL OF FLY ASH, OTHER POZZOLANS AND SILICA FUME</td> <td>---</td> <td colspan="2">35%</td> </tr> </table> <p>WHERE ANY OF THE ABOVE MATERIALS ARE USED IN COMBINATION, THE INDIVIDUAL LIMITS ARE STILL APPLICABLE, IN ADDITION TO THE TOTAL LIMITS.</p> <p>STRENGTH TEST RECORDS FOR EACH CONCRETE MIX USED ON THE PROJECT SHALL BE SUBMITTED IN ACCORDANCE WITH THE REQUIREMENTS OF ACI 318, CHAPTER 5.</p> <p>3.3. PLACEMENT REQUIREMENTS ALL CONCRETE IS TO BE MECHANICALLY VIBRATED UPON PLACEMENT. SLABS ON GRADE NEED ONLY BE VIBRATED AT REINFORCING LOCATIONS, ANCHOR LOCATIONS, SLAB EDGES, AND KEYS. REINFORCING LOCATIONS, ANCHOR LOCATIONS, SLAB EDGES, AND KEYS. FOR CONCRETE DRILLED PIER FOUNDATIONS, ONLY THE TOP 5 FEET OF THE PIER REQUIRES MECHANICAL VIBRATION AND IT IS TO BE VIBRATED 15 MINUTES AFTER CONCRETE PLACEMENT.</p> <p>AMBIENT AIR WASHINGTON/NATURE CONCRETE WASHINGTON/NATURE RELATIVE HUMIDITY, WIND SPEED AND SOLAR RADIATION TO ALL INFLUENCE CONCRETE'S PROPERTIES. FOR THIS REASON, THE REQUIREMENTS OF ACI 305 "HOT WEATHER CONCRETING" AND ACI 306 "COLD WEATHER CONCRETING" ARE TO BE FOLLOWED.</p> <p>3.4. REINFORCING REQUIREMENTS</p> <p>3.4.1. REINFORCING MATERIAL REQUIREMENTS REFER TO THE MAIN REINFORCING SECTION OF THIS G.S.N. FOR ADDITIONAL REINFORCING MATERIAL REQUIREMENTS NOT SHOWN IN THIS SECTION.</p> <p>3.4.2. LAP SPLICES LAP SPLICES ARE TO BE PER THE LAP SPLICE SCHEDULE IN THE TYPICAL DETAILS. ALL SPLICE LOCATIONS ARE SUBJECT TO APPROVAL. BENT BARS ARE TO BE PROVIDED AT ALL CORNERS AND INTERSECTIONS AND ARE TO MATCH AND LAP HORIZONTAL REINFORCING BARS IN WALLS AND FOOTINGS.</p> <p>4. REINFORCING (CONCRETE)</p> <p>4.1. STEEL REINFORCING</p> <p>4.1.1. REINFORCING BARS - REFERENCED STANDARDS ALL STEEL REINFORCING BARS SHALL BE MANUFACTURED AND PLACED IN ACCORDANCE WITH ACI STANDARD 301, "SPECIFICATIONS FOR STRUCTURAL CONCRETE BUILDINGS", ACI 318, "BUILDING CODE REQUIREMENTS FOR STRUCTURAL CONCRETE", ACI SP-66, "ACI DETAILING MANUAL", AWS D1.4, "STRUCTURAL WELDING CODE - REINFORCING STEEL", CRSI DA-4, "MANUAL OF STANDARD PRACTICE", AND CRSI P1, "PLACING REINFORCING BARS", DA-530, "MANUAL OF STANDARD PRACTICE", CRSI P1, "PLACING REINFORCING BARS", ACI 530, "BUILDING CODE REQUIREMENTS FOR MASONRY STRUCTURES", AND ACI 530.1, "SPECIFICATION FOR MASONRY STRUCTURES"</p> <table border="1"> <tr> <td colspan="4">REINFORCING BARS - MATERIAL REQUIREMENTS</td> </tr> <tr> <td>BAR TYPES</td> <td>DESIGNATION</td> <td>YIELD STRENGTH</td> <td>NOTES</td> </tr> <tr> <td>#5 BARS AND SMALLER (NON-WELDABLE)</td> <td>ASTM A615</td> <td>60 KSI</td> <td>---</td> </tr> </table> <p>4.1.2. REINFORCING BARS - INSTALLATION REQUIREMENTS ALL REINFORCING IS TO BE SECURELY SET INTO PLACE BEFORE CONCRETE PLACEMENT. PLACEMENT OF CONCRETE AND OTHER CONSTRUCTION RELATED PROCESSES SHALL NOT DISPLACE THE REINFORCING MORE THAN THE SPECIFIED TOLERANCES FOR REINFORCEMENT PLACEMENT. REINFORCING BAR SPACING SHOWN IN THE PLANS AND DETAILS ARE MAXIMUM ON CENTER SPACING.</p> <p>4.1.3. REINFORCING BARS - BENDS REINFORCING BARS ARE TO BE BENT PER THE TYPICAL DETAIL. THESE BENDS SHALL BE COMPLETED IN THE SHOP UNDER CONTROLLED CONDITIONS. FIELD BENDING OF REINFORCING BARS IS ONLY PERMITTED UNDER CERTAIN CIRCUMSTANCES, WHICH ARE OUTLINED IN THE TABLE BELOW. FIELD BENDING OF REINFORCING BARS SHALL NOT BE COMPLETED ON BARS LARGER THAN #4. HEAT IS TO BE APPLIED TO ALL #6 BARS AND LARGER AND ALL #5 BARS THAT HAVE BEEN PREVIOUSLY HEATED. ONLY #4 BARS AND SMALLER AND #5 BARS WHICH HAVE NOT BEEN PREVIOUSLY HEATED MAY BE BENT IN THE FIELD WITHOUT APPLYING HEAT. IN APPLYING HEAT, THE ENTIRE BEND LENGTH, PLUS 2" ON EACH END IS TO BE HEATED TO A UNIFORM WASHINGTON/NATURE THROUGHOUT THE THICKNESS OF THE BAR.</p> <table border="1"> <tr> <td colspan="4">REQUIREMENTS FOR FIELD BENDING OF REINFORCING BARS</td> </tr> <tr> <td>BAR</td> <td>INSIDE BEND</td> <td>REQUIRED WASHINGTON TEMPERATURE RANGE</td> <td>NOTES</td> </tr> <tr> <td>SIZE</td> <td>DIAMETER</td> <td>MINIMUM</td> <td>MAXIMUM</td> </tr> <tr> <td>#5</td> <td>8 BAR DIAMETERS</td> <td>1300°F</td> <td>1400°F</td> </tr> </table> <p>4.1.4. REINFORCING BARS - CLEAR DISTANCES IN CONCRETE CONSTRUCTION CONCRETE REINFORCING BARS ARE TO BE PLACED IN ORDER TO MAINTAIN THE FOLLOWING CLEAR DISTANCES</p> <table border="1"> <tr> <td colspan="4">CLEAR DISTANCES FOR CONCRETE REINFORCING BARS</td> </tr> <tr> <td>CONDITION</td> <td>BAR SIZE</td> <td>CLEAR DISTANCE</td> <td>NOTES</td> </tr> <tr> <td>CAST AGAINST & PERMANENTLY EXPOSED TO EARTH</td> <td>ALL</td> <td>3"</td> <td>---</td> </tr> <tr> <td>FORMED CONCRETE EXPOSED TO EARTH AND WEATHER</td> <td>#5 & SMALLER</td> <td>2"</td> <td>---</td> </tr> <tr> <td></td> <td>#6 & LARGER</td> <td>1 1/2"</td> <td>---</td> </tr> </table> <p>4.2. CAST IN PLACE ANCHORS & EMBEDMENT</p> <p>4.2.1. CAST IN PLACE ANCHORS - MATERIAL REQUIREMENTS CAST IN PLACE ANCHORS INCLUDE HEADED, HOOKED, AND THREADED ANCHOR ROD. ANCHOR MATERIAL SHALL BE PER THE TABLE BELOW AND ARE TO BE MANUFACTURED AND SUPPLIED IN ACCORDANCE WITH THE REFERENCED SPECIFICATION.</p> <table border="1"> <tr> <td colspan="4">CAST IN PLACE ANCHORS - MATERIAL REQUIREMENTS</td> </tr> <tr> <td>TYPE</td> <td>SPECIFICATION</td> <td>GRADE</td> <td>REQUIREMENTS WHEN WELDED TO PLATE OR MEMBER</td> </tr> <tr> <td>ANCHOR RODS</td> <td>ASTM F1554</td> <td>36</td> <td>---</td> </tr> <tr> <td>HOOKED ANCHORS</td> <td>ASTM F1554</td> <td>36</td> <td>---</td> </tr> </table> <p>WHEN ASTM F1554 GRADE 55 ANCHORS ARE SPECIFIED, THE MATERIAL SHALL BE ORDERED WITH SUPPLEMENT S1, TO ENSURE WELDABILITY BUT ARE ONLY TO BE WELDED WHERE SPECIFICALLY INDICATED ON THE STRUCTURAL DRAWINGS. ASTM F1554 GRADE 36 ANCHORS MAY BE WELDED, BUT ONLY WHERE SPECIFICALLY INDICATED ON THE STRUCTURAL DRAWINGS. ASTM F1554 GRADE 105 ANCHORS ARE NEVER TO BE WELDED. WHERE ASTM F1554 GRADE 36 ANCHORS ARE SPECIFIED, ANCHORS PER ASTM A36 MAY BE USED FOR ANCHOR ROD APPLICATIONS.</p> <p>UNLESS NOTED OTHERWISE, ALL NUTS USED ON ANCHORS SHALL BE PER ASTM A194 AND SHALL BE A COMPATIBLE GRADE, SURFACE FINISH, AND STYLE FOR EACH GRADE, AND SIZE OF ANCHOR BOLT USED.</p> <p>4.2.2. CAST IN PLACE ANCHORS - CONSTRUCTION REQUIREMENTS WHERE THREADED, HEADED, DEFORMED, OR HOOKED ANCHORS ARE TO BE WELDED TO A PLATE OR OTHER MEMBER THEY SHALL BE AUTOMATICALLY WELDED TO THE CONNECTING PLATE OR MEMBER.</p> <p>ANCHOR RODS ALONE ARE NOT TO BE USED TO TRANSFER ANY LOADS. THE ANCHORING MECHANISM SHALL CONSIST OF TWO NUTS ON THE EMBEDDED END OF THE ROD WITH A PLATE WASHER BETWEEN THE NUTS. THE NUTS ARE TO BE TIGHTENED AGAINST EACH OTHER AND THE PLATE WASHER TO SECURE THEM IN PLACE. THE END OF THE ROD IS TO PROTRUDE 1/2" MINIMUM BEYOND THE LAST NUT AND THE ROD THREADS ARE TO BE DINGED ABOVE AND BELOW THE NUTS, AFTER THE NUTS ARE TIGHTENED TO PREVENT THEM FROM SPINNING OFF DURING CONSTRUCTION.</p> <p>5. WOOD</p> <p>5.1. GENERAL REQUIREMENTS</p> <p>5.1.1. REFERENCED STANDARDS ALL WOOD CONSTRUCTION TO BE MANUFACTURED AND INSTALLED IN ACCORDANCE WITH THE NDS, "NATIONAL DESIGN SPECIFICATION FOR WOOD CONSTRUCTION".</p> <p>5.1.2. NOTCHING & DRILLING OF MEMBERS NO WOOD FRAMING MEMBER SHALL BE DRILLED OR NOTCHED UNLESS SPECIFICALLY SHOWN ON THE STRUCTURAL DRAWINGS OR WITHOUT PRIOR APPROVAL FROM TECHNOLOGY ASSOCIATES.</p> <p>5.2. SAWN LUMBER</p> <p>5.2.1. MATERIAL REQUIREMENTS ALL SAWN LUMBER SHALL COMPLY WITH THE GRADING REQUIREMENTS OF THE WWP, WCLIB, SPIB, OR PRE APPROVED EQUIVALENT, AND SHALL BE IN ACCORDANCE WITH THE REQUIREMENTS NOTED IN THE TABLE BELOW.</p> <table border="1"> <tr> <td colspan="4">MATERIAL REQUIREMENTS - SAWN LUMBER</td> </tr> <tr> <td>APPLICATION</td> <td>SUBCATEGORY</td> <td>WOOD SPECIES</td> <td>WOOD GRADE</td> <td>NOTES</td> </tr> <tr> <td>WALL PLATES</td> <td>TOP PLATES</td> <td>Douglas Fir-Larch</td> <td>#2</td> <td>---</td> </tr> <tr> <td>WALL PLATES</td> <td>BOTTOM PLATES</td> <td>Douglas Fir-Larch</td> <td>#2</td> <td>---</td> </tr> <tr> <td>STUDS</td> <td>2x6 OR LARGER</td> <td>Douglas Fir-Larch</td> <td>#2</td> <td>---</td> </tr> </table> <p>5.2.2. CONSTRUCTION REQUIREMENTS IN WOOD FRAMING, UNLESS NOTED OTHERWISE, PROVIDE DOUBLE STUDS AT ALL JAMBS, CORNERS, INTERSECTIONS AND AT LOCATIONS OF ISOLATED BEARING APPLICATIONS. UNLESS NOTED OTHERWISE, PROVIDE SIMPSON H3 ANCHORS AT EACH WALL STUD TO PLATE CONNECTION (BOTH AT THE TOP AND BOTTOM).</p> <p>PROVIDE 2" BLOCKING BETWEEN JOISTS AND RAFTERS AT ALL BEARING POINT</p> <p>5.3. WOOD STRUCTURAL PANELS</p> <p>5.3.1. REFERENCED STANDARDS ALL WOOD STRUCTURAL PANELS SHALL MEET THE REQUIREMENTS OF DOC PS 1 "STRUCTURAL PLYWOOD" AND DOC PS 2 "PERFORMANCE STANDARD FOR WOOD-BASED STRUCTURAL-USE PANELS".</p> <p>5.3.2. MATERIAL REQUIREMENTS ALL PANELS WHICH HAVE ANY EDGE OR SURFACE EXPOSED LONG TERM TO THE WEATHER SHALL BE CLASSED EXTERIOR. ALL WOOD STRUCTURAL PANELS SHALL BE IN ACCORDANCE WITH THE REQUIREMENTS NOTED IN THE TABLE BELOW. EACH PANEL SHALL BE MARKED WITH THE APA APPROVED STAMP, INDICATING THE PANEL GRADE, SPAN RATING, BOND CLASSIFICATION, DECIMAL THICKNESS, PRODUCT STANDARD, AND PERFORMANCE CATEGORY.</p> <p>ALL PANELS THAT HAVE AN EDGE, END, OR SURFACE THAT WILL HAVE LONG TERM EXPOSURE TO WEATHER SHALL BE SUPPLIED WITH THE EXTERIOR BOND CLASSIFICATION. ALL OTHER PANELS ARE TO BE SUPPLIED WITH THE EXPOSURE 1 BOND CLASSIFICATION.</p> <table border="1"> <tr> <td colspan="5">MATERIAL REQUIREMENTS - WOOD STRUCTURAL PANELS</td> </tr> <tr> <td>APPLICATION</td> <td>PANEL GRADE</td> <td>MINIMUM NOMINAL PANEL THICKNESS</td> <td>SPAN RATING</td> <td>NOTES</td> </tr> <tr> <td</tr></table>										DEAD LOADS (BASED ON SELF WEIGHT OF CONSTRUCTION MATERIALS)				LOAD CLASSIFICATION	AREA	CONCENTRATED	NOTES	ROOF	13 PSF	---	---	LIVE LOADS (BASED ON 2021 INTERNATIONAL BUILDING CODE)				LOAD CLASSIFICATION	AREA	CONCENTRATED		ROOFS	20 PSF	---		SNOW LOADS (BASED ON ASCE 7-16, CHAPTER 7)				DESIGN VARIABLE	VALUE	NOTES		GROUND SNOW LOAD	20 PSF	PER MAPS WITHIN THE 2021 IBC		DESIGN SNOW LOAD	20 PSF	PER MAPS WITHIN THE 2021 IBC		EXPOSURE FACTOR	1.00	PARTIALLY EXPOSED IN TERRAIN CATEGORY C		TERMAL FACTOR	1.00	ALL OTHER STRUCTURES		IMPORTANCE FACTOR	1.00	OCCUPANCY CATEGORY: II		WIND LOADS (BASED ON ASCE 7-16, CHAPTER 26, THROUGH 30)				DESIGN VARIABLE	VALUE	NOTES		3-SECOND WIND SPEED	110 MPH	PER MAPS WITHIN THE 2018 IBC		EXPOSURE CLASSIFICATION	C	OPEN TERRAIN WITH SCATTERED OBSTRUCTION		SEISMIC LOADS (BASED ON ASCE 7, CHAPTERS 11 THROUGH 23)				DESIGN VARIABLE	VALUE	NOTES		S _s	1.402	SPECTRAL RESPONSE ACCEL. PARAMETER AT SHORT PERIODS		S ₁	0.501	SPECTRAL RESPONSE ACCEL. PARAMETER AT 1-SECOND PERIOD		SOIL SITE CLASS	D	PER GEOTECH OR ASCE 7 SECTION COEFFICIENT		IMPORTANCE FACTOR	1	OCCUPANCY CATEGORY: II		F _a	1.2	SHORT-PERIOD SITE COEFFICIENT		F _v	-	1-SECOND PERIOD SITE COEFFICIENT		S _{ds}	1.122	DESIGN SPECTRAL RESPONSE ACCEL. PARA AT 1-SECOND PERIOD		S _{d1}	N/A	DESIGN SPECTRAL RESPONSE ACCEL PARA AT 1-SECOND PERIOD		SEISMIC DESIGN CATEGORY	D	BASED ON 1-SEC AND SHORT PERIOD ACCELERATION PARAMETER		R	6.5	RESPONSE MODIFICATION COEFFICIENT		LATERAL FORCE SYSTEM	LIGHT FRAME (WOOD) SHEATHING WOOD STRUCTURAL PANELS RATED FOR SHEAR RESISTANCE			FOUNDATION DESIGN VALUES AND NOTES PER GEOTECHNICAL REPORT				PARAMETER	VALUE	VALUE		ALLOWABLE BEARING PRESSURE	1500 PSF	BEARING DEPTH OF 18"		CONCRETE MIX REQUIREMENTS						INTENDED USE	f _c	SLUMP AT PLACEMENT	MAX W/c RATIO	MAX AGGREGATE	AIR ENTRAINMENT	SPREAD FOOTING & WALL FUNDINGS	3000 PSI	3" TO 5"	---	3/4"	6 ± 1.5	SLABS ON GRADE (INTERIOR)	3000 PSI	5" TO 7"	---	3/4"	6 ± 1.5	SLABS ON GRADE (EXTERIOR)	3000 PSI	5" TO 7"	---	3/4"	6 ± 1.5	CEMENTITIOUS MATERIAL REQUIREMENTS				CEMENTITIOUS MATERIAL	REFERRED STANDARD	MAXIMUM AMOUNT		FLY ASH OR OTHER POZZOLANS	ASTM C618	25%		SLAG	ASTM C989	50%		SILICA FUME	ASTM C1240	10%		TOTAL OF FLY ASH, OTHER POZZOLANS, SLAG, AND SILICA FUME	---	50%		TOTAL OF FLY ASH, OTHER POZZOLANS AND SILICA FUME	---	35%		REINFORCING BARS - MATERIAL REQUIREMENTS				BAR TYPES	DESIGNATION	YIELD STRENGTH	NOTES	#5 BARS AND SMALLER (NON-WELDABLE)	ASTM A615	60 KSI	---	REQUIREMENTS FOR FIELD BENDING OF REINFORCING BARS				BAR	INSIDE BEND	REQUIRED WASHINGTON TEMPERATURE RANGE	NOTES	SIZE	DIAMETER	MINIMUM	MAXIMUM	#5	8 BAR DIAMETERS	1300°F	1400°F	CLEAR DISTANCES FOR CONCRETE REINFORCING BARS				CONDITION	BAR SIZE	CLEAR DISTANCE	NOTES	CAST AGAINST & PERMANENTLY EXPOSED TO EARTH	ALL	3"	---	FORMED CONCRETE EXPOSED TO EARTH AND WEATHER	#5 & SMALLER	2"	---		#6 & LARGER	1 1/2"	---	CAST IN PLACE ANCHORS - MATERIAL REQUIREMENTS				TYPE	SPECIFICATION	GRADE	REQUIREMENTS WHEN WELDED TO PLATE OR MEMBER	ANCHOR RODS	ASTM F1554	36	---	HOOKED ANCHORS	ASTM F1554	36	---	MATERIAL REQUIREMENTS - SAWN LUMBER				APPLICATION	SUBCATEGORY	WOOD SPECIES	WOOD GRADE	NOTES	WALL PLATES	TOP PLATES	Douglas Fir-Larch	#2	---	WALL PLATES	BOTTOM PLATES	Douglas Fir-Larch	#2	---	STUDS	2x6 OR LARGER	Douglas Fir-Larch	#2	---	MATERIAL REQUIREMENTS - WOOD STRUCTURAL PANELS					APPLICATION	PANEL GRADE	MINIMUM NOMINAL PANEL THICKNESS	SPAN RATING	NOTES
DEAD LOADS (BASED ON SELF WEIGHT OF CONSTRUCTION MATERIALS)																																																																																																																																																																																																																																																																																																									
LOAD CLASSIFICATION	AREA	CONCENTRATED	NOTES																																																																																																																																																																																																																																																																																																						
ROOF	13 PSF	---	---																																																																																																																																																																																																																																																																																																						
LIVE LOADS (BASED ON 2021 INTERNATIONAL BUILDING CODE)																																																																																																																																																																																																																																																																																																									
LOAD CLASSIFICATION	AREA	CONCENTRATED																																																																																																																																																																																																																																																																																																							
ROOFS	20 PSF	---																																																																																																																																																																																																																																																																																																							
SNOW LOADS (BASED ON ASCE 7-16, CHAPTER 7)																																																																																																																																																																																																																																																																																																									
DESIGN VARIABLE	VALUE	NOTES																																																																																																																																																																																																																																																																																																							
GROUND SNOW LOAD	20 PSF	PER MAPS WITHIN THE 2021 IBC																																																																																																																																																																																																																																																																																																							
DESIGN SNOW LOAD	20 PSF	PER MAPS WITHIN THE 2021 IBC																																																																																																																																																																																																																																																																																																							
EXPOSURE FACTOR	1.00	PARTIALLY EXPOSED IN TERRAIN CATEGORY C																																																																																																																																																																																																																																																																																																							
TERMAL FACTOR	1.00	ALL OTHER STRUCTURES																																																																																																																																																																																																																																																																																																							
IMPORTANCE FACTOR	1.00	OCCUPANCY CATEGORY: II																																																																																																																																																																																																																																																																																																							
WIND LOADS (BASED ON ASCE 7-16, CHAPTER 26, THROUGH 30)																																																																																																																																																																																																																																																																																																									
DESIGN VARIABLE	VALUE	NOTES																																																																																																																																																																																																																																																																																																							
3-SECOND WIND SPEED	110 MPH	PER MAPS WITHIN THE 2018 IBC																																																																																																																																																																																																																																																																																																							
EXPOSURE CLASSIFICATION	C	OPEN TERRAIN WITH SCATTERED OBSTRUCTION																																																																																																																																																																																																																																																																																																							
SEISMIC LOADS (BASED ON ASCE 7, CHAPTERS 11 THROUGH 23)																																																																																																																																																																																																																																																																																																									
DESIGN VARIABLE	VALUE	NOTES																																																																																																																																																																																																																																																																																																							
S _s	1.402	SPECTRAL RESPONSE ACCEL. PARAMETER AT SHORT PERIODS																																																																																																																																																																																																																																																																																																							
S ₁	0.501	SPECTRAL RESPONSE ACCEL. PARAMETER AT 1-SECOND PERIOD																																																																																																																																																																																																																																																																																																							
SOIL SITE CLASS	D	PER GEOTECH OR ASCE 7 SECTION COEFFICIENT																																																																																																																																																																																																																																																																																																							
IMPORTANCE FACTOR	1	OCCUPANCY CATEGORY: II																																																																																																																																																																																																																																																																																																							
F _a	1.2	SHORT-PERIOD SITE COEFFICIENT																																																																																																																																																																																																																																																																																																							
F _v	-	1-SECOND PERIOD SITE COEFFICIENT																																																																																																																																																																																																																																																																																																							
S _{ds}	1.122	DESIGN SPECTRAL RESPONSE ACCEL. PARA AT 1-SECOND PERIOD																																																																																																																																																																																																																																																																																																							
S _{d1}	N/A	DESIGN SPECTRAL RESPONSE ACCEL PARA AT 1-SECOND PERIOD																																																																																																																																																																																																																																																																																																							
SEISMIC DESIGN CATEGORY	D	BASED ON 1-SEC AND SHORT PERIOD ACCELERATION PARAMETER																																																																																																																																																																																																																																																																																																							
R	6.5	RESPONSE MODIFICATION COEFFICIENT																																																																																																																																																																																																																																																																																																							
LATERAL FORCE SYSTEM	LIGHT FRAME (WOOD) SHEATHING WOOD STRUCTURAL PANELS RATED FOR SHEAR RESISTANCE																																																																																																																																																																																																																																																																																																								
FOUNDATION DESIGN VALUES AND NOTES PER GEOTECHNICAL REPORT																																																																																																																																																																																																																																																																																																									
PARAMETER	VALUE	VALUE																																																																																																																																																																																																																																																																																																							
ALLOWABLE BEARING PRESSURE	1500 PSF	BEARING DEPTH OF 18"																																																																																																																																																																																																																																																																																																							
CONCRETE MIX REQUIREMENTS																																																																																																																																																																																																																																																																																																									
INTENDED USE	f _c	SLUMP AT PLACEMENT	MAX W/c RATIO	MAX AGGREGATE	AIR ENTRAINMENT																																																																																																																																																																																																																																																																																																				
SPREAD FOOTING & WALL FUNDINGS	3000 PSI	3" TO 5"	---	3/4"	6 ± 1.5																																																																																																																																																																																																																																																																																																				
SLABS ON GRADE (INTERIOR)	3000 PSI	5" TO 7"	---	3/4"	6 ± 1.5																																																																																																																																																																																																																																																																																																				
SLABS ON GRADE (EXTERIOR)	3000 PSI	5" TO 7"	---	3/4"	6 ± 1.5																																																																																																																																																																																																																																																																																																				
CEMENTITIOUS MATERIAL REQUIREMENTS																																																																																																																																																																																																																																																																																																									
CEMENTITIOUS MATERIAL	REFERRED STANDARD	MAXIMUM AMOUNT																																																																																																																																																																																																																																																																																																							
FLY ASH OR OTHER POZZOLANS	ASTM C618	25%																																																																																																																																																																																																																																																																																																							
SLAG	ASTM C989	50%																																																																																																																																																																																																																																																																																																							
SILICA FUME	ASTM C1240	10%																																																																																																																																																																																																																																																																																																							
TOTAL OF FLY ASH, OTHER POZZOLANS, SLAG, AND SILICA FUME	---	50%																																																																																																																																																																																																																																																																																																							
TOTAL OF FLY ASH, OTHER POZZOLANS AND SILICA FUME	---	35%																																																																																																																																																																																																																																																																																																							
REINFORCING BARS - MATERIAL REQUIREMENTS																																																																																																																																																																																																																																																																																																									
BAR TYPES	DESIGNATION	YIELD STRENGTH	NOTES																																																																																																																																																																																																																																																																																																						
#5 BARS AND SMALLER (NON-WELDABLE)	ASTM A615	60 KSI	---																																																																																																																																																																																																																																																																																																						
REQUIREMENTS FOR FIELD BENDING OF REINFORCING BARS																																																																																																																																																																																																																																																																																																									
BAR	INSIDE BEND	REQUIRED WASHINGTON TEMPERATURE RANGE	NOTES																																																																																																																																																																																																																																																																																																						
SIZE	DIAMETER	MINIMUM	MAXIMUM																																																																																																																																																																																																																																																																																																						
#5	8 BAR DIAMETERS	1300°F	1400°F																																																																																																																																																																																																																																																																																																						
CLEAR DISTANCES FOR CONCRETE REINFORCING BARS																																																																																																																																																																																																																																																																																																									
CONDITION	BAR SIZE	CLEAR DISTANCE	NOTES																																																																																																																																																																																																																																																																																																						
CAST AGAINST & PERMANENTLY EXPOSED TO EARTH	ALL	3"	---																																																																																																																																																																																																																																																																																																						
FORMED CONCRETE EXPOSED TO EARTH AND WEATHER	#5 & SMALLER	2"	---																																																																																																																																																																																																																																																																																																						
	#6 & LARGER	1 1/2"	---																																																																																																																																																																																																																																																																																																						
CAST IN PLACE ANCHORS - MATERIAL REQUIREMENTS																																																																																																																																																																																																																																																																																																									
TYPE	SPECIFICATION	GRADE	REQUIREMENTS WHEN WELDED TO PLATE OR MEMBER																																																																																																																																																																																																																																																																																																						
ANCHOR RODS	ASTM F1554	36	---																																																																																																																																																																																																																																																																																																						
HOOKED ANCHORS	ASTM F1554	36	---																																																																																																																																																																																																																																																																																																						
MATERIAL REQUIREMENTS - SAWN LUMBER																																																																																																																																																																																																																																																																																																									
APPLICATION	SUBCATEGORY	WOOD SPECIES	WOOD GRADE	NOTES																																																																																																																																																																																																																																																																																																					
WALL PLATES	TOP PLATES	Douglas Fir-Larch	#2	---																																																																																																																																																																																																																																																																																																					
WALL PLATES	BOTTOM PLATES	Douglas Fir-Larch	#2	---																																																																																																																																																																																																																																																																																																					
STUDS	2x6 OR LARGER	Douglas Fir-Larch	#2	---																																																																																																																																																																																																																																																																																																					
MATERIAL REQUIREMENTS - WOOD STRUCTURAL PANELS																																																																																																																																																																																																																																																																																																									
APPLICATION	PANEL GRADE	MINIMUM NOMINAL PANEL THICKNESS	SPAN RATING	NOTES																																																																																																																																																																																																																																																																																																					

WEST BAKERVIEW - SCHLOSSER - SNOPUD
4822 103RD PL SW MUKILTEO, WA 98275

5.4.2. WOOD TRUSS ENGINEERING REQUIREMENTS
THE TRUSS MANUFACTURER SHALL PROVIDE ENGINEERED DRAWINGS AND CALCULATIONS FOR EACH TRUSS. THE DRAWINGS AND CALCULATIONS ARE TO BE SIGNED AND SEALED BY A REGISTERED STRUCTURAL ENGINEER IN THE STATE OF WASHINGTON.

5.4.3. GENERAL LOADING CRITERIA
THE WOOD TRUSS ENGINEER MAY USE EITHER THE ASD OR LRFD DESIGN PROCEDURE TO DESIGN THE TRUSSES. THE WOOD TRUSS ENGINEER IS TO DESIGN THE TRUSSES FOR THE DEAD LOADS SHOWN IN THE GENERAL STRUCTURAL NOTES, THE LOADS SHOWN IN THE DETAILS, THE LOADS SHOWN ON THE STRUCTURAL PLANS, AND THE LOADS IN DRAWINGS FROM OTHER TRADES (MECHANICAL, PLUMBING, ELECTRICAL & ARCHITECTURAL). ALL OTHER LOADS ARE TO BE DERIVED IN ACCORDANCE WITH THE 2021 IBC.

ALL LOADS SHOWN IN THE STRUCTURAL DRAWINGS ARE SERVICE LEVEL LOADS, WITH THE EXCEPTION OF THE SEISMIC AND WIND LOADS, WHICH ARE AT A STRENGTH LEVEL. THIS IS DONE SO THAT NO MODIFICATIONS NEED TO BE MADE TO THE LOADS BEFORE THEY ARE USED IN EITHER THE ASD OR LRFD LOAD COMBINATIONS OF THE 2021 IBC.

IN ADDITION TO THE LOADS MENTIONED ABOVE, THE WOOD TRUSS ENGINEER IS TO DESIGN THE TRUSSES FOR THE ADD LOADS SHOWN IN THE TABLE BELOW.

TRUSS LOCATION	LOAD TYPE			NOTES
	VERTICAL DEAD LOAD		HORIZONTAL WIND OR SEISMIC TOP CHORD	
	AREA (1)	CONCENTRATED (2)	AXIAL LOAD (3)	
ROOFS	5 PSF	--	300 LBS	--

TABLE NOTES:

- 1) THE AREA LOADS IN THE CHART ABOVE ARE TO BE APPLIED TO THE FULL TRIBUTARY AREA OF EACH TRUSS.
- 2) THE CONCENTRATED LOAD NEED ONLY BE APPLIED AT A SINGLE PANEL POINT (TOP CHORD AND BOTTOM CHORD) AT ANY GIVEN TIME. THE TRUSS IS TO BE DESIGNED TO SUPPORT THIS LOAD IF IT IS APPLIED TO ANY TOP OR BOTTOM CHORD PANEL POINT.
- 3) THE HORIZONTAL AXIAL LOAD IS TO BE APPLIED TO PRODUCE BOTH TENSION OR COMPRESSION IN THE TRUSS. THE LOAD IS TO BE APPLIED AT EACH TRUSS BEARING POINT (NOT SIMULTANEOUSLY). ONLY HALF OF THIS LOAD MAY BE USED FOR FUTURE LOADING.

5.4.4. DEFLECTION LIMITATIONS

WOOD TRUSSES ARE TO BE DESIGNED FOR THE FOLLOWING DEFLECTION LIMITATIONS.

DEFLECTION LIMITATIONS - PREFABRICATED WOOD TRUSSES				
TRUSS LOCATION	TRUSS SUPPORT ELEMENTS	DEFLECTION LIMIT		NOTES
		TOTAL LOAD	LIVE LOAD	
ROOF	SUPPORTING PLASTER CEILING	L/240	L/360	--
	SUPPORTING DRYWALL CEILING	L/180	L/240	--
	NO CEILING	L/120	L/180	--

REFER TO THE ARCHITECTURAL DRAWINGS TO DETERMINE FLOOR COVERING TYPE. DEFLECTION CRITICAL FLOOR COVERINGS INCLUDE, BUT ARE NOT LIMITED TO, CERAMIC TILE, MARBLE, AND STONE.

5.4.5. WOOD TRUSSES - MINIMUM MEMBER REQUIREMENTS
AS A MINIMUM, WOOD TRUSS MEMBERS ARE TO BE 1 1/2" WIDE. THE SPECIFIC GRAVITY OF THE TOP CHORD MEMBERS MUST BE EQUAL TO OR GREATER THAN 0.42.

5.5. WOOD CONNECTIONS - NAILS

5.5.1. REFERENCED STANDARDS - NAILS
ALL NAILS MUST BE MANUFACTURED IN ACCORDANCE WITH AND MEET THE REQUIREMENTS OF ASTM F1667, STANDARD SPECIFICATION FOR DRIVEN FASTENERS: NAILS, SPIKES, AND STAPLES.

5.5.2. WOOD NAILING SCHEDULE
A WOOD NAILING SCHEDULE IS SHOWN IN THE TYPICAL DETAILS FOR THIS PROJECT. REFER TO THIS SCHEDULE FOR REQUIREMENTS FOR TYPICAL NAILED CONNECTIONS, REQUIRED NAIL DIAMETERS AND LENGTHS, AND NAIL TYPES.

5.5.3. NAIL TYPES
WITHIN THESE DRAWINGS, COMMON, BOX, AND SINKER NAILS MAY ALL BE SPECIFIED. UNLESS NOTED OTHERWISE, ALL NAILS SHALL BE COMMON NAILS. IN NO CASE SHALL THE TYPE OF NAIL BE CHANGED FROM WHAT IS SPECIFIED WITHOUT THE PRIOR APPROVAL OF TECHNOLOGY ASSOCIATES.

5.5.4. INSTALLATION REQUIREMENTS
A NAIL THAT SPLITS THE WOOD WILL NOT TAKE THE DESIGN LOAD. IF SPLITTING OCCURS, THE CONTRACTOR IS TO REPLACE THE MEMBER THAT SPLITS AND PRE-DRILL THE HOLES TO PREVENT THE SPLITTING. DRY WOOD MAY SPLIT EASILY EASILY AND SHOULD BE EVALUATED AS REQUIRED.

TOE-NAILS SHALL BE DRIVEN AT AN ANGLE OF APPROXIMATELY 30 DEGREES WITH THE MEMBER AND STARTED APPROXIMATELY 1/8 THE LENGTH OF THE NAIL FROM THE MEMBER END. REQUIRED MINIMUM EDGE DISTANCE, END DISTANCE, AND NAIL SPACING ARE SHOWN IN NDS TABLES 11.5.1A THROUGH 11.5.1D.

6. SHOP DRAWINGS

6.1. GENERAL REQUIREMENTS
TECHNOLOGY ASSOCIATES WILL ONLY REVIEW SHOP DRAWING FOR GENERAL CONFORMANCE WITH THE STRUCTURAL DRAWINGS. THE CONTRACTOR MAY SUBMIT SHOP DRAWINGS FOR REVIEW AT THEIR DISCRETION, UNLESS REQUIRED BY THE AH OR THE PROJECT SPECIFICATIONS. REVIEW OF SHOP DRAWINGS BY TECHNOLOGY ASSOCIATES IS INTENDED AS AN AID ONLY. THE SHOP DRAWINGS DO NOT TAKE THE PLACE OF THE STRUCTURAL DRAWINGS. THE SHOP DRAWINGS SHOULD NOT BE THE SOLE DOCUMENTATION USED BY FIELD PERSONNEL TO CONSTRUCT THE STRUCTURE. TECHNOLOGY ASSOCIATES IS NOT RESPONSIBLE FOR THE OVER ALL ACCURACY OF THE SHOP DRAWINGS.

ALL SHOP DRAWINGS ARE TO BE SUBMITTED ELECTRONICALLY IN PDF FORMAT. NO HARD COPIES WILL BE REVIEWED.

THE CONSTRUCTION DOCUMENTS MAY NOT BE REPRODUCED AS SHOP DRAWINGS AND TECHNOLOGY ASSOCIATES WILL NOT SUPPLY ELECTRONIC BASE FILES TO BE USED AS A STARTING POINT FOR ANY SHOP DRAWINGS.

PRIOR TO SUBMITTING SHOP DRAWINGS TO TECHNOLOGY ASSOCIATES, THE CONTRACTOR IS TO REVIEW, STAMP, INITIAL AND DATE THEM. ANY ITEMS IN CONFLICT SHALL BE FLAGGED BY THE CONTRACTOR FOR REVIEW. ITEMS THAT HAVE CHANGED AND WERE NOT FLAGGED BY THE CONTRACTOR ARE NOT TO BE CONSIDERED OFFICIAL CHANGES TO THE CONTRACT DOCUMENTS. SHOP DRAWINGS NOT REVIEWED PRIOR TO SUBMITTAL WILL BE RETURNED, WITHOUT REVIEW.

ALL ENGINEERING DESIGNS AND CALCULATIONS PROVIDED BY OTHERS AND SUBMITTED FOR REVIEW SHALL BEAR THE SEAL OF THE PROFESSIONAL ENGINEER WHO WAS IN RESPONSIBLE CHARGE OF THEIR CREATION. THE PROFESSIONAL ENGINEER SHALL BE REGISTERED WITHIN THE STATE OF TECHNOLOGY ASSOCIATES WITHIN THE AREAS OF CIVIL OR STRUCTURAL ENGINEERING, OR AS REQUIRED BY THE STATE.

6.2. DEFERRED SUBMITTALS
PLANS AND SPECIFICATIONS FOR DEFERRED SUBMITTAL ITEMS SHALL BE SUBMITTED TO THE DEVELOPMENT SERVICES DEPARTMENT OF THE AH AFTER BEING REVIEWED FOR CONFORMITY WITH THE STRUCTURAL DRAWINGS DESIGN BY TECHNOLOGY ASSOCIATES AND THE CONTRACTOR AND PRIOR TO ERECTION, CONSTRUCTION OR INSTALLATION IN THE FIELD. TECHNOLOGY ASSOCIATES WILL PROVIDE A NOTATION ON ALL DEFERRED DOCUMENTS THAT ACKNOWLEDGES REVIEW OF SUCH DOCUMENTS. A SEPARATE PERMIT FOR THE INSTALLATION OF A DEFERRED ITEM SHALL NOT BE REQUIRED UNLESS SPECIFIED

ALLOWABLE STRUCTURAL ELEMENTS SUBMITTED AS DEFERRED SUBMITTALS		
ITEM	NOTES	
1	PREFABRICATED WOOD TRUSSES	--

7. SPECIAL STRUCTURAL INSPECTION (SSI)

7.1. GENERAL REQUIREMENTS
THE CONTRACTOR IS ENCOURAGED TO SCHEDULE A PRE-CONSTRUCTION CONFERENCE WITH ALL SUBCONTRACTORS, AND TECHNOLOGY ASSOCIATES TO REVIEW THE SSI REQUIREMENTS AND PROCEDURES FOR THIS PROJECT.

SPECIAL STRUCTURAL INSPECTIONS ARE TO BE SCHEDULED A MINIMUM OF 24 HOURS IN ADVANCE. TO SCHEDULE AN SSI, CONTACT THIRD PARTY.

ALL SPECIAL INSPECTIONS ARE TO BE COMPLETED UNDER THE SUPERVISION OF A REGISTERED CIVIL OR STRUCTURAL ENGINEER WITHIN THE STATE OF WASHINGTON. AS A MINIMUM, ALL SPECIAL STRUCTURAL INSPECTORS SHALL BE EITHER ICC CERTIFIED IN THE AREA OF THE INSPECTION, OR SHALL HAVE AN EIT CERTIFICATION WITHIN THE STATE OF TECHNOLOGY ASSOCIATES. THE QUALIFICATIONS FOR THE SPECIAL INSPECTORS SHALL BE REVIEWED AND APPROVED BY TECHNOLOGY ASSOCIATES PRIOR TO CONSTRUCTION.

SPECIAL STRUCTURAL INSPECTIONS DO NOT TAKE THE PLACE OF ANY OTHER INSPECTIONS REQUIRED BY THE AHJ, AND/OR BY CHAPTER 1 OF THE 2021 IBC.

7.2. REQUIREMENTS OF THE SPECIAL STRUCTURAL INSPECTOR
THE SPECIAL STRUCTURAL INSPECTOR SHALL OBSERVE ALL WORK REQUIRING SSI FOR COMPLIANCE WITH THE APPROVED DESIGN DRAWINGS AND SPECIFICATIONS. THE INSPECTOR SHALL FURNISH REPORTS FOR EACH INSPECTION TO THE CONTRACTOR, ARCHITECT, OWNER, AND AHJ. ALL REPORTS SHALL BE SUBMITTED NO MORE THAN 24 HOURS AFTER THE INSPECTION.

TECHNOLOGY ASSOCIATES SHALL BE IMMEDIATELY NOTIFIED OF ALL DISCREPANCIES AND DEVIATIONS FOUND DURING THE INSPECTION.

7.3. ITEMS AND MATERIALS REQUIRING SPECIAL STRUCTURAL INSPECTION
ALL SPECIAL STRUCTURAL INSPECTION IS TO BE PERFORMED IN ACCORDANCE WITH THE PROVISIONS OF IBC, CHAPTER 17, AND THE REQUIREMENTS OF THE AHJ. THE FOLLOWING ITEMS AND MATERIALS REQUIRE SPECIAL STRUCTURAL INSPECTION.

THE FREQUENCY OF THE SPECIAL STRUCTURAL INSPECTIONS ARE CLASSIFIED AS EITHER CONTINUOUS OR PERIODIC. CONTINUOUS INSPECTIONS REQUIRE THE FULL-TIME OBSERVATION OF WORK, WHILE PERIODIC INSPECTIONS REQUIRE PART-TIME, OR INTERMITTENT OBSERVATION OF WORK. TO FURTHER CLARIFY PERIODIC, A PERCENTAGE IS SHOWN NEXT TO EACH INSPECTION ITEM. THIS PERCENTAGE REPRESENTS THE REQUIRED PERCENTAGE OF THE WORK THAT NEEDS TO BE OBSERVED. IT IS THE RESPONSIBILITY OF THE CONTRACTOR TO ENSURE THIS MINIMUM PERCENTAGE IS MET OR EXCEEDED.

ONLY ITEMS REQUIRING SPECIAL STRUCTURAL INSPECTION HAVE BEEN LISTED HEREIN. OTHER INSPECTIONS, INCLUDING, BUT NOT LIMITED TO, GEOTECHNICAL INSPECTIONS, FIRE RELATED INSPECTIONS, MECHANICAL, PLUMBING, AND ELECTRICAL INSPECTIONS ARE TO BE PERFORMED BY OTHERS.

CONCRETE CONSTRUCTION (2021 IBC TABLE 1705.3 & 1705.12.1)

FIRM	VERIFICATION AND INSPECTIONS	FREQUENCY	NOTES
THIRD PARTY	REINFORCING STEEL AND TENDONS	50%	VERIFY PRIOR TO PLACING CONCRETE THAT REINFORCING IS OF SPECIFIED TYPE, GRADE AND SIZE; THAT IT IS FREE OF OIL, DIRT AND RUST; THAT IT IS LOCATED AND SPACED PROPERLY; THAT HOOKS, BENDS, TIES, STIRRUPS AND SUPPLEMENTAL REINFORCEMENT ARE PLACED CORRECTLY; THAT LAP LENGTHS, STAGGERS AND OFFSETS ARE PROVIDED; AND THAT ALL MECHANICAL CONNECTIONS ARE INSTALLED PER THE MANUFACTURER'S INSTRUCTIONS AND/OR EVALUATION REPORTS.
THIRD PARTY	CAST-IN-PLACE BOLTS, RODS AND EMBEDMENT	50%	INSPECTION OF ANCHORS OR EMBEDMENT CAST IN CONCRETE
THIRD PARTY	PLACEMENT OF CONCRETE	100%	INSPECT PLACEMENT PROCEDURES INCLUDING CONSOLIDATION, MAINTENANCE OF REINFORCING LOCATION, AND MAINTENANCE OF ALL CLEAR DISTANCES

SPECIAL CASES

FIRM	VERIFICATION AND INSPECTIONS	FREQUENCY	NOTES
THIRD PARTY	POST INSTALLED ANCHORS	100%	CONTINUOUS INSPECTION OF HOLE DIAMETER, SIZE, SPACING, AND CLEARANCE. MANUFACTURER CONTINUOUS INSPECTION OF SIZE, LENGTH, AND SPACING OF ANCHORS. CONTINUOUS INSPECTION OF INSTALLATION OF EPOXY ADHESIVE ANCHORS, EXPANSION ANCHORS, AND SCREW ANCHORS.

TAG LEGEND

WF1	WALL FOOTING - SEE SCHEDULE THIS SHEET.
H1	WOOD HEADER - SEE SCHEDULE THIS SHEET.
TA 10-0"	SHEAR WALL - SEE SCHEDULE THIS SHEET.
△	SHEAR WALL HOLDOWN - SEE SCHEDULE THIS SHEET.

SHEET NAME:

GENERAL
STRUCTURAL
NOTES

DATE: 03.07.2025


DRAWN BY: TV

CHECKED BY: MKS

PROJECT NUMBER: SE01458B

SHEET NUMBER: S0.1

ISSUE RECORD / REVISION:
PURPOSE: _____
DATE: _____

SEAL:


PLANS PREPARED BY:
Technology & Associates
SEATTLE MARKET OFFICE
9725 3RD AVENUE NE, STE. 410
SEATTLE, WA 98115

WEST BAKERVIEW - SCHLOSSER - SNOPUD
4822 103RD PL SW MUKILTEO, WA 98275

WOOD NAILING SCHEDULE					
DESCRIPTION OF BUILDING ELEMENT	NUMBER, TYPE, & SPACING OF NAILS		LOCATION		
	COMMON NAILS	BOX NAILS			
ROOF					
BLOCKING BETWEEN CEILING RAFTERS OR RAFTERS TO TOP PLATE	(3) 16d	(3) 16d	AT EACH END, TOENAIL		
CEILING RAFTER TO TOP PLATE	(3) 16d	(3) 16d	PER RAFTER, TOENAIL		
CEILING RAFTER NOT ATTACHED TO PARALLEL RAFTER, LAPS OVER PARTITIONS (NO THRUST)	(3) 16d	(4) 10d	FACE NAIL		
COLLAR TIE TO RAFTER	(3) 10d	(4) 10d	FACE NAIL		
RAFTER OR ROOF TRUSS TO TOP PLATE	(3) 16d	(3) 16d	TOENAIL		
ROOF RAFTERS TO RIDGE VALLEY OR HIP RAFTERS OR ROOF RAFTERS TO 2 INCH RIDGE BEAM	(2) 16d	(3) 10d	END NAIL		
	(3) 16d	(3) 16d	TOENAIL		
WALLS					
STUD TO STUD (NOT AT SHEAR WALLS)	16d@24" O.C.	16d@24" O.C.	FACE NAIL		
STUD TO STUD AND ABUTTING STUD AT INTERSECTING WALLS (AT SHEAR WALLS)	16d@16" O.C.	16d@12" O.C.	FACE NAIL		
BUILT-UP HEADER (2-INCH TO 2-INCH HEADER)	16d@16" O.C.	16d@12" O.C.	EACH EDGE, FACE NAIL		
CONTINUOUS HEADER TO STUD	(4) 16d	(4) 16d	TOENAIL		
TOP PLATE TO TOP PLATE	16d@16" O.C.	10d@12" O.C.	FACE NAIL		
			FACE NAIL ON EACH SIDE OF END JOINTS (MINIMUM 24" LAP SPACES LENGTH EACH SIDE OF END RAFTER)		
TOP PLATE TO TOP PLATE AT END JOINTS	(8) 16d	(12) 10d			
BOTTOM PLATE TO RAFTER, RIM RAFTER BAND RAFTER OR BLOCKING (NOT AT SHEAR WALLS)	16d@16" O.C.	16d@12" O.C.	FACE NAIL		
BOTTOM PLATE TO RAFTER, RIM RAFTER BAND RAFTER OR BLOCKING AT SHEAR WALLS	(2) 16d@16" O.C.	(3) 16d@16" O.C.	FACE NAIL		
STUD TO BOTTOM PLATE (USE EITHER OPTION)	(4) 16d	(4) 16d	TOENAIL		
OR: (2) 16d	OR: (3) 10d	END NAIL			
TOP OR BOTTOM PLATE TO STUD	(2) 16d	(3) 10d	END NAIL		
TOP PLATES, LAP AT CORNERS AND INTERSECTIONS	(2) 16d	(3) 10d	FACE NAIL		




STANDARD COMMON BOX SINKER STEEL WIRES NAILS							
TYPE	PENNYWEIGHT						
	6d	8d	10d	12d	16d	20d	
COMMON	L D H	2" 0.113" 0.266"	2 1/2" 0.131" 0.281"	3" 0.148" 0.312"	3 1/4" 0.148" 0.312"	3 1/2" 0.162" 0.344"	4" 0.192" 0.406"
	L D H	2" 0.099" 0.266"	2 1/2" 0.113" 0.297"	3" 0.128" 0.312"	3 1/4" 0.128" 0.312"	3 1/2" 0.135" 0.344"	4" 0.148" 0.375"
	L D H	1 7/8" 0.092" 0.234"	2 3/8" 0.113" 0.266"	3" 0.12" 0.281"	3 1/4" 0.135" 0.312"	3 1/2" 0.148" 0.344"	4" 0.177" 0.375"

NOTES:


1. THIS IS AN ABRIDGED VERSION OF THE NAILING SCHEDULE PRESENTED IN IBC TABLE 2304.10.1. REFER TO THE IBC TABLE FOR ADDITIONAL REQUIREMENTS NOT SHOWN HERE.
2. REFER TO ASTM F1667 FOR NAIL DIMENSIONAL TOLERANCES.
3. POWER-DRIVEN NAILS MAY BE USED AT CONTRACTOR'S OPTION AND SHALL BE PER ICC ESR-1539. THE MINIMUM DIMENSIONS SHOWN HERE MUST BE MAINTAINED.

17 WOOD NAILING SCHEDULE

S1.1 NOT TO SCALE




NOTE:
1. SEE GSN FOR ADDITIONAL INFORMATION ON SHEATHING AND NAILS NOT SHOWN HERE.
2. LONG DIMENSION OF SHEATHING PANEL IS TO BE ORIENTED PERPENDICULAR TO FRAMING.
3. WHERE SHEAR WALL THK. CHANGES, PROVIDE SHEATHING AT FLAT SIDE WHERE BOTH WALL SURFACE ALIGN




11 WOOD SHEAR WALL CONSTRUCTION

S1.1 NOT TO SCALE




15 TYPICAL WOOD STUD WALL

S1.1 NOT TO SCALE



16 PLYWOOD SHEAR PANEL

S1.1 NOT TO SCALE



NOTE:
EITHER SPLICE OPTION MAY BE USED AT CONTRACTOR'S OPTION UNLESS NOTES OTHERWISE

13 TYPICAL WOOD TOP CHORD SPLICE

S1.1 NOT TO SCALE

SHEET NAME: _____

TYPICAL DETAILS

DATE: **03.07.2025**

DRAWN BY: **TV**

CHECKED BY: **MKS**

PROJECT NUMBER: **SE01458B**

SHEET NUMBER: **S1.1**

SEAL:




PLANS PREPARED BY:

Technology Associates


SEATTLE MARKET OFFICE
9725 3RD AVENUE NE, STE. 410
SEATTLE, WA 98115

WEST BAKERVIEW - SCHLOSSER - SNOPUD

4822 103RD PL SW MUKILTEO, WA 98275



FOUNDATION PLAN
SCALE: 3/8" = 1'-0"



ROOF FRAMING PLAN
SCALE: 3/8" = 1'-0"

WOOD STUD SHEAR WALL () SCHEDULE				
LEADING NUMBER: SHEATHING MATERIAL, ATTACHMENT, AND BASE CONNECTION				* INDICATED SHEATHING IS TO BE APPLIED TO BOTH SIDES OF WALL
FIRST LETTER: HOLDOWN AT EACH END OF WALL (DASH (-) DENOTES NO HOLDOWN REQUIRED)				8'-0"
SHEAR WALL LENGTH				
SHEAR WALL TAG KEY				
NOTES: 1. FOR ADDITIONAL INFORMATION, SEE DETAILS 103/S3.0. 2. ▲ WHERE SHOWN ON PLANS INDICATED HOLDOWN PER SCHEDULE BELOW.				
SHEATHING AND BASE CONNECTION REQUIREMENTS				
TAG	SHEATHING MATERIAL	SHEATHING ATTACH.	SILL PLATE ATTACHMENT AT	
EDGE	FIELD	FOUNDATIONS (4)(S)	UPPER FLOORS	
1	3/8" UNBLOCKED	8d AT 6" O.C.	8d AT 12" O.C.	1/2" ANCHOR BOLT AT 32" O.C.
HOLDOWN REQUIREMENTS				
TAG	MODEL	FASTENERS	ANCHOR BOLTS	MINIMUM POST REQUIREMENTS REFERENCED DETAIL
A	LSTHD8	(20) 0.148x3 1/4	8" EMBED (CAST-IN PLACE)	(2) 2xWIDTH OF WALL SEE DETAIL 103/S3.0
NOTES: (1) VALUES ARE FOR SHEATHING ON ONE SIDE DOUG FIR FRAMED WALLS. DOUBLE VALUE IF SHEATHING ON BOTH SIDES. FOR SHEAR WALLS WITH SHEATHING APPLIED TO BOTH SIDES, SILL PLATE ATTACHMENT SPACING SHALL BE HALF THE SPACING SHOWN. (2) FRAMING AT ADJOINING PANEL EDGES SHALL BE 3" NOMINAL OR WIDER AND NAILS SHALL BE STAGGERED. (3) WHERE PLYWOOD IS APPLIED ON BOTH FACES OF WALL AND NAIL SPACING IS LESS THAN 6" O.C., PANEL JOINTS SHALL BE OFFSET TO FALL ON DIFFERENT FRAMING MEMBERS, OR FRAMING SHALL BE 3 INCH NOMINAL OR THICKER AND NAILS ON EACH SIDE SHALL BE STAGGERED. (4) SHOT PIN OPTION NOT ALLOWABLE AT EXTERIOR WALLS. SHOT PINS SHALL BE HILTI X-U INSTALLED WITH WASHERS AND 1" EMBEDMENT PER ESR-2269. (5) CAST-IN-PLACE ANCHOR BOLTS MAY BE REPLACED WITH 1/2" DIA EXPANSION BOLTS AT SAME SPACING AT INTERIOR WALLS ONLY. EXPANSION BOLTS SHALL BE HILTI KWIK BOLT 3 WITH 4" EMBED - ESR #2302 (6) STAGGER NAILS IN SILL PLATE.				
SHEAR WALL NOTES:				
1. STUD SPACING IN ALL SHEAR WALLS SHALL NOT EXCEED 16" O.C. 2. ALL PANEL EDGES SHALL BE BACKED WITH MINIMUM 2 INCH NOMINAL FRAMING. 3. BLOCKING SHALL BE PROVIDED NEAR MID-HEIGHT OF WALL AT SHEATHING JOINT. 4. SPACING APPLIES TO NAILING AT ALL STUDS, TOP AND BOTTOM PLATES AND BLOCKING. 5. SEE ARCHITECTURAL DRAWINGS FOR ADDITIONAL (FINISHED SURFACE) WALL COVERINGS NOT NOTED. 6. TYPE X DRYWALL SHALL BE PROVIDED WHERE INDICATED ON ARCHITECTURAL DWGS. 7. FOR EXTERIOR SHEAR WALLS USING DRYWALL, USE EXTERIOR TYPE DRYWALL PER ARCHITECTURAL DRAWINGS. 8. "ANCHOR BOLT SHALL HAVE A STEEL PLATE WASHER UNDER EACH NUT NOT LESS THAN 0.229x3x3" IN SIZE. THE PLATE WASHER SHALL EXTEND WITHIN 1/2" OF EDGE OF BOTTOM PLATE ON THE SIDE(S) WITH SHEATHING OR OTHER MATERIAL PER 2015 SDPWS 4.3.6.4.3". 9. GYPSUM SHEATHING SHALL CONFORM TO ASTM C 1396 AND SHALL BE INSTALLED IN ACCORDANCE WITH ASTM C 840. 10. GYPSUM WALLBOARD TO BE APPLIED HORIZONTALLY OR VERTICALLY. END JOINTS OF ADJACENT COURSES OF GYPSUM WALLBOARD INSTALLED WITH THE LONG DIMENSION PERPENDICULAR TO FRAMING, SHALL BE STAGGERED. GYPSUM SHEATHING TO GO OVER SILL PLATES AND DOUBLE TOP PLATES COMPLETELY				

FOUNDATION NOTES - TYP U.N.O.				
1. VERIFY ALL DIMENSIONS AND ELEVATIONS WITH THE ARCHITECTURAL DRAWINGS AND FIELD CONDITIONS. BUILDING DIMENSIONS AND ELEVATIONS, WHERE SHOWN, WERE PROVIDED BY THE ARCHITECT AND IT IS THE CONTRACTOR'S RESPONSIBILITY TO VERIFY AND COORDINATE ALL DIMENSIONS PRIOR TO PROCEEDING WITH THE WORK. ANY DISCREPANCIES SHALL BE RESOLVED THROUGH THE ARCHITECT.				
2. SCHEDULED TAG DESIGNATIONS ARE TYPICAL TO THE PROJECT AND MAY NOT NECESSARILY BE FOUND ON THIS PLAN.				
3. UNLESS NOTED OTHERWISE ON PLANS AND/OR DETAILS, DEPTH OF FOOTING DIMENSIONS INDICATED IN THE G.S.N. ARE MINIMUMS. FOUNDATION CONTRACTOR SHALL COORDINATE WITH SOIL REPORT AND ALL TRADES TO INSURE THAT THESE MINIMUMS ARE SUFFICIENT FOR THE WORK. SEE TYPICAL DETAILS FOR ADDITIONAL REQUIREMENTS.				
4. BUILDING CONCRETE SLAB ON GRADE SHALL BE AS NOTED ON PLAN. VERIFY EXACT SIZE AND LOCATION OF DEPRESSED AND/OR RAISED SLABS WITH ARCHITECTURAL DRAWINGS. FOR SIDEWALK LOCATION, SEE ARCHITECTURAL DRAWINGS. FOR ADDITIONAL INFORMATION, SEE G.S.N. AND TYPICAL DETAILS.				
ROOF FRAMING NOTES - TYP U.N.O.				
1. VERIFY ALL DIMENSIONS AND ELEVATIONS WITH THE ARCHITECTURAL DRAWINGS AND FIELD CONDITIONS. BUILDING DIMENSIONS AND ELEVATIONS, WHERE SHOWN, WERE PROVIDED BY THE ARCHITECT AND IT IS THE CONTRACTOR'S RESPONSIBILITY TO VERIFY AND COORDINATE ALL DIMENSIONS PRIOR TO PROCEEDING WITH THE WORK. ANY DISCREPANCIES SHALL BE RESOLVED THROUGH THE ARCHITECT.				
2. SCHEDULED TAG DESIGNATIONS ARE TYPICAL TO THE PROJECT AND MAY NOT NECESSARILY BE FOUND ON THIS PLAN.				
3. FOR CLARITY, DETAILS MAY SHOW ONLY ONE SIDE OF FRAMING CONDITIONS. ALL OPENINGS MAY NOT BE SHOWN ON THIS PLAN. FOR EXACT SIZE, NUMBER AND LOCATION OF OPENINGS, SEE ARCHITECTURAL, MECHANICAL, PLUMBING, ELECTRICAL, SPRINKLER AND THEIR RELATED DRAWINGS. FOR FRAMING AT OPENINGS, SEE TYPICAL DETAILS.				


WALL TYPE LEGEND				
	WOOD STUD WALL - 2 x WIDTH OF WOOD STUD WALL WITH STUDS SPACED AT 16" O.C. FOR HEADERS IN WOOD STUD WALLS, SEE SCHEDULE - TYPICAL U.N.O. SEE G.S.N. PLANS, AND DETAILS FOR ADDITIONAL INFORMATION. WALLS ONLY SHOW HATCHING WHEN CONTINUOUS TO LEVEL ABOVE.			
	WOOD STUD SHEAR WALL - SEE WOOD STUD SHEAR WALL SCHEDULE THIS SHEET. WALLS ONLY SHOW HATCHING WHEN CONTINUOUS TO LEVEL ABOVE.			
	STRUCTURAL BEARING AND / OR SHEAR WALL BELOW			

WALL FOOTING (WF) SCHEDULE				
TAG	DIMENSIONS		FOOTING REINFORCING	
WF1	HEIGHT	WIDTH	LONGITUDINAL	TRANSVERSE
	1'-0"	1'-4"	2 #5 AT BOTTOM	--
NOTES: 1. FOOTING REINFORCING SHALL BE PLACED AT THE BOTTOM (3" CLR) OF THE FOOTING U.N.O. 2. FOOTING SHALL BE EXTENDED 12" MINIMUM BEYOND WALL ENDS, U.N.O. 3. REFER TO G.S.N. FOR FOUNDATION DEPTH REQUIREMENTS. DEPTH SHOWN IS A MINIMUM. CONTRACTOR SHALL COORDINATE FOUNDATION DEPTH WITH REQUIREMENTS FROM OTHER TRADES. 4. COLUMN IS TO BE CENTERED ON FOOTING, U.N.O.				

HEADER (H) SCHEDULE				
TAG	SIZE	JAMB STUDS	KING STUDS	REMARKS
H1	(2)2x6	2x6	2x6	-

SHEET NAME: _____
FOUNDATION AND ROOF FRAMING PLAN
DATE: 03.07.2025
DRAWN BY: TV
CHECKED BY: MKS
PROJECT NUMBER: SE01458B
SHEET NUMBER: S2.0


ISSUE RECORD / REVISION:
PURPOSE: _____
DATE: _____

SEAL:



PLANS PREPARED BY:
Technology & Associates
 SEATTLE MARKET OFFICE
 9725 3RD AVENUE NE, STE. 410
 SEATTLE, WA 98115

WEST BAKERVIEW - SCHLOSSER - SNOPUD


4822 103RD PL SW MUKILTEO, WA 98275



201 WOOD TRUSS AT WOOD STUD WALL (PERPENDICULAR)
S3.0 NOT TO SCALE




101 EXTERIOR WALL FOOTING AT OPENING
S3.0 NOT TO SCALE



202 WOOD TRUSS AT WOOD STUD WALL (PARALLEL)
S3.0 NOT TO SCALE

102 WOOD STUD WALL AT CONCRETE FOOTING
S3.0 NOT TO SCALE



NOTE:
 A. HOLDOWN ANCHOR IS TO BE FULLY INSTALLED IN THE CONCRETE STEM
 WALL AS SHOWN. CONCRETE FOOTING MAY NEED TO BE LOCALLY SET
 LOWER THAN ADJACENT FOOTING TO ALLOW FOR FULL ANCHOR LENGTH
 TO BE INSTALLED IN THE STEM WITH THE CLEARANCES SHOWN
 #5 BAR - 24" LONG.

103 SHEARWALL HOLDOWN AT CONCRETE FOOTING
S3.0 NOT TO SCALE



SHEET NAME:
**FOUNDATION AND ROOF
FRAMING DETAILS**

DATE: **03.07.2025**
 DRAWN BY: **TV**
 CHECKED BY: **MKS**
 PROJECT NUMBER: **SE01458B**
 SHEET NUMBER: **S3.0**

T Mobile

19807 NORTH CREEK PKWY N
BOTHELL, WA 98011

LANDLORD SIGNATURE



Notes:
 1- Shrubs shall be of quality prescribed in the root observations detail and specifications.
 2- See specifications for further requirements related to this detail.

SHRUB PLANTING DETAIL

NO SCALE

PLANT SCHEDULE

SYMBOL	QTY.	SCIENTIFIC NAME	COMMON NAME	SIZE / COMMENTS
SHRUBS	1	ACER P. VAR. DISSECTUM 'RED DRAGON'	RED DRAGON LACELEAF JAPANESE MAPLE	5 GAL., AS NOTED
	4	CORNUS STOLONIFERA 'ARCTIC FIRE'	ARCTIC FIRE REDTWIG DOGWOOD	5 GAL., 5' O.C.
	4	HOSTA SIEBOLDIANA 'HALCYON'	HALCYON BLUE HOSTA	1 GAL., 36" O.C.
	5	HYDRANGEA M. 'ANNABELLE'	WHITE ANNABELLE HYDRANGEA	5 GAL., 4' O.C.
	8	HAKONECHLOA MACRA 'AUREOLA'	GOLDEN JAPANESE FOREST GRASS	1 GAL., 30" O.C.
	6	RHODY SP. 'DORA AMATEIS'	DORA AMATEIS RHODY	5 GAL., 4' O.C.
	1	SPIREA JAPONICA 'GOLDMOUND'	GOLDMOUND SPIREA	2 GAL., 4' O.C.
	3	THUJA O. 'EMERALD GREEN'	EMERALD GREEN ARBORVITAE	6' HT. BB, 3' O.C.

IRRIGATION NOTE:

1. ALL NEW PLANTINGS WILL BE WATERED BY HAND OR WITH SOAKER HOSES BY THE HOMEOWNER.
2. APPLICANT WILL CONTRACT WITH A LANDSCAPE MAINTENANCE COMPANY TO WATER THE NEW PLANTINGS UNTIL THEY ARE FULLY ESTABLISHED.
3. LANDSCAPE CONTRACTOR WILL MONITOR WATER NEEDS AND MAINTAIN REQUIRED PLANTINGS.

LANDSCAPE NOTES:

CONTRACTORS NOTES:

1. THIS IS NOT A FORMAL SURVEY. PROPERTY INFORMATION CONTAINED HEREIN, CALCULATED FROM OWNERS DOCUMENTS, CITY RECORDS, & ON SITE OBSERVATIONS.
2. ALL CONSTRUCTION CONTRACTS SHALL BE BETWEEN HOMEOWNER AND CONTRACTOR EXCLUSIVELY.
3. PROJECT MANAGER, ACTS AS AGENT FOR OWNER AND IS NOT RESPONSIBLE FOR PAYMENT TO CONTRACTORS.
4. CONTRACTOR OR OWNER MUST VERIFY ON SITE DIMENSIONS PRIOR TO PURCHASE OF MATERIALS OR CONSTRUCTION, AND INFORM OWNER OR LANDSCAPE ARCHITECT OF DISCREPANCIES.
5. CONTRACTOR SHALL BE RESPONSIBLE FOR LOCATION AND PROTECTION OF ALL UNDERGROUND UTILITIES AND SHALL ACCEPT FULL RESPONSIBILITY DUE TO NEGLIGENCE.
6. CONTRACTOR SHALL BE FULLY RESPONSIBLE FOR STRUCTURAL INTEGRITY AND DURABILITY OF ALL ARCHITECTURAL AND LANDSCAPE CONSTRUCTION.
7. ALL CONSTRUCTION SHALL MEET BUILDING CODES AS THEY APPLY.
8. OWNER SHALL BE RESPONSIBLE FOR OBTAINING ALL REQUIRED PERMITS AND PAYING ALL PERMIT FEES. LANDSCAPE ARCHITECT WILL ASSUME OWNER HAS OBTAINED ALL PERMITS UNLESS SPECIFICALLY INSTRUCTED BY OWNERS TO OBTAIN PERMITS ON THEIR BEHALF.
9. CONTRACTOR SHALL ENSURE PROPER DRAINAGE FOR ALL LANDSCAPE AREAS. FINISH GRADES SHALL MEET EXISTING GRADES AND PROMOTE POSITIVE DRAINAGE.
10. ALL SALVAGEABLE MATERIALS AND ITEMS SHALL REMAIN PROPERTY OF OWNER.
11. ALL CONCRETE FORM WORK SHALL BE INSPECTED BY OWNER OR LANDSCAPE ARCHITECT PRIOR TO POUR.

PLANTING NOTES

12. PLANT ALL SHRUBS AND TREES WITH A MINIMUM 6" TOPSOIL MIX AROUND ROOT BALL. MIX TOPSOIL 50% WITH EXISTING SOIL.
13. USE THREE WAY OR BETTER FOR ALL IMPORTED TOPSOIL.
14. COVER ALL PLANT BEDS WITH 3" BLACK FINE BARK MULCH.
15. SPREAD PREEN OR MIRACLE GROW WEED AND FEED HERBICIDE WITH TRIFLUORINE PER MANUFACTURES SPECIFICATIONS, ONLY IN PLANT BEDS. APPLY PREEN AFTER PLANTING AND PRIOR TO APPLICATION OF MULCH, AND AGAIN TO TOP SURFACE AFTER APPLYING MULCH.
16. ALL PLANT MATERIAL SHALL BE AVAILABLE ON SITE FOR INSPECTION BY OWNER OR PROJECT MANAGER PRIOR TO PLANTING.
17. EXISTING PLANTS SHALL BE SAVED WHENEVER PRACTICAL, AND REINCORPORATED INTO THE LANDSCAPE.
18. NO SUBSTITUTION FOR PLANT MATERIAL SHALL BE ALLOWED WITHOUT WRITTEN PERMISSION FROM LANDSCAPE ARCHITECT.
19. ALL PLANT MATERIAL SHALL BE FREE OF PEST AND DISEASES AND WITHOUT DAMAGE TO ROOT OR FOLIAGE.
20. ALL PLANT PLACEMENT SHALL BE INSPECTED BY LANDSCAPE ARCHITECT PRIOR TO PLANTING.
21. PROVIDE 48 HOUR NOTICE FOR INSPECTIONS.

SOD LAWN NOTES

22. SET ROUGH GRADES WITHIN 2"-4" OF FINISH GRADE.
23. SPREAD 4" THREE WAY MIX TOPSOIL OR BETTER, OVER LAWN BED AREA.
24. APPLY DOLOMITE LIME AT RATE OF 50 LBS. PER 1000 S.F.
25. TILL TO A DEPTH OF 6"-8". FLOAT AND RAKE FREE OF DEBRIS LARGER THAN 1" IN DIA.
26. ROLL WITH 200 LB. ROLLER TWO DIRECTIONS. LIGHTLY RAKE SURFACE.
27. LAY SOD CROSS SLOPE, WITH STAGGERED JOINTS. ROLL SET SOD WITH 200 LB. ROLLER TWO DIRECTIONS.
28. USE COUNTRY GREEN, PREMIUM SOD OR EQ. WITH MINIMUM 60% PERENNIAL RYE GRASS AND 20% CREEPING FESCUE MIX.
29. SOD SHALL BE LAID WITHIN 48 HOURS OF DELIVERY AND BE HEALTHY AND MOIST AT TIME OF DELIVERY.

LAWN SEED MIX NOTES

30. SET ROUGH GRADE WITHIN 2" OF FINISH GRADE.
31. SPREAD 4" THREE WAY MIX TOPSOIL OR BETTER, OVER LAWN BED AREA.
32. APPLY DOLOMITE LIME AT RATE OF 50 LBS. PER 1000 S.F. AND TILL TO A DEPTH OF 6"-8" OVER ALL DISTURBED AREAS.
33. FLOAT AND RAKE FREE OF DEBRIS LARGER THAN 1".
34. ROLL WITH 200 LB. ROLLER, TWO DIRECTIONS. LIGHTLY RAKE SURFACE.
35. HYDROSEED WITH FESCUE, BENTGRASS, BLUEGRASS ESTATE SHADE MIX, OR EQ.
36. APPLY AT RATE OF 12 LBS. SEED PER 1000 S.F. APPLY WITH GROUND TEMP. ABOVE 55 DEGREES F., AND NO LATER THAN OCTOBER 15TH.

PLANS PREPARED BY:

SUMMIT LANDSCAPE ARCHITECTURE
 LEE OHLE, PLA
 WA STATE LANDSCAPE ARCHITECT #20115231

CALL DIAL-A-DIG
 AT 1-800-424-5555

A MINIMUM OF 48 HOURS
 BEFORE CONSTRUCTION BEGINS



PLANS PREPARED BY:

Technology Associates

SEATTLE MARKET OFFICE
 1455 NW LEARY WAY, STE. 400
 SEATTLE, WA 98107

JURISDICTION APPROVAL SEAL:



DRAWING NOTICE:
 THESE DOCUMENTS ARE CONFIDENTIAL
 AND ARE THE SOLE PROPERTY OF
 T-MOBILE AND MAY NOT BE REPRODUCED,
 DISSEMINATED OR REDISTRIBUITED
 WITHOUT THE EXPRESS WRITTEN
 CONSENT OF T-MOBILE.

REVISIONS:	DESCRIPTION	DATE	BY	REV
ISSUED FOR 90% CD		07/30/2025	MGM	A

SITE NAME:
 WEST BAKERVIEW -
 SCHLOSSER - SNOPUDSITE NUMBER:
 SE01458BSITE ADDRESS:
 4822 103RD PL SW
 MUKILTEO, WA 98275SHEET DESCRIPTION:
 LANDSCAPE PLAN

SHEET NUMBER:

PLANS PREPARED FOR: —

T Mobile

19807 NORTH CREEK PKWY N
BOTHELL, WA 98011

PLANS PREPARED BY: —

Technology Associates

SEATTLE MARKET OFFICE
1455 NW LEARY WAY, STE. 400
SEATTLE, WA 98107

JURISDICTION APPROVAL S



DRAWING NOTICE: THESE DOCUMENTS ARE CONFIDENTIAL AND ARE THE SOLE PROPERTY OF T-MOBILE AND MAY NOT BE REPRODUCED, DISSEMINATED OR DISTRIBUTED WITHOUT THE EXPRESS WRITTEN CONSENT OF T-MOBILE.

SITE NAME: WEST BAKERVIEW -
SCHLOSSER, SNOPLUR

SITE ADDRESS: 4822 103RD PL SW
MIKILTEO, WA 98275

SHEET DESCRIPTION: —

**TREE RETENTION
SITE PLAN**

SHEET NUMBER: _____

NOTE: THE ORIGINAL SIZE OF THIS PLAN IS 24" X 36". SCALE RATIO IS NOT VALID FOR REDUCED OR ENLARGED SHEET SIZES

PLANS PREPARED BY:

SUMMIT LANDSCAPE ARCHITECTURE
LEE OHLDE, PLA
WA STATE LANDSCAPE ARCHITECT #20115231

**CALL DIAL-A-DIG
AT 1-800-424-5555**

A MINIMUM OF 48 HOURS
BEFORE CONSTRUCTION BEGINS

TREE RETENTION SITE PLAN


10'	0'	5'	10'	SCALE: 1" = 10'-0" (24x36)	
				(OR) 1/2" = 10'-0" (11x17)	

L2.0

T Mobile®

SE01458B
WEST BAKERVIEW - SCHLOSSER - SNOPUD
4822 103RD PL SW
MUKILTEO, WA 98275

Technology  Associates



AERIAL MAP

